



**NI 43-101 Technical Report  
On the Monster Lake South property**

**Hazeur Township  
N.T.S. 32G07  
Québec (Canada)**

**Prepared for  
Cannabix Technologies Inc.  
Formerly named  
West Point Resources Inc.**

**By  
Jeannot Théberge P.Geo  
TERRAX MANAGEMENT INC.**

**January 5<sup>th</sup> 2015**

## **1 Summary**

Terrax Management (“Terrax”) was contracted on August 8<sup>th</sup> 2014 by West Point Resources Inc. (“West Point”), to complete a Technical Report (“the report”) for the Monster Lake South property (“the property”) in Québec, Canada, in compliance with National Instrument 43-101 and Form 43-101F1. The report is addressed to Cannabix Technologies Inc., (formerly named West Point Resources Inc.), a Canadian company listed on the Canadian Securities.

The property is located about 60 km south-west of the town of Chibougamau in the Hazeur Township, NTS 32G07, near the north edge of Caopatina Lake. The approximate UTM coordinate for the geographic center of the property are 520785 mE and 5482050 mN (zone 18, NAD83).

The Monster Lake South property comprises 6 active mining titles covering a total of 112.45 ha.

West Point has performed a program of four diamond drill hole in September 2014 for a total length of 1200 meters.

Based on the results obtained from the 2014 work program and the location of the property in an exploration hot spot, it is recommended to pursue exploration work on this property. Future exploration efforts should focus in deep drilling following a positive IP borehole survey investigation.

## **TABLE OF CONTENTS**

<b>1</b>	<b><i>Summary</i></b>	<b>2</b>
<b>2</b>	<b><i>Introduction and terms of reference</i></b>	<b>6</b>
<b>3</b>	<b><i>Reliance on other experts</i></b>	<b>8</b>
<b>4</b>	<b><i>Property description and location</i></b>	<b>9</b>
<b>4.1</b>	<b>Location</b>	<b>9</b>
<b>4.2</b>	<b>Mineral titles status</b>	<b>9</b>
<b>5</b>	<b><i>Accessibility, climate, local resources, infrastructure and physiography</i></b>	<b>14</b>
<b>5.1</b>	<b>Accessibility</b>	<b>14</b>
<b>5.2</b>	<b>Climate</b>	<b>14</b>
<b>5.3</b>	<b>Local Resources and infrastructure</b>	<b>14</b>
<b>5.4</b>	<b>Physiography and Vegetation</b>	<b>15</b>
<b>6</b>	<b><i>History</i></b>	<b>15</b>
<b>7</b>	<b><i>Geological setting</i></b>	<b>18</b>
<b>7.1</b>	<b>Regional geology</b>	<b>18</b>
<b>7.2</b>	<b>Geological setting of the Hazeur property</b>	<b>20</b>
<b>7.3</b>	<b>Structure</b>	<b>22</b>
<b>8</b>	<b><i>Deposit types</i></b>	<b>22</b>
<b>9</b>	<b><i>Mineralization</i></b>	<b>22</b>
<b>10</b>	<b><i>Exploration</i></b>	<b>23</b>
<b>11</b>	<b><i>Drilling (2014)</i></b>	<b>23</b>
<b>11.1</b>	<b>Data</b>	<b>23</b>
<b>11.2</b>	<b>Results</b>	<b>26</b>
<b>12</b>	<b><i>Sampling method and approach</i></b>	<b>28</b>
<b>13</b>	<b><i>Sample preparation, analyses and security</i></b>	<b>28</b>

<b>14</b>	<b><i>Data verification</i></b> .....	<b>29</b>
<b>15</b>	<b><i>Adjacent properties</i></b> .....	<b>29</b>
<b>16</b>	<b><i>Mineral processing and metallurgical testing</i></b> .....	<b>30</b>
<b>17</b>	<b><i>Mineral resource and mineral reserve estimates</i></b> .....	<b>30</b>
<b>18</b>	<b><i>Other relevant data and information</i></b> .....	<b>30</b>
<b>19</b>	<b><i>Interpretation and conclusions</i></b> .....	<b>30</b>
<b>20</b>	<b><i>Recommendations</i></b> .....	<b>31</b>
<b>21</b>	<b><i>Signature page</i></b> .....	<b>31</b>
<b>22</b>	<b><i>References</i></b> .....	<b>32</b>
<b>23</b>	<b><i>Additional requirements for technical reports an development properties and production properties</i></b> .....	<b>35</b>
<b>24</b>	<b><i>Certificate of author</i></b> .....	<b>36</b>

## List of Figures

Figure 1: Monster Lake South General Location Map

Figure 2: Monster Lake South Location Map

Figure 3: Monster Lake South Mining Claims

Figure 4: Monster Lake South Property Regional Geology

Figure 5: Monster Lake South Geological Map (SIGEOM)

Figure 6: Monster Lake South 2014 DDH Location

## **List of Tables**

Table 1: Units and abbreviation

Table 2: Monster Lake South Property Claims

Table 3: 2014 Diamond Drill Hole Campaign Collar Information

Table 4: Best Gold Intersection 2014 DDH Campaign

Table 5: Best Gold Intersection, Historical Holes

## **List of Appendix**

Appendix 1: 2014 log

Appendix 2: Lab Certificate

## 2 Introduction and terms of reference

Terrax Management (“Terrax”) was contracted on August 8<sup>th</sup> 2014 by West Point Resources Inc. (“West Point”), to complete a Technical Report (“the report”) for the Monster Lake South property (“the property”) in Québec, Canada, in compliance with National Instrument 43-101 and Form 43-101F1. The report is addressed to Cannabix Technologies Inc., (formerly named West Point Resources Inc.), a Canadian company listed on the Canadian Securities. Terrax is an independent exploration consulting firm based in Rouyn-Noranda, Québec. The report was prepared for the purpose of providing an update for the Monster Lake South property, as well as recommendations for an exploration program. This report is required to complete qualifying transaction requirements with the Canadian Securities Exchange or TSX Venture Exchange.

This report reviews historical work on the property and compiles all the data needed to recommend an exploration program. Terrax consulted government databases for assessment reports and status of mining titles.

The author, Jeannot Théberge, B.Sc., P.Geo. wrote this report after reviewing data from previous reports and any information judged relevant, suitable and reliable. The author is a Qualified and Independent Person as defined by National Instrument 43-101. Technical support was provided by Michel Levesque (Terrax).

The author has a good understanding of mineral deposit exploration models for Archean gold deposits by virtue of having worked in such environment for at least 20 years. The author visited the property on August 11<sup>th</sup> 2014 and between September 15<sup>th</sup> to 24<sup>th</sup> during the diamond drilling campaign. The site visit allowed the author to find several old drill collar and the diamond drill campaign provide good information on rock, mineralization and structures.

This report uses both Imperial and Metric Systems for measures and lengths. Conversions from the Metric System to the Imperial System are provided below and quoted where practical. Many of the geologic publications and the more recent work assessment files now use the Metric System, but the older work assessment files almost exclusively referred to the Imperial System.

**Table 1: Units and abbreviations**

Abbreviation	Unit or Term
Ag	Silver
Au	Gold
cm	Centimetre
m	Metre
°C	degree (degrees) Celcius
ddh	diamond drill hole
ft	foot (feet)
g	Gram
ha	Hectare
km	Kilometre
MRNF	Ministère des Ressources Naturelles et de la Faune
%	Percent
ppb	parts per billion
ppm	parts per million
N	North
S	South
E	East
W	West
Oz/ton	Ounce per ton
Oz	Ounce
g/t	gram per tonne
\$	Canadian dollar

Conversion factors utilized in this report include:

1 inch (in) = 2.54 centimetres (cm)

1 pound (lb.) = 0.454 kilograms (kg)

1 foot (ft) = 0.3048 metres (m)

1 troy ounce per short ton (oz/ton) = 34.2857 gram/metric tonne (g/t) = 34.2857 ppm

### **3 Reliance on other experts**

The author, a qualified and independent person as defined by National Instrument 43-101, was contracted by the issuer to study technical documentation relevant to the report and provide an update on the Monster Lake South property, and to recommend a work program if warranted. The author has reviewed the mining titles, their status, any agreements and technical data supplied by the issuer, and any public sources of relevant technical information.

Information about the mining titles and option agreements were supplied by Rav Mlait, CEO and Director of West Point. Terrax is not qualified to express any legal opinion with respect to the property titles or current ownership and possible litigation.

Many of the geological and technical reports for the projects in the vicinity of the Monster Lake South project were prepared before the implementation of National Instrument 43-101 in 2001 and Regulation 43-101 in 2005. The authors of such reports appear to have been qualified, and the information prepared according to standards that were acceptable to the exploration community at that time. However, the data are incomplete in some cases and do not fully meet the current requirement of regulation 43-101. The author of this report is therefore not responsible for information provided from such sources, although there is no known reason to believe that any information used in the preparation of this report is invalid or contain misrepresentations.

The author believes the information used to prepare the report and formulate its conclusions and recommendations is valid and appropriate considering the status of the project and the purpose for which the report is prepared.

## **4 Property description and location**

### **4.1 Location**

The property is located about 60 km south-west of the town of Chibougamau in the Hazeur Township, NTS 32G07, near the north edge of Caopatina Lake, figure 1 and figure 2. The approximate UTM coordinate for the geographic center of the property are 520785mE and 5482050mN (zone 18, NAD83).

### **4.2 Mineral titles status**

The Monster Lake South property comprises 6 active mining titles covering a total of 112.45 ha. The claims are grouped into two blocks of contiguous claims figure 3, Table 2 list the active mining titles.

On February 7, 2014, an agreement was reached between West Point ("the Purchaser") and Junita Tedy Asihto ("the Vendor") regarding 6 mining titles that constitute the Monster Lake South property. The hole HO-92-06 showing occurs within those 6 claims.

The agreement stipulates that West Point purchase 100% of the property. As consideration, the Company paid CAD \$7,800 in cash and issued 300 000 common shares of West Point. The property is subject to a 2% net smelter returns ("NSR") royalty payable by the company. Payments of the NSR interests shall begin nine months after the property is deemed to be in commercial production. In the annual financial statements dated April 30<sup>th</sup> 2014, all payments have been done to vendor.


According to the GESTIM database (Québec's claim management system), all the mining titles comprising the Hazeur property are currently registered to West Point Resources Inc. at 100% and all claims are in good standing.

There are no liens or charges that appear to be registered against the Monster Lake South property.

Terrax is not qualified to express any legal opinion with respect to the property titles or current ownership and possible litigation.

**Table 2: Monster Lake South Property Claims**

NTS Sheet	Title #	Expiry date	Area (ha)	Title holder
32G07	2290060	2016-01-18	15.90	West Point Resources Inc.
32G07	2273684	2016-01-18	9.57	West Point Resources Inc.
32G07	2273685	2016-01-18	24.18	West Point Resources Inc.
32G07	2273686	2016-01-18	30.31	West Point Resources Inc.
32G07	2282604	2016-01-18	16.41	West Point Resources Inc.
32G07	2273683	2016-01-18	16.08	West Point Resources Inc.







Figure 2 MONSTER LAKE SOUTH  
LOCATION MAP

Coordinate System: NAD83 UTM, Zone 18 North, Meter  
Projection: Transverse Mercator  
Datum: North American 1983





## **5 Accessibility, climate, local resources, infrastructure and physiography**

### **5.1 Accessibility**

The property is located about 60 km south-west of the town of Chibougamau in the Hazeur Township, figure 1. The claim block is easily accessible by road, using the main lumber road from the Barette Chapais mill toward km 36 post, figure 2. A secondary lumber road gives us access to the south of the property.

### **5.2 Climate**

The climate of the area is temperate with warm to hot summers, cold winters, and a moderate average annual precipitation. Summer weather is usually in the 20° C range with little precipitation. Winters are cold, with temperature averaging -20° C, but it can get as low as -35° C for periods of couple of weeks at a time. Exploration is possible throughout the year.

### **5.3 Local Resources and infrastructure**

The town of Chibougamau has a population of some 8000 people and local exploration and mining firms can provide trained labor, supplies, equipment and maintenance. All the major services are available in Chibougamau or in Val d'Or.

The property is located near two provincial roads: Provincial road 113 connecting the Abitibi-Témiscamingue region to Provincial road 167 toward the Saguenay-Lac-St-Jean region. Electrical power transmission line is found a few km north of the property and abundant sources of water are found locally. The Chibougamau-Chapais regional airport can accommodate large aircraft and provides regular air services from Montreal, Roberval and Val d'Or.

## 5.4 Physiography and Vegetation

The Monster Lake South property area is flat dominated by a large swamp area. The general elevation is less than 385 m. The overburden coverage is about 15m. Cold climate forest essentially represented by black spruce and birch covers the area.

Several forestry roads still exist on the property and in the surrounding areas.

## 6 History

The first exploration recorded in the sector was by Quebec Smelting & Refining Ltd in 1951 were we can see a geological map just south of the Monster Lake South property.(GM 02138)

In 1952 Hazeur Chibougamau Mine Ltd made a geophysical survey and trenching exposed a shear zone for a length of 230 feet and a width of 50 feet containing quartz veining mineralized with pyrite and galena. Values are low except for an assay of about 1 oz/ton Au reported from a bluish quartz stringer with visible gold. This vein is near the boundary between the Hazeur and Rasles Township 2km east of the property. (GM 02008, GM 1832-A)

Hazeur, Gamache, Fancamp and Rasles Township were subjected to intensive prospecting and exploration activity during the period 1953-1956, primarily induced by the discovery of the Chibex (now Joe Mann Mine) prospect in Rohault Township. The western portion of the Hazeur north area were tested by ground geophysical surveys, prospecting and drilling.(RP 284(A)

1953 Hazeur Chibougamau Mine Ltd drilled 6 holes (3002 feet), 2km east of the property. (No assays reported) (GM 01832-B). In 1956, they drills 7 more hole (740 feet, best intersection 22\$ over 10 feet)(GM 03900-B) and made a magnetic survey (GM 03900-A).

1954 Englewood-Chibougamau Mines Ltd magnetic and resistivity survey, west of the property (GM 03460-A, GM 03146) and diamond drilling in 1955( 3 hole for 2002 feet some copper and zinc values)(GM 03160).

1954 Riverside-Chibougamau Mines Ltd started some exploration program, 2 km to the west of the property. (GM 03046-A, GM 02910). In 1956, diamond drilling ( 4 hole, 2346 feet, best intersection 2 feet at 0.87 oz/ton Au, 1.36 oz/t Ag)(GM 03046-B).

Between 1959 and 1973 few work were done in the Township except for some geological and geophysical report of the old work (GM 04611, GM 13569, GM 16056, GM 28908) Siddeley, (GM 28909) report that Hudson Bay Mining & Smelting Co have made a E.M. survey covering a large block of ground passing right across the north part of Hazeur Townships and followed up, in 1969, with an unspecified amount of groundwork and drilling, with over 10,000ft of core stacked on the north shore of Coapatina Lake. Claims were allowed to lapse at the end of the first year without any assessment work being filed. This sector (about 2km east of the property) continued to be active during the 1973 to 197 with Chibougamau Mining and Smelting Co Inc. doing some geological and geophysical report (GM 31149,

The area of the property was covered by regional airborne survey by Cominco in 1974 (GM 32742, GM 31615) and a geological report in 1976 (GM 32746, GM 32741). Portion of the property area were covered by cut grids and subjected to magnetic, HLEM and gravity surveys with inconclusive results.

In 1977, the area was covered by regional EM survey Input MK VI by the provincial government. Many anomalies were detected directly on the property (DP 496).

In 1984, Golden Tiger, Lac Winchester Project 323 claims, covering the entire present property was prospected and partly mapped (GM 41477, GM 42628, 42629). 4 holes were drilled, one of them, 84-4, was drilled 1.5km to the N-W of the property, no economic result were fund. In 1986 a total of 11 mineralized (up to 11.25 g/t Au) of siliceous diorite and quartz-carbonate-sulfide rock were located about 2km to the east of the property (GM 45015) and 12 diamond drill holes (GM 44982) were drilled (1750m) in the same area some anomalous gold result were fund. During the winter 85-86, 13 holes (3250.7 feet) were drilled (GM 43518) and another 61 holes (1944 feet) in reverse circulation (GM 43517). The RC holes are on the north side of the property looking for mineralization further north and useless for the Monster Lake South property. There is a till sample who have returned 14 890 ppb Au in hole R-36 on the north border of the property. During the same period a VLF-Mag-Maxmin was done (GM 43515).

In 1987, the Golden Tiger property is optioned to Golden Rock. Trenching, geophysics and 40 holes (8559.5m) are done that year (GM 45432). 4 holes were done north of the R-36 to find the source of this till sample with no result.

In 1991, Homestake drilled 7 holes (1043 m). From those holes, 2 were done directly on the present property; H-91-06 and H-91-07. H-91-07 confirmed the presence of a series of variably sheared gabbro sills in a sequence of mafic flows with subordinate siliceous

sedimentary rocks. Anomalous gold concentrations up to 0.41 g/t Au across 1.0 meter were intersected in sheared portions of the gabbro, and peak gold concentration of 2.13 g/t Au across a core length of 1.4 meters was intersected in a discordant quartz-tourmaline vein within the gabbro (GM 50625).

In fall 1991, Westminer Canada Ltd took the project and made a geochemical program (GM 51740). An excellent primary target was defined on the property (magnetic high transected by regional break in the vicinity of a major cross-structure) and was further evaluated by geophysics (mag-IP)(GM 51650) and drilling including 16 diamond drill holes (3222 m) (GM 51369, GM 51738). Hole HO-92-06 returned the best intersection with 5.39 g/t Au over 8.0 meter. After that Westminer optioned ground to the east and south and made 3 winters drilling campaign with mitigate result (GM 51990, GM 51991, GM 51992).

## 7 Geological setting


### 7.1 Regional geology

The Monster Lake South property is located in the south-eastern part of the Matagami-Chibougamau Archean greenstone belt, Abitibi Sub-Province of the Archean Superior Province of the Canadian Shield Craton.

Most of this section was borrowed and modified from De Chavigny (1992), which provides a thorough description of the regional geology.

That southern part, also called the Caopatina-Desmaraisville segment, is bounded to the east by the Grenvillian Front. The stratigraphy of the Caopatina-Desmaraisville belt, from the base to the top, consists of the Obatogamau Formation includes massive, brecciated to pillow mafic flows and comagmatic more or less differentiated gabbroic sills. Minor sequences of interflow sediments including graphitic formationals sediments are also interdigitated with mafic flows. A more felsic member occurs within the Obatogamau Formation: the “Lac des Vents” member, including felsic to mafic flows, pyroclastic and volcanoclastic sediments. The Obatogamau Formation is overlain by the Caopatina Formation, a sedimentary sequence including feldspathic wackes, siltstones, mudstones (turbidites) with minor mafic flows and gabbroic sills. The greenstone belt is also intruded by numerous early to late felsic to intermediate intrusions. The Kenoran orogeny has deformed these lithologies into EW isoclinal folds which are associated with the regional foliation and greenschist facies metamorphism. Higher metamorphic grade is met in the vicinity of the Grenvillian Front and near late plutons. Structurally the greenstone belt is also affected by numerous regional EW breaks (deformation corridors) often marking the contact zone between different geological domains. The Guercheville system is one of them and can be traced along strike for over 80 kilometers with numerous sub-parallel branches showing an anastomosing pattern. The corridors are characterized by the development of a strong S2 fabric within zones of highly strained rocks. Alteration package developed along the structure includes chlorite-calcite from the outer zones, with generally anomalous gold-arsenic values. The Guercheville system is also characterized by strong vertical lineation.

In term of economic potential for the system, the Guercheville is the host of the following gold deposits: Bachelor, Joe Mann, Lac Shortt and Phillipert.



# INTER LAKE SOUTH PROPERTY REGIONAL GEOLOGY

## 7.2 Geological setting of the Hazeur property


The geology of the property is mainly known from geophysics and number of diamond drill holes carried out by Westminier Canada Ltd and Homestake. The property is notably characterized by its lack of outcrop and by its thick glaciated overburden blanket represented by boulder till ( 7-18 meters thick). Geophysically speaking three domains have been recognized on the property and described as follow:

- 1- High magnetic features represent mafic intrusions consisting of differentiated magnetic gabbroic sills.
- 2- Flat to low magnetic feature represent mainly mafic volcanic flows with minor non-magnetic mafic intrusions and non-conductive interflow sediments related to the Obatogama Formation.
- 3- Highly conductive feature represents a formational graphitic interflow unit including volcanogenic sediments.

Based on drill holes information, the main high magnetic feature trending ENE over a strike length of 1 km corresponds to a differentiated gabbroic sill (Hazeur sill) with a moderate dip toward the NW (48-50) and facing the SE. The thickness of the sill ranges from 35 meter at the WSW end to locally 150 meters in the middle. The sill is surrounded essentially by mafic volcanics of the Obatogama Formation with sporadic non-magnetic interflow sediments. The internal stratigraphy of the Hazeur sill has been characterized and is described schematically as follows, from base to the top.

- 1- Medium to coarse grained pyroxenite (locally ± magnetic)
- 2- Pyroxenitic gabbro (dolerite), transition zone
- 3- Pegmatoidic gabbro (dolerite), transition zone
- 4- Medium grained, plagioclase rich dolerite (generally non-magnetic or slightly magnetic)
- 5- Granophyre (Quartz rich dolerite), strongly magnetic with up to 10-12% disseminated primary titanio-magnetite and ilmenite.

All the lithologies of the Hazeur property have been affected by amphibolite grade metamorphism. Garnets were observed mainly in the granophytic unit and rarely within the pegmatoidic gabbro. No ganet was observed elsewhere within the mafic volcanic surrounding rocks.



# Monster Lake South GEOLOGICAL MAP (SIGEOM)

Ejercicio 5

5 Km

1:50 000 32G07 / 32G10  
Coordinate System: NAD83 UTM, Zone 18 North, Meter  
Projection: Transverse Mercator  
Datum: North American 1983



### **7.3 Structure**

The geological units have been more or less affected by a strong deformation episode interpreted to be related to a regional deformation zone belonging to the southern branch of the Guercheville system. Two sub-parallel ENE regional breaks, part of the same corridor occur on the property. The north one is closely related to a formation conductive graphitic layer located within interflow sediments, part of the Obatogamau's stratigraphic package. The south one is sub-concordant to the Hazeur sill with an average thickness of 130m and zones of highly strained rock are separated by less strained zones characterizing an anastomosing pattern well documented in the Guercheville system. Depending on the competency of the geological units traversed by the shear, the stress regime change from ductile-brittle to brittle-ductile. The pyroxenitic members of the sill are deformed in a more ductile manner than the iron rich more competent granophytic unit which is deformed in a more brittle way. From the cross section examination, the sill seem to be slightly folded and that folding episode seems to be responsible for the garnet development within the granophyre. According to some petrological observation made by De Chavigny (1992), folding episode appears to be pre-gold mineralization and represents possibly a pre-shearing event but certainly has played an important role for the development of dilatancy zones within the granophytic unit, which represents a chemically iron rich trap, and mechanically a competent unit. The flexure observed within the Hazeur sill and plunging shallowly (13 degrees) toward the WSW is related to a drag fold located on the south limb of a more regional overturned anticlinal structure.

## **8 Deposit types**

Dion and Simard in MB 99-33 have already defined four types of gold mineralization occurring in the area covered by the property. We mainly favour the type Alb (Philibert type), weak disseminated pyrite mineralization associated with shear zones intersecting east-west volcanic rocks and associated mafic intrusions. The Philibert deposit is located in an altered gabbro, the same kind of lithology as found on the Monster Lake South property.

## **9 Mineralization**

The gold bearing mineralized zones found within the Hazeur sill are of replacement type and are particularly well developed within a chemically iron rich strongly competent unit represented by the granophytic member of the sill. The mineralization consists of sulphidized (2-10% combined Po-Py as disseminations and veinlet) strongly silicified and carbonatized (calcite-ankerite) sub-parallel zones ranging in width from 0.5 m to up to 11 meters, forming more or less continuous lensoid bodies traceable over about 450 meters in strike length.

Sulphides form a relatively simple suite of minerals associated with native gold. Primary monoclinic (magnetic) pyrrhotite and pyrite form the primary sulphide assemblage. Rare traces of chalcopyrite, sphalerite and arsenopyrite occur as accessories ( Page M.L. 1992).

Oxidation has commonly converted pyrrhotite to supergene mineral consisting of secondary pyrite, marcasite and melnikovite pyrite. Primary magmatic oxides (titanomagnetite and ilmenite) from the iron rich granophyre (8-12%) have been partially to completely replaced by the sulphide assemblage pyrrhotite-pyrite showing a strong decrease of the magnetic susceptibility within the mineralized zones compared to the unmineralized granophytic host unit. Native gold is present within the mineralized zones and as a strong association with sulphides and calcite, usually at the edges of sulphide or within carbonate.

## 10 Exploration

West Point has performed a program of four diamond drill hole in September 2014 for a total length of 1200 meters. This exploration item will be discussed in chapter 11.

## 11 Drilling (2014)

West Point has performed a program of four diamond drill hole in September 2014 for a total length of 1200 meters. The drilling was completed by Forage Nordic of Val d'Or (Québec). The assay work was completed by Actlabs Laboratory in Ste-Germaine (Québec). The supervision of the exploration work completed in 2014 was done by the author. Those diamond drill holes were completed on the main showing of the property.

### 11.1 Data

Four (4) diamond drill holes were completed on the main showing in order to validate and verify the lateral extension of previous drill holes and understand the distribution of the gold in the system. Drilling was completed using appropriate Quality Assurance and Quality Control (QA/QC protocol) with duplicates, blanks and standards. A total of 1200 m were drilled.

**Table 3: 2014 Diamond Drill Hole Campaign Collar Information**

DDH #	East UTM	North UTM	Azimuth	Dip	Length (m)
WP-14-01	520460	5481873	165°	-70°	300
WP-14-02	520534	5481986	165°	-53°	300
WP-14-03	520639	5481982	165°	-60°	300
WP-14-04	520639	5481982	165°	-50°	300

Drill holes were supervised, logged and sampled by the author. A total of 277 core samples and 29 QA/QC control samples were collected. The table below presents the most significant intersections (see appendix 1 for complete results).




Figure 6

## Monster Lake South 2014 DDH LOCATION

32G07 NAD 1983, CSRS, UTM Zone 18N

## 11.2 Results

Gold values were obtained in all holes. The best intersection, 24546 ppb Au (208.50 m to 209 m), came from the hole WP-14-04. The gold mineralized zones are for the majority of the time associated with shear zones within mafic intrusive. Some nice zones of mineralization, pyrite + pyrrhotite, were disappointing in terms of their gold content. We also noticed that in some places we had the presence of centimetric sulphide veins in the core axis.

The results of the 2014 drilling program are consistent with those obtained in previous years but do not demonstrate this enrichment zone that Westminer predicted.

**Table 4: Best Gold Intersection 2014 DDH Campaign**

Best Au intersection > 1g/t				
Au				
2014 DDH				
HOLES #	FROM metre	TO metre	LENGTH metre	Au g/t
WP-14-01	160.71	161.16	0.45	4273
WP-14-01	161.16	162.00	0.84	2381
WP-14-01	177.00	178.00	1.00	1255
WP-14-01	215.50	216.60	1.10	1770
WP-14-02	214.75	216.00	1.25	7661
WP-14-02	241.92	242.42	0.50	1320
WP-14-02	283.38	284.60	1.22	1270
WP-14-03	213.75	214.75	1.00	1252
WP-14-03	289.67	290.00	0.33	1585
WP-14-04	139.25	140.00	0.75	1196
WP-14-04	208.50	209.00	0.50	24546
WP-14-04	284.78	285.40	0.62	1659

**Table 5: Best Gold Intersection, Historical holes**

<b>Best Au intersection</b>				
Historical holes				
HOLES #	FROM metre	TO metre	LENGTH metre	Au g/t
H-91-07	67.80	69.20	1.40	2.13
HO-92-01	32.60	35.40	2.80	2.20
HO-92-01	43.30	45.00	1.70	3.17
HO-92-01	53.90	56.40	2.50	2.46
HO-92-02	54.00	54.60	0.60	2.01
HO-92-02	60.50	60.80	0.30	1.58
HO-92-02	92.50	93.20	0.70	2.57
HO-92-04	37.60	39.10	1.50	1.22
HO-92-04	54.60	55.00	0.40	5.62
HO-92-04	67.50	69.40	1.90	3.89
HO-92-04	91.10	92.70	1.60	2.08
HO-92-04	98.20	109.60	11.40	1.04
HO-92-05	34.10	35.40	1.30	0.99
HO-92-05	53.00	59.50	6.50	1.40
HO-92-05	75.60	76.10	0.50	3.57
HO-92-06	118.00	119.30	1.30	1.16
HO-92-06	120.90	122.30	1.40	0.91
HO-92-06	123.80	127.20	3.40	1.24
HO-92-06	127.20	131.80	4.60	8.46
HO-92-06	159.10	163.90	4.80	1.42
HO-92-06	166.10	168.30	2.20	1.24
HO-92-07	299.50	301.00	1.50	1.03
HO-92-07	349.55	350.07	0.52	1.58
HO-92-08	174.00	175.50	1.50	3.11
HO-92-10	160.70	163.00	2.30	2.54
HO-92-10	176.70	178.80	2.10	3.18
HO-92-10	180.70	181.70	1.00	1.92
HO-92-10	199.70	201.50	1.80	1.54
HO-92-12	106.55	107.70	1.15	2.27
HO-92-14	123.00	123.90	0.90	2.13
HO-92-14	142.50	143.00	0.50	1.14
HO-92-14	145.60	150.10	4.50	1.20
HO-92-14	180.50	180.80	0.30	1.80
HO-92-15	146.65	147.40	0.75	1.05
HO-92-15	154.00	155.15	1.15	2.37
HO-92-16	266.90	267.50	0.60	3.49

Terrax Management Inc. NI 43-101 Technical Report on the Monster Lake South property.

## **12 Sampling method and approach**

The drill core sampling method and approach was established by Terrax Management. The drill core is boxed, covered and sealed at the drill rig and moved to the side of the gravel road by the drillers where they are piled on the ground. The author has transported the drill core boxes to the core shack in Rouyn-Noranda.

After being examined and described (logged), the core is sampled according to an established protocol. The core of the selected section is first cut in half using a circular rock saw, with one half put aside for eventual shipment to the laboratory. The second half of the core is then put back in its place in the core box, and tag bearing the same number is placed at the end of the sawed core forming the sample length. Core sample intervals are selected based on the presence of favourable geological units and placed into sample bags before being shipped to the assay lab.

Most core sample range from 0.10 to 1.50 meter long. Every unit with sulfur mineralization was systematically sampled. Based on the author's observation of the core, samples collected by diamond drilling are generally intact with little possibility of loss due to wash out and are considered to be of good quality. Overall, the drill core sample recovery from mineralized zones is considered representative.

There is no indication of anything in the drilling, core handling and sampling procedures, or in the sampling methods and approach that could have had a negative impact on the reliability of the reported assay results.

For the historic drilling, none of the reports reviewed while preparing this report, described the sampling method and approach used for the drill core sampling. As no information is available, the author cannot comment on the sampling method and approach.

## **13 Sample preparation, analyses and security**

Circée core logging facility in Rouyn-Noranda was used for the drilling program. Sample preparation, analyses and security protocols for West Point's program were defined by Terrax Management. Assays were performed at the independent and accredited Actlabs laboratory in Ste-Germaine-Boulé, Québec (Techni-Lab S.G.B. Abitibi Inc.).

After being logged and sampled at Circée facility in Rouyn-Noranda, the samples are delivered to the laboratory by the author.

The laboratory delivered results in electronic format by e-mail sent uniquely to Jeannot Théberge. Assay results were then transferred directly into the West Point database.

There is no indication of anything in the core handling and sample preparation that could have a negative impact on the reliability of the reported assay results.

For the historic drilling, none of the reports reviewed while preparing this report, described the sampling preparation for the drill core. As no information is available, the author cannot comment on the sampling preparation, analyses and security.

## 14 Data verification

The author has visited the property during the drilling campaign and ensured that the previous drilling was done by locating old drill casing but for the reasons provided in item 12.0 and 13.0, the author was unable to verify the data. As the historic drill core was destroyed or impossible to locate and only reports and drill logs are available, it is impossible to verify the data. As the exploration work was performed before West Point acquired the property, this situation is completely beyond its control, and simply reflects the norm prior to the introduction of NI 43-101 in 2001. However, West Point drilled four holes and the author observed that the geology correspond to the previous owner's description of the Hazeur property.

During a field visit some old drill casing were found. Hole HO-92-06 is in the same section as the HO-92-07 and not as placed in the MRNF database.

## 15 Adjacent properties

The Monster Lake South property is completely surrounded by Visible Gold property. The property is located within the Tomagold-Lamgold (Monster Lake showing), Vanstar (Liam-Nelligan showing) and SOQUEM (Philibert deposit). This zone is currently one of the most active exploration sector in Québec.

## **16 Mineral processing and metallurgical testing**

No mineral processing or metallurgical testing has been conducted on the Monster Lake South property.

## **17 Mineral resource and mineral reserve estimates**

No mineral resource estimate has been conducted on the Monster Lake South property

## **18 Other relevant data and information**

There is no other relevant information to be included in this report.

## **19 Interpretation and conclusions**

Previous work on the property has outlined several gold bearing features, the main one being the main showing (Redess showing), which is also the main subject of this report. Until now, it has been probed by holes drilled by Homestake in 1991, Westminner Canada in 1992 and by West Point in 2014.

A four holes diamond drilling program took place in the fall of 2014 on the Monster Lake South property to investigate the showing at depth and laterally and to better define the geometry of the gold bearing zone.

All four holes from the 2014 drilling campaign investigated the main showing (Redess showing) and each of these intersected some gold mineralization but do not demonstrate this enrichment zone that Westminner predicted.

Several mineralized zones are present in this showing but the possibilities of discovering a surface economic zone seems slim. The possibilities remain open at depth.

## 20 Recommendations

Based on the results obtained from the 2014 work program and the location of the property in an exploration hot spot, it is recommended to pursue exploration work on this property. Future exploration efforts should focus in deep drilling following a positive IP borehole survey investigation.

### Phase 1

Localisation of casing	5 000.00 \$
Geophysic IP Borehole survey	20 000.00 \$
total	25 000.00 \$


### Phase 2

750m of NQ drilling all included	100\$/m 75 000.00 \$
----------------------------------	----------------------

## 21 Signature page

All of which is respectfully submitted for your information and consideration.

Rouyn-Noranda, Québec  
January 5, 2015

  
Jeannot Théberge, P.Geo. #740 OGO  


## 22 References

**GM 02138** Morgan, J.H., Geological plan, Windy Lake Group, Quebec smelting & Refining LTD,1952.

**GM 02008** Graham,R.B., Report on property examinations in the Chibougamau district., MRN, 1952.

**GM 01832-A** Quinn, W.R., Report on geological survey. Hazeur Chibougamau Mines Ltd., 1952.

**RP 287-A** Graham,R.B., Mning properties and development in the Chibougamau region,Abitibi-East and Roberval counties during 1952.,MRN, 1952.

**RP 284-A** Grenier, P.E., Preliminary report on Gamache area, Abitibi East County., MRN, 1953.

**GM 01832-B** Quinn, W.R., Diamond drill record., Hazeur Chibougamau Mines Ltd., 1953.

**GM 03160-A** Sheppard,E.P., Report on resistivity and magnetic survey., Englewood-Chibougamau Mines Ltd., 1954.

**GM 03146** Sheppard,E.P., Report on resistivity and magnetic survey., Claim Cowan., 1954.  
**GM 03046-A** Morgan, J.H., Caopatina Lake Property, Riverside-Chibougamau Mines Ltd., 1954.

**GM 02910** Sheppard, E.P., Report on resistivity survey., Riverside-Chibougamau Mines Ltd., 1954.

**GM 03160-B** Diamond drill log, Windy Lake Area., Englewood-Chibougamau Mines Ltd., 1955.

**GM 03046-B** Diamond drill log. Riverside-Chibougamau Mines Ltd., 1955.

**GM 03900-B** Coulombe, R., Journaux de sondage et croquis de localisation. Hazeur Chibougamau Mines Ltd. 1956.

**GM 03900-B** Sharpe, W.J., Report on magnetic survey. Hazeur Chibougamau Mines Ltd. 1956.

**GM 04611** Caraghiaur, E., Rapport géologique., Claims Mack. 1960.

**GM 13569** Juteau, L., Rapport géologique., Benray Mining Exploration Co Ltd, Claims Lamarier., 1963.

**GM 16056** Juteau, L., Geological report., Benray Mining Exploration Co Ltd, Claims Crepault., 1963.

**GM 28909** Siddeley, G., Geological Report, Chibougamau Mng & Smtg Co inc., 1973

**GM 28908** Koskitalo, L. O., Geophysical surveys., Chibougamau Mng & Smtg Co inc., 1973

**GM 32742** Hayles, J.G., Assessment report, geophysical surveys, Windy project., Cominco Ltee., 1975.

**GM 31615** Stemp, R.W., Report on airborne geophysical survey of Windy project area of Quebec., Cominco Ltee., 1975.

**GM 31491** Hayles, J.G., Geophysical surveys, Haze property., Cominco Ltee., 1975.

**GM 31149** Ford, G. M., Assessment report, Hazeur Gold Group., Chibougamau mining and smelting Co Inc., 1975.

**GM 32746** Shimron, A.E., Wallis, C.S., Geological report,Windy project., Cominco Ltee., 1976.

**GM 32741** Pickett,J.W., Wallis,C.S., Year end report, Windy project and Haze Group., Cominco Ltee., 1976.

**DP 496** Levé EM aérien par Input MK-VI-région De La Dauversière, Questor Surveys Ltd.,1977.

**GM 42628** Smith, P.H., Otish, S., Report, Winchester Project., Société d'exploration Golden Tiger inc., 1984.

**GM 41477** Lechow, W.R., Vertical magnetic gradient and vlf survey of Lac Coapatina Area, Project #26GOC., Golden Tiger Mining exploration Co inc., 1984.

**GM 42629** Laforest, G., Frederic, J.R., Rapport sur les terrains, Projet Chibougamau., Société d'exploration minière Golden Tiger inc., 1985.

**GM 45015** Lambert,R., Jenkins, C. H., Auriferous boulder follow-up, Chibougamau property., Société d'exploration Golden Tiger inc., 1986.

**GM 45014** Bussière,Y. Compilation des travaux antérieurs et recommandations de travaux, propriété Golden Tiger., Société d'exploration Golden Tiger Inc., 1986.

**GM 44982** Vachon,A., Lill,J.R., Résultats des forages C-86-1 à 12, Projet Chibougamau., Société d'exploration Golden Tiger Inc., 1986.

**GM 43515** Coda, R., Rapport des travaux, propriété Golden Tiger, Exploreco Inc., 1986.

**GM 43517** Meyer, D., Breton, W E., Program of reverse circulation drilling, Winchester Lake Gold Property., Société d'exploration Golden Tiger Inc., 1986.

**GM 43518** Otis, S., Rapport sur la champagne de sondage de l'hiver 1985-86 sur les propriétés Winchester, Coapatina et Gamache., Société d'exploration Golden Tiger Inc., 1986.

**GM 45432** Bussières, Y., Brassard, B., Lill, J R., Travaux d'exploration, Janvier et Février 1987, propriétés de Chibougamau., 1987.

**GM 50625** Bending, D., Assessment report of 1991 diamond drilling program, Hazeur North Target, Moress, Orcaness, Redess Projects., Homestake Canada Inc.,1991.

**GM 51740** Sexton, A. J., Geochemical Program, Hazeur option project (4025)., Westminier Canada Ltd., 1992.

**GM 51650** Lachapelle, R., Induced polarization survey, Hazeur-Option project (3267)., Westminier Canada Ltd., 1992.

**GM 51369** De Chavigny, P., Report on WMC 1992 (January to March) drilling program, Hazeur option project (4025)., Westminier Canada Ltd., 1992.

**GM 51738** De Chavigny, P., Allard, P., Exploration on the Hazeur option, Project (4025)., Westminier Canada Ltd., 1992.

**GM 51990** De Chavigny, P., Report on the 1992-93 winter drilling campaign on the Lac Caopatina Option project (4034)., Mines Homstake Canada, Ressources Freewest Inc., Westminier Canada Ltd., 1993.

**GM 51991** De Chavigny, P., Report on the 1992-93 winter drilling campaign on the Lac Winchester option project (4031)., Mines Homstake Canada, Ressources Freewest Inc., Westminier Canada Ltd., 1993.

**GM 51992** De Chavigny, P., Simard, R., Report on the 1992-93 winter drilling campaign on La Dauversière project (4007) (Shadow pressure target)., Mines Homstake Canada, Ressources Freewest Inc., Westminier Canada Ltd., 1993.

**MB 99-33** Dion, C., Simard, M., Compilation et synthèse géologique et métallogénique du segment de Caopatina, Région de Chibougamau., MRN., 1999.

## **23 Additional requirements for technical reports an development properties and production properties**



There is no other relevant information to be included in this report.

## 24 Certificate of author

I, Jeannot Théberge, P.Geo #740 OGQ, do hereby certify that:

- 1- I am a consulting geologist and the President of:  
Services Géologiques T-Rex Inc.  
20, 17<sup>e</sup> rue  
Rouyn-Noranda, Qc, J9X 2L3.
- 2- I graduated from the University Laval with a B.Sc. Geology in 1993.
- 3- I am a member in good standing of the l'Ordre des géologues du Québec (OGQ), #740.
- 4- This certificate applies to the Technical Report entitled "NI 43-101 Technical Report on the Monster Lake South property". This Report was written for Cannabix Technologies Inc. and dated January 5, 2015.
- 5- I have worked as a geologist for over 20 years since my graduation. I have been involved on a variety of gold exploration and production properties.
- 6- I am responsible for all sections of the Technical Report titled "NI 43-101 Technical Report on the Monster Lake South property".
- 7- I have read NI 43-101 and the 43-101 F1 form and related appendices and that the Technical Report has been prepared in compliance with the National Instrument 43-101.
- 8- I am independent of the issuer Cannabix Technologies Inc, (formely named West Point Resources Inc.) applying all of the tests in section 1.4 of NI 43-101.
- 9- I fulfill the requirements to be a "qualified person" as defined in the National Policy 43-101.
- 10- I have visited the Hazeur property on August 11<sup>th</sup> 2014 and between September 15<sup>th</sup> to 24<sup>th</sup> during the diamond drilling campaign.
- 11- I consent to the filling of the Technical Report with any stock exchange and other regulatory authority and any publication by them, including electronic publication.

Dated this day January 5, 2015




Jeannot Théberge P.Geo. #740 OGQ QUÉBEC

## **APPENDIX 1**

### **2014 Log**

## West Point

<b>Sondage :</b>	WP-14-01	Titre minier :	2273685	Section :		
Canton :		Rang :	Hazeur	Niveau :		
Foré par :	Forage Nordic	Lot :		Place de travail :		
Décrit par :	Jeannot Théberge	Du :	2014-09-15	Date de description :	2014-11-05	
Au :	2014-09-17					
<hr/>						
Collet						
Azimut :	165.00°	Plongée :	-70.00°	Élevation :	UTM Nad83 Zone 18 Est 520 460.0 Nord 5 481 873.0 381.0	
Plongée :		Longueur :	300.00 m			
<hr/>						
Déviation						
Type	Profondeur	Azimut	Plongée	Invalidé	Description	
Flexite	51.00	162.60°	-65.80°	Non	mag:55770	
Flexite	102.00	162.50°	-64.70°	Non	mag:55626	
Flexite	150.00	160.10°	-64.50°	Non	mag:55613	
Flexite	201.00	159.70°	-64.50°	Non	mag:56220	
Flexite	252.00	166.20°	-64.40°	Non	mag:54937	
Flexite	300.00	165.30°	-64.10°	Non	mag:55316	
<hr/>						
Description						
Dimension de la carotte :	Carotte NQ					Cimenté : Non
Projet : MLS						Entreposé : Oui
						2015-01-05



## West Point

	Description	Analyse				
		D <sub>e</sub>	A	N° d'échantillon	Longueur	Au (ppb)
0.00	9.60 OB <b>Overburden</b> Overburden (Casing left)					
9.60	68.58	V3				
		<b>Mafic Volcanic</b> Dark green-grey, generally aphanitic to fine grained. Moderate to strong fracturation (about 30 fractures by box). Non-magnetic rock except for a small section between 38.75m and 38.90m. Average C.A. 65-70°. Several veins of quartz carbonatite C.A. 65-70°.				
18.37	19.00	V3				
		<b>Mafic Volcanic</b> several veins and stringers of quartz carbonate C.A. 80-85°, trace of Pyrrhotite.				
20.22	20.80	V3				
		<b>Mafic Volcanic</b> Stringers of quartz carbonate in mafic volcanic with a black mineral (hornblende) and chlorite C.A. 75-80°.				
23.31	23.52	V3				
		VEI:20-75°;Pd01; Vein 20 75° Pyrrhotite 1%				
24.73	24.90	V3				
		<b>Mafic Volcanic</b> Quartz carbonate stringers with black minerals (Hornblende) and chlorite in mafic volcanic. While grey quartz carbonate vein C.A. 75° trace of pyrrhotite.				
26.00	27.25	V3				
		<b>Mafic Volcanic</b> Several calcic-quartz schist bands(pillows rims relic?).				
36.61	36.85	V3				
		<b>Mafic Volcanic</b> Carbonate stringers with black minerals (Hornblende) C.A. 80°.				
38.90	39.63	V3				
		<b>Mafic Volcanic</b> Carbonate zone with black minerals (hornblende) trace of pyrrhotite. VEI:70°;Pd01; Vein 70° Pyrrhotite 1%				
41.50	41.75	V3				
		Quartz carbonate vein with chlorite, trace -1% Pyrrhotite, C.A. 70.				
42.00	47.00	V3				
		<b>Mafic Volcanic</b> Weak foliation with carbonate and sericite alteration, trace of pyrrhotite C.A. 45-80°.				
47.00	55.00	V3				
		<b>Mafic Volcanic</b> More intensely fractured with carbonate stringers, one set concordant and the other one parallel to the core. C.A. 60-70°. From 52.40 to 52.95m some pyrite with hornblende.				

## West Point

	Description	Analyse				
		D <sub>e</sub>	A	N° d'échantillon	Longueur	Au (ppb)
55.00	68.58 V3	56.20	56.65	55259	0.45	<8
	<b>Mafic Volcanic</b> From 55m the carbonate stringers are less penetrative with alteration halo of few millimeters.	56.20	56.65	55260 (Bln)	0.45	<8
60.59	60.78 VEl:...80°;P=0°; Vein 80° Pyrrhotite 1% Quartz carbonate shear vein with trace of pyrrhotite. C.A. 80° .	60.50	60.87	55261	0.37	32
68.58	92.00 TU3; V3 <b>Mafic Tuff; Mafic Volcanic</b> Alternation of mafic tuff with mafic volcanic zone, fine grained, non-magnetic, green-dark grey green.	68.55	69.95	55262	1.40	<8
68.58	71.50 TU3 <b>Mafic Tuff 75°</b> Carbonated shear mafic Tuff C.A. 75-80° with trace of pyrite and pyrrhotite especially in the first half.	69.95	70.40	55263	0.45	<8
71.50	73.26 V3 <b>Mafic Volcanic</b> Fine to aphanitic grained with 5% random carbonate quartz stringers.	70.40	71.25	55264	0.85	11
73.26	77.37 TU3 <b>Mafic Tuff</b> Tuff, fine grained green with some mafic volcanic zone.	77.30	78.00	55266	0.70	12
77.37	79.26 TU3 <b>Mafic Tuff 75°</b> Shear carbonate tuff C.A. 75-80° with sharp contact with black needle mineral (2-3%), trace of pyrrhotite.					
79.26	80.63 V3 <b>Mafic Volcanic</b> Generally aphanitic dark green, uniform semi-massive. 2-3% of carbonate veinlets.					
80.63	82.40 TU3; V3 <b>Mafic Tuff; Mafic Volcanic</b> Tuff or mafic volcanic medium grained with needle of black mineral.					
82.40	83.25 V3 <b>Mafic Volcanic</b> Fine grained mafic volcanic.					
83.25	84.57 V3; TU3 <b>Mafic Volcanic; Mafic Tuff</b> Tuff?? or mafic volcanic coarser grained.					
84.57	92.00 V3 <b>Mafic Volcanic</b> Mafic fractured, RQD 10-15%, 3-5% quartz-carbonate veinlets. At 87.50m fine stringers of pyrite in 2 orientation, one parallel to the core and one concordant with the foliation (70-75°).	87.00	88.00	55267	1.00	<8
92.00	126.50 V3			99.00	99.35	55268 0.35

## West Point

	Description	Analyse				
		De	A	N° d'échantillon	Longueur	Au (ppb)
99.36	<b>Mafic Volcanic</b> Fine to aphanitic grained rock with some small tuff zone. Same kind of veinlets like 47m to 55m (veinlets parallel to the core with alteration halo) VEI:::75°;Po01 Cpo0;	99.35	99.78	55269	0.43	<8
99.75	<b>Vein 75% Pyrrhotite 1% Chalcocpyrite 0%</b> White quartz vein with some carbonate, trace of pyrrhotite and chalcocpyrite, C.A.75°.	99.78	100.25	55270	0.47	<8
102.00	<b>V3</b> <b>Mafic Volcanic</b> carbonated zone.	102.00	103.15	55271	1.15	16
105.50		103.15	104.30	55272	1.15	<8
		104.30	105.50	55273	1.20	<8
		110.80	111.10	55274	0.30	<8
111.03	VEI:::75°;Py; <b>Vein 75% Pyrite</b> White quartz vein C.A. 75°, trace of pyrite in the wall rock.	111.03	111.50	55275	0.89	<8
116.61	<b>V3; TU3</b> <b>Mafic Volcanic; Mafic Tuff</b> Tuff?? More intensely shear with more carbonate, C.A. 80-85°.	116.61	126.00	55276	1.30	<8
126.50	<b>V3; TU3</b> <b>Mafic Volcanic; Mafic Tuff</b> Mafic volcanic and mafic tuff with 5-10% of carbonate veins and veinlets C.A. 75-80°. Fine disseminated pyrrhotite and pyrite up to 2% stretched in the foliation. VEI:::75°;Py Po;	126.50	127.30	55277	1.50	<8
126.64	<b>V3; TU3</b> <b>Mafic Volcanic; Mafic Tuff</b> Grey quartz vein with trace of pyrrhotite and pyrite. C.A.75°.	126.64	128.80	55278	1.20	23
		128.80	130.00	55279	1.00	<8
		130.00	131.00	55280	1.00	109
		131.00	132.00	55281	1.50	9
		132.00	133.50	55282	1.50	<8
		133.50	135.00	55283	0.50	<8
		135.00	135.50	55284	0.50	12
135.08	VEI:::70°;Po Py; <b>Vein 70% Pyrrhotite Pyrite</b> Breciated grey quartz vein with some sericitic in the walls, trace of pyrite and pyrrhotite. C.A. 65-70°.	135.08	136.00	55285 (Bln)	0.50	<8
135.62	VEI:::Po03; <b>Vein Pyrite 3%</b> Breciated grey quartz vein with some tourmaline and carbonate. 2-3% of pyrite.	135.62	136.00	55286	0.70	42
136.69	VEI:::75°;; <b>Vein 75%</b> Grey quartz vein with some tourmaline, C.A.75°.	136.69	136.70	55287	0.30	37
136.82	<b>I3A</b> <b>Gabbro</b>	136.82				

## West Point

	Description	Analyse				
		D <sub>e</sub>	A	N° d'échantillon	Longueur	Au (ppb)
140.40	144.90 V3; TU3 <b>Mafic Volcanic; Mafic Tuff</b> Fine grained with iron carbonate veinlets, some magnetic zone, trace of pyrite and pyrrhotite.	140.40 141.70 144.00 144.00 144.60 145.30	141.70 144.60 144.60 145.30	55288 55289 55280 (Std) 55291	1.30 0.60 0.60 0.70	<8 16 6 024 268
144.10	144.60 VEI:::75°;Py Po; <b>Vein 75° Pyrite Pyrrhotite</b> Quartz tourmaline vein, trace of pyrite and pyrrhotite C.A. 75°.	145.30	146.08	55292	0.78	11
144.90	147.00 13A <b>Gabbro</b> Transition zone grey-green rock, silicified, slightly magnetic with some amphibole zone.	145.37 145.57 VEI:::Po01 Py01; <b>Vein Pyrrhotite 1% Pyrite 1%</b> Slightly pinkish quartz carbonate vein with 1-2% of pyrite and pyrrhotite at the contact.	146.08 147.00	55293	0.92	54
145.88	146.04 VEI:::35°;Py Po; <b>Vein 35° Pyrite Pyrrhotite</b> Breciated quartz carbonate vein with trace of pyrite and pyrrhotite. C.A. 35°.	150.70 13A <b>Gabbro</b> Coarse grain hematized gabbro with black amphibole with some magnetic zone, trace-1% pyrrhotite and pyrite + trace of chalcopyrite.	151.85 152.70 151.85 152.70 151.85 152.70 152.70 157.50 159.00	55294 55295 55295 55295 55295 55296 55296 55297 55298	1.15 0.85 1.15 <8 0.85 1.30 1.30 1.50	<8 54 <8 <8 <8 68 68 38 181
147.00	152.60 13A <b>Gabbro</b> Coarse grain hematized gabbro with black amphibole with some magnetic zone, trace-1% pyrrhotite and pyrite + trace of chalcopyrite.	151.85 152.60 VEI:::75°;; <b>Vein 75°</b> White quartz vein with trace of pyrite and pyrrhotite on contact, C.A. 75°.	152.70 154.00 152.70 154.00 157.50 159.00	55295 55295 55296 55296 55297 55298	0.85 0.85 0.85 0.85 1.50 0.86	<8 <8 <8 <8 38 181
152.60	154.85 V3 <b>Mafic Volcanic</b> Grey-green fine grained with 3-5% of pyrite until 153.3m. From 154.50 to 154.85 little fault C.A. 30°, broken rock.	154.85 164.68 13A <b>Gabbro</b> Dark grey to dark green rock, medium grained and magnetic. 3-5% of pyrrhotite + trace to 1% of pyrite + trace of chalcopyrite. Some garnet staining at 159.10m. Mineralized quartz vein from 159.86 to 160.65m. After the vein the rock still silicified until 161.10m with 5-10% of fine pyrite in the foliation C.A. 75-80°. Frome 161.10 to 162 less silicified more carbonated until 163.44m with 5% of pyrite from 162.45m to 162.62m.	159.86 160.71 161.16 161.16 162.00 163.50	55289 55300 55301 55302 55303	0.85 0.45 0.84 1.50 1.20	215 4 273 2 381 438 21
159.86	160.65 VEI:::75°;Py08; <b>Vein 75° Pyrite 8%</b> Grey quartz vein with fine pyrite 5-10% C.A. 75°.	160.71 161.16 161.16 162.00 164.70	160.71 161.16 161.16 163.50 164.70	55289 55300 55301 55302 55303	0.85 0.45 0.84 1.50 1.20	215 4 273 2 381 438 21

## West Point

	Description	Analyse				
		D <sub>e</sub>	A	N° d'échantillon	Longueur	Au (ppb)
164.68	169.70 I3A <b>Gabbro</b> Dark grey medium grained, silicified rock. Non-magnetic with some mineralized zone like 164.68m to 165.35m with 3-5% of fine pyrite.	164.70 165.40 166.50 168.00 169.50 171.00	165.40 166.50 168.00 169.50 171.00	55304 55305 55306 55307 55308	0.70 1.10 1.50 1.50 1.50	957 <8 <8 19 12
169.70	171.70 I3A <b>Gabbro</b> Gabbro as above but magnetic with 2% of fine disseminated pyrite. VEI: 45° Py Po; Vein 45° Pyrite Pyrrhotite While quartz vein with trace of pyrite and pyrrhotite. C.A. 45°.	171.00 172.50 171.00 172.50	172.50 172.50 173.00	55309 55310 (Bln) 55311	1.50 1.50 0.50	79 <8 <8
170.06	170.23 I3A <b>Gabbro</b> Same as above but non-magnetic, silicified and lighter grey. Fine disseminated pyrite 3-5%. Slightly hematized.	173.00 174.00 174.00	174.00 175.10 175.10	55312 55313	1.00 1.10	42 142
172.80	177.10 I3A <b>Gabbro</b> Same as above but magnetic, 3-5% of pyrite with silicified and carbonated zone + hematite.	175.10 175.10 175.75 175.75 177.00 178.00 179.62	175.75 175.75 177.00 177.00 178.00 179.62	55314 55315 (Sid) 55316 55317 55318	0.65 0.65 1.25 1.00 1.62	42 877 980 1255 166
174.40	175.60 TU3 <b>Mafic Tuff</b> coarse grained.	179.62 180.65 180.65 182.35 183.70	180.65 180.65 182.35 183.70	55319 55320 (Dbl) 55321 55322	1.03 1.03 1.70 1.35	38 34 159 584
177.10	179.60 V3 <b>Mafic Volcanic</b> Carbonated and magnetic fine grained rock.	179.62 179.62 180.65 182.35	180.65 180.65 182.35 183.70	55319 55320 (Dbl) 55321 55322	1.03 1.03 1.70 1.35	38 34 159 584
179.60	182.50 V3 <b>Mafic Volcanic</b> Fine grained rock, non-magnetic with carbonated veins C.A. 80°.	198.00 199.50 201.00 202.50 204.00	199.50 201.00 201.00 202.50 204.00	55323 55324 55325 55326	1.50 1.50 1.50 1.50	10 52 14 <8
182.50	192.10 I3A <b>Gabbro</b> Coarse-medium grained rock, magnetic, massive. 3-5% of pyrite in the first 50cm. 5% of carbonated veins.	198.00 199.50 201.00 202.50 204.00	199.50 201.00 201.00 202.50 204.00	55323 55324 55325 55326	1.50 1.50 1.50 1.50	10 52 14 <8
192.10	212.10 I3A <b>Gabbro</b> Grey-black rock, magnetic with 3-5% of carbonated veins. C.A. 75-80°. Trace-1% of pyrite from 198m to 204m.					

## West Point

		Description	Analyses				
			D <sub>e</sub>	A	N° d'échantillon	Longueur	Au (ppb)
212.10	218.12	TU3 <b>Mafic Tuff 75°*</b> Tuff - shear zone C.A. 75-80°, 3-5% concordant carbonate veinlets with some narrow zone with pyrite. Silicified zone from 217.83 to 218.12m, 1-2% pyrite. Magnetic.	212.50 214.00 215.50 216.60 218.12 218.12 219.00 219.00 220.50 221.10 221.50 221.10 221.50 222.30 222.90 224.00 224.00 225.00 226.25 227.75	214.00 216.60 218.12 219.00 220.50 221.10 221.50 222.30 222.90 224.00 225.00 226.25 227.75 229.20	55327 55328 55329 55330 55331 55332 55333 55334 55335 (Bln) 55336 55337 55338 55339 55340 (Db) 55341 55342 55343	1.50 1.50 1.10 1.52 0.88 1.50 0.60 0.40 0.40 0.80 0.60 1.10 1.00 1.00 1.25 1.50 1.45	68 <8 1770 215 105 131 97 202 <8 <8 14 60 29 19 189 143 10
218.12	221.35	I3A <b>Gabbro</b> Magnetic silicified dark grey rock with garnet with trace of pyrite, 2-3% of pyrite-pyrrhotite-chalcopyrite in the last 10 centimeters. C.A. 70-75°.					
221.35	229.10	I3A <b>Gabbro</b> Dark grey medium grained, magnetic rock, foliation C.A. 80°, 3-4% quartz carbonate veinlets with trace of pyrite and chalcopyrite.					
229.10	233.00	TU3 <b>Mafic Tuff 75°*</b> Green carbonated tuff, non-magnetic, foliation 75-80°, 2-3% quartz carbonate veinlets.					
233.00	236.40	I3A <b>Gabbro</b> Dark grey greenish medium grained rock with some amphibolite. Massif few veinlets.					
236.40	244.00	TU3 <b>Mafic Tuff 75°*</b> Green carbonated rock, foliation 75°, non-magnetic with zone of silicification from 237.90 to 238.68m. 2% of pyrite in the last meter.					
244.00	255.56	V3 <b>Mafic Volcanic</b> Fine grained non-magnetic green rock, 5% of concordant carbonate veinlets. From 250.60 to 250.86m 2% pyrite streak in the foliation.					
244.00	244.22	VEI..... Vain Grey fractured quartz vein					
255.56	273.76	V3 <b>Mafic Volcanic</b> Dark green, fine grained rock with amphibolite. Foliation C.A. 70°. From 264 to 270.5m trace-1% of					

## West Point

	Description	Analyse				
		De	A	N° d'échantillon	Longueur	Au (ppb)
273.76	276.85 V3 <b>MaFic Volcanic 60°</b> Shear chloritized and carbonatized fine grained rock. C.A. 60° - 3-4% carbonated veinlets.	275.00	276.00	55348	1.00	<8
276.85	298.10 V3 <b>MaFic Volcanic</b> Fine grained 2-3% carbonated veinlets C.A. 70-75°, trace of pyrrhotite and pyrite. From 295.5 to 297m fractured in the core axe with same pyrite (2-3%).	286.87	287.57	55349	0.70	<8
287.10	287.20 V3!!!:25°-Py01 Cp; Veh 25° Pyrite 1% Chalcopyrite Quartz carbonate vein, C.A. 25°, trace to 1% of pyrite + chalcopyrite.	295.50	297.00	55350	1.50	<8
298.10	300.00 V3 <b>MaFic Volcanic 70°</b> Shear carbonated maFic volcanic C.A. 70° - 5-10% veinlets.					
300.00						

Fin du sondage  
 Nombre d'échantillons : 91  
 Nombre d'échantillons QAQC : 9  
 Longueur totale échantillonnée : 91.21

## West Point

<b>Sondage :</b> WP-14-02	Titre minier : 2273686 Canton : Hazeur Rang : Lot : Foré par : Forage Nordic Décrit par : Jeannot Thérèbe	Section : Niveau : Place de travail :																																										
Collet	Du : 2014-09-17 Au : 2014-09-20	Date de description : 2014-11-07																																										
<p style="text-align: center;"><b>UTM Nad83 Zone 18</b></p> <table border="1" style="margin-left: auto; margin-right: auto; border-collapse: collapse; text-align: center;"> <tr> <td>Est</td> <td>520 534.0</td> </tr> <tr> <td>Nord</td> <td>5 481 986.0</td> </tr> <tr> <td>Élévation</td> <td>381.0</td> </tr> </table>			Est	520 534.0	Nord	5 481 986.0	Élévation	381.0																																				
Est	520 534.0																																											
Nord	5 481 986.0																																											
Élévation	381.0																																											
Azimut : 165.00° Plongée : -53.00° Longueur : 300.00 m	Déviation																																											
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Type</th> <th>Profondeur</th> <th>Azimut</th> <th>Plongée</th> <th>Invalidé</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>Flexite</td> <td>50.00</td> <td>163.00°</td> <td>-54.90°</td> <td>Non</td> <td>mag:55429</td> </tr> <tr> <td>Flexite</td> <td>102.00</td> <td>165.00°</td> <td>-55.20°</td> <td>Non</td> <td>55552</td> </tr> <tr> <td>Flexite</td> <td>153.00</td> <td>165.80°</td> <td>-55.30°</td> <td>Non</td> <td>mag:54911</td> </tr> <tr> <td>Flexite</td> <td>201.00</td> <td>168.60°</td> <td>-54.90°</td> <td>Non</td> <td>mag:55406</td> </tr> <tr> <td>Flexite</td> <td>252.00</td> <td>172.50°</td> <td>-55.20°</td> <td>Non</td> <td>mag:56918</td> </tr> <tr> <td>Flexite</td> <td>300.00</td> <td>172.10°</td> <td>-54.90°</td> <td>Non</td> <td>mag:57456</td> </tr> </tbody> </table>			Type	Profondeur	Azimut	Plongée	Invalidé	Description	Flexite	50.00	163.00°	-54.90°	Non	mag:55429	Flexite	102.00	165.00°	-55.20°	Non	55552	Flexite	153.00	165.80°	-55.30°	Non	mag:54911	Flexite	201.00	168.60°	-54.90°	Non	mag:55406	Flexite	252.00	172.50°	-55.20°	Non	mag:56918	Flexite	300.00	172.10°	-54.90°	Non	mag:57456
Type	Profondeur	Azimut	Plongée	Invalidé	Description																																							
Flexite	50.00	163.00°	-54.90°	Non	mag:55429																																							
Flexite	102.00	165.00°	-55.20°	Non	55552																																							
Flexite	153.00	165.80°	-55.30°	Non	mag:54911																																							
Flexite	201.00	168.60°	-54.90°	Non	mag:55406																																							
Flexite	252.00	172.50°	-55.20°	Non	mag:56918																																							
Flexite	300.00	172.10°	-54.90°	Non	mag:57456																																							
Déviation	Description																																											
																																												
Dimension de la carotte :	Carotte NQ Cimenté : Non Entreposé : Oui																																											
Terrax Management																																												

## West Point

	Description	Analyse				
		D <sub>e</sub>	A	N° d'échantillon	Longueur	Au (ppb)
0.00	21.00 OB <b>Overburden</b> Overburden (casing left)					
21.00	30.35 V3 <b>Mafic Volcanic 75°</b> Pale grey-greenish rock, fine grained, slightly carbonated and shear, C.A. 75-80°. Non-magnetic.					
30.35	69.10 V3 <b>Mafic Volcanic</b> Dark grey greenish rock, aphanitic to fine grained with some zone with black minerals (Hornblende). Every 1.5m to 2.5m some shear chlorite zone, probably pillows contact. Non-magnetic with some fractures C.A.10-20°.					
35.14	35.41 VEI:::80°;Py; <b>Vein 80° Pyrite</b> Shear quartz carbonate vein C.A. 85-90°, hornblende, trace of pyrite.					
54.67	55.21 VEI:::80°;Py; <b>Vein 80° Pyrite</b> Shear quartz carbonate vein with hornblende C.A. 80-85°, trace of pyrite.					
61.17	61.37 VEI:::Po; <b>Vein Pyrrhotite</b> Shear quartz carbonate vein C.A. 80° trace to 1% pyrrhotite stretch in the shearing.					
69.10	74.50 V3 <b>Mafic Volcanic 80°</b> Green to light green non-magnetic rock with more veins and veinlets C.A. 75-80°.					
69.80	70.04 V3 <b>Mafic Volcanic</b> Brecia zone (trace to 1% of pyrrhotite).					
74.50	77.40 V3 <b>Mafic Volcanic</b> Green rock aphanitic to fine grained rock.					
77.40	79.12 TU3 <b>Mafic Tuff 75°</b> Grey greenish sheared rock, C.A. 75°, carbonated with hornblende, trace of pyrrhotite.					
79.12	176.50 V3 <b>Mafic Volcanic</b> Green aphanitic to fine grained rock with some carbonated and amphibolitized zone, non-magnetic. Some small sheared zone C.A. 75-80°. From 141m we start to see, parallel to the core, some veinlets with alteration halo. From 156m to 161.50m fractured zone.					
91.50	92.10 STW:::80°;Py;02; <b>Stockwork 80° Pyrite 2%</b> Some quartz carbonale 1cm veins C.A. 80-85°, pyrite 1-2%.					
		35.00	35.50	55351	0.50	16
		54.57	55.50	55352	0.93	<8
		61.00	61.45	55353	0.45	30
		69.78	70.14	55354	0.36	<8
		91.50	92.10	55355	0.60	15

## West Point

	Description	Analyse				
		De	A	N° d'échantillon	Longueur	Au (ppb)
109.58	109.85 V3 <b>Mafic Volcanic</b> Carbonated breccia.					
114.00	114.30 SH <b>Shear 80°</b> Sheared zone C.A. 80-85° with quartz carbonate and trace to 1% pyrrhotite.	119.00	119.42	55356	0.42	<8
119.10	119.25 V3 <b>Mafic Volcanic</b> Serecillized breccia trace to 1% pyrite-pyrrhotite.	126.00	127.00	55357	1.00	<8
126.22	126.80 V3 <b>Mafic Volcanic</b> 1-3% very fine pyrite pyrrhotite with many quartz carbonate veinlets concordant with the foliation.	127.00	128.00	55358	1.00	10
129.63	129.90 V3 <b>Vein 80° Pyrrhotite 1%</b> Chloritized quartz vein C.A. 80-85°, shared wall rock, 1% pyrrhotite.	128.00	129.50	55359	1.50	<8
176.50	179.12 V3 <b>Mafic Volcanic</b> Green rock with many more veins and veinlets (quartz+carbonate), non-magnetic	129.50	129.50	55360 (Bln)	1.50	<8
179.12	182.50 V3 <b>Mafic Volcanic</b> Green to dark green rock with 3-5% carbonated veinlets.	130.00	130.00	55361	0.50	16
182.50	187.23 TU3 <b>Mafic Tuff 75°</b> Fine to medium grained tuff, magnetic from 186.50 to 187.23m.	187.23	189.20	55363	0.56	
187.23	193.04 I3A <b>Gabbro</b> Medium grained gabbro, slightly amphibolitized, 2-3% of carbonated veinlets.	189.75	189.75	55363	0.56	16
193.04	195.94 V3 <b>Mafic Volcanic</b> Fine grained , slightly carbonated trace of pyrite and pyrrhotite.	195.94	197.85	55364	1.25	
197.85	202.50 I3A <b>Gabbro</b> Fine grained gabbro, non-magnetic.	201.90	203.15	55365 (Std)	1.25	
202.50	230.70 I3A <b>Gabbro</b> Coarse grained gabbro with some magnetic zone. Disseminated pyrite and pyrrhotite 1-2%.	203.15	204.00	55366	0.85	192
		204.00	205.50	55367	1.50	76

West Point

Analyses	Description	Analyses				Au (ppb)
		D <sub>e</sub>	A	N° d'échantillon	Longueur	
		205.50	207.00	55368	1.50	166
		207.00	208.50	55369	1.50	50
		208.50	210.00	55370	1.50	52
		210.00	211.50	55371	1.50	303
		211.50	213.00	55372	1.50	27
		213.00	213.53	55373	0.53	139
		213.53	214.75	55374	1.22	280
		213.53	214.75	55375 (Dbl)	1.22	541
		214.75	216.00	55376	1.25	7 661
		216.00	217.50	55377	1.50	10
		217.50	219.00	55378	1.50	104
		219.00	220.50	55379	1.50	13
		220.50	222.00	55380	1.50	120
		222.00	223.50	55381	1.50	<8
		223.50	225.00	55382	1.50	<8
		225.00	226.50	55383	1.50	44
		226.50	228.00	55384	1.50	31
		226.50	228.00	55385 (Bln)	1.50	<8
		228.00	229.28	55386	1.28	9
		229.28	230.70	55387	1.42	55
		230.70	231.60	55388	0.90	15
		231.60	232.10	55389	0.50	23
		231.60	232.10	55390 (Std)	0.50	854
		232.10	233.25	55391	1.15	55
		233.66	238.15	55392	1.50	637
		238.40	TU3			
	Mafic Tuff 70°					
	Carbonated and chloritized shear mafic luff, magnetic, C.A. 70-75°, trace of pyrite and pyrrhotite.					
		13A				
	Gabbro					
	Medium grained gabbro, green rock with sharp contacts, non-magnetic except for the last meter. Slightly shear at the contatct. From 231.80 to 232.05m 3% of pyrrhotite and pyrite					
		VEI:::45°;PO01;				
	Vein 45° Pyrrhotite 1%					
	Quartz carbonate vein C.A. 45-50° , 1% of pyrrhotite.					
	VEI:::45°;PO02;					
238.40	288.00					
241.92	242.42					0.50
245.00	245.30					0.30
245.00	245.27					0.30
						41

West Point

## West Point

<b>Sondage :</b> WP-14-03	Titre minier : 2273686 Canton : Hazeur Rang :	Section : Niveau : Place de travail :																																																												
Foré par : Forage Nordic Décrit par : Jeannot théberge	Lot : Du : 2014-09-22 Au : 2014-09-24	Date de description : 2014-11-12																																																												
<p><b>Collet</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;">Azimut :</td> <td style="width: 15%;">165.00°</td> <td style="width: 15%;">Plongée :</td> <td style="width: 15%;">-60.00°</td> <td style="width: 15%;">Longueur :</td> <td style="width: 15%;">300.00 m</td> </tr> <tr> <td colspan="6" style="text-align: center; padding-top: 10px;"><b>Déviation</b></td> </tr> <tr> <td colspan="6"> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Type</th> <th>Profondeur</th> <th>Azimut</th> <th>Plongée</th> <th>Invalidé</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>Flexite</td> <td>54.00</td> <td>162.50°</td> <td>-59.70°</td> <td>Non</td> <td>mag:55557</td> </tr> <tr> <td>Flexite</td> <td>102.00</td> <td>164.40°</td> <td>-59.40°</td> <td>Non</td> <td>mag:55243</td> </tr> <tr> <td>Flexite</td> <td>150.00</td> <td>163.20°</td> <td>-59.40°</td> <td>Non</td> <td>mag:55283</td> </tr> <tr> <td>Flexite</td> <td>201.00</td> <td>163.00°</td> <td>-59.40°</td> <td>Non</td> <td>mag:55415</td> </tr> <tr> <td>Flexite</td> <td>252.00</td> <td>169.90°</td> <td>-59.60°</td> <td>Non</td> <td>mag:54965</td> </tr> <tr> <td>Flexite</td> <td>300.00</td> <td>170.50°</td> <td>-59.70°</td> <td>Non</td> <td>mag:53683</td> </tr> </tbody> </table> </td> </tr> </table>			Azimut :	165.00°	Plongée :	-60.00°	Longueur :	300.00 m	<b>Déviation</b>						<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Type</th> <th>Profondeur</th> <th>Azimut</th> <th>Plongée</th> <th>Invalidé</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>Flexite</td> <td>54.00</td> <td>162.50°</td> <td>-59.70°</td> <td>Non</td> <td>mag:55557</td> </tr> <tr> <td>Flexite</td> <td>102.00</td> <td>164.40°</td> <td>-59.40°</td> <td>Non</td> <td>mag:55243</td> </tr> <tr> <td>Flexite</td> <td>150.00</td> <td>163.20°</td> <td>-59.40°</td> <td>Non</td> <td>mag:55283</td> </tr> <tr> <td>Flexite</td> <td>201.00</td> <td>163.00°</td> <td>-59.40°</td> <td>Non</td> <td>mag:55415</td> </tr> <tr> <td>Flexite</td> <td>252.00</td> <td>169.90°</td> <td>-59.60°</td> <td>Non</td> <td>mag:54965</td> </tr> <tr> <td>Flexite</td> <td>300.00</td> <td>170.50°</td> <td>-59.70°</td> <td>Non</td> <td>mag:53683</td> </tr> </tbody> </table>						Type	Profondeur	Azimut	Plongée	Invalidé	Description	Flexite	54.00	162.50°	-59.70°	Non	mag:55557	Flexite	102.00	164.40°	-59.40°	Non	mag:55243	Flexite	150.00	163.20°	-59.40°	Non	mag:55283	Flexite	201.00	163.00°	-59.40°	Non	mag:55415	Flexite	252.00	169.90°	-59.60°	Non	mag:54965	Flexite	300.00	170.50°	-59.70°	Non	mag:53683
Azimut :	165.00°	Plongée :	-60.00°	Longueur :	300.00 m																																																									
<b>Déviation</b>																																																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Type</th> <th>Profondeur</th> <th>Azimut</th> <th>Plongée</th> <th>Invalidé</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>Flexite</td> <td>54.00</td> <td>162.50°</td> <td>-59.70°</td> <td>Non</td> <td>mag:55557</td> </tr> <tr> <td>Flexite</td> <td>102.00</td> <td>164.40°</td> <td>-59.40°</td> <td>Non</td> <td>mag:55243</td> </tr> <tr> <td>Flexite</td> <td>150.00</td> <td>163.20°</td> <td>-59.40°</td> <td>Non</td> <td>mag:55283</td> </tr> <tr> <td>Flexite</td> <td>201.00</td> <td>163.00°</td> <td>-59.40°</td> <td>Non</td> <td>mag:55415</td> </tr> <tr> <td>Flexite</td> <td>252.00</td> <td>169.90°</td> <td>-59.60°</td> <td>Non</td> <td>mag:54965</td> </tr> <tr> <td>Flexite</td> <td>300.00</td> <td>170.50°</td> <td>-59.70°</td> <td>Non</td> <td>mag:53683</td> </tr> </tbody> </table>						Type	Profondeur	Azimut	Plongée	Invalidé	Description	Flexite	54.00	162.50°	-59.70°	Non	mag:55557	Flexite	102.00	164.40°	-59.40°	Non	mag:55243	Flexite	150.00	163.20°	-59.40°	Non	mag:55283	Flexite	201.00	163.00°	-59.40°	Non	mag:55415	Flexite	252.00	169.90°	-59.60°	Non	mag:54965	Flexite	300.00	170.50°	-59.70°	Non	mag:53683															
Type	Profondeur	Azimut	Plongée	Invalidé	Description																																																									
Flexite	54.00	162.50°	-59.70°	Non	mag:55557																																																									
Flexite	102.00	164.40°	-59.40°	Non	mag:55243																																																									
Flexite	150.00	163.20°	-59.40°	Non	mag:55283																																																									
Flexite	201.00	163.00°	-59.40°	Non	mag:55415																																																									
Flexite	252.00	169.90°	-59.60°	Non	mag:54965																																																									
Flexite	300.00	170.50°	-59.70°	Non	mag:53683																																																									
<p><b>Dimension de la carotte :</b> Carotte NQ</p> <p><b>Clementé :</b> Non</p> <p><b>Entreposé :</b> Oui</p> <p></p>																																																														
<p><b>Projet :</b> MLS</p> <p><b>Terrax Management</b></p> <p><b>Date :</b> 2015-01-05</p>																																																														

West Point

N°	Description	Analyse					
		D <sub>e</sub>	A	N° d'échantillon	Longueur	Au (ppb)	
0.00	16.50 OB <b>Overburden</b> overburden (casing left)						
16.50	58.60 V3 <b>Mafic Volcanic</b> Aphanitic to fine grained rock, green, non-magnetic, fractured with 2-5% carbonate veinlets C.A. 65-75° Vein 75° Pyrite	24.90	25.33	55472	0.43	10	
25.00	25.08 STW.....Pb; <b>Stockwork Pyrrhotite</b> Quartz carbonate vein with trace of pyrite in the wall C.A. 75°	36.70	37.50	55473	0.80	<8	
36.90	37.40 Quartz carbonate chlorite veins and veinlets zone, trace of pyrrhotite.						
42.90	43.70 SH <b>Shear 76°</b> Carbonated shear zone C.A. 75°.	42.94	43.80	55474	0.86	<8	
52.50	53.04 SH <b>Shear 70°</b> Carbonated shear zone, trace of pyrrhotite, C.A. 70-75°.	52.50	53.20	55476	0.70	38	
58.60	62.27 TU3 <b>Mafic Tuff 70°</b> Grey, greenish laminated and sheared rock with some amphibole. Non-magnetic.	57.82	58.60	55477	0.78	11	
60.80	61.16 V3 <b>Mafic Volcanic</b> Aphanitic to fine grained rock, green with some short shear zone C.A. 70-75°, non-magnetic and some veinlets parallel to the C.A. 10% of concordant veinlets starting at 68m and some parallel to the C.A. with alteration halo even more starting at 84m.	58.60	60.00	55478	1.40	13	
62.27	89.00 V3 <b>Mafic Volcanic</b> Grey-greenish beige fine grained rock slightly shear C.A. 70°, 3-4% quartz, quartz carbonate grey vein. A lot less parallel veinlets. Non-magnetic.	60.00	60.75	55479	0.75	<8	
89.00	98.15 V3 <b>Mafic Volcanic</b> Grey beige shear rock, carbonated, C.A. 70-75°. From 108 to 111m more fractured.	61.25	61.25	55480	0.50	22	
98.15	125.00 V3 <b>Mafic Volcanic</b> Aphanitic to fine grained green fractured rock. 5% of quartz carbonate concordant veins and veinlets. Some short shear zone C.A. 70-75°. From 108 to 111m more fractured.	71.00	72.00	55482	1.00	<8	
125.00	126.38 TU3 <b>Mafic Tuff 75°</b> Grey beige shear rock, carbonated, C.A. 70-75°, non-magnetic, fine grained trace of pyrite.	81.80	82.80	55483	1.00	<8	
		85.60	87.00	55484	1.40	<8	
		85.60	87.00	55485 (Blin)	1.40	<8	
		91.00	92.00	55486	1.00	19	
		92.00	93.00	55487	1.00	49	
		125.00	126.38	55488	1.38		

## West Point

	Description	Analyse				
		D <sub>e</sub>	A	N° d'échantillon	Longueur	Au (ppb)
126.38	131.86 V3 <b>Mafic Volcanic</b> Fine grained green rock, non-magnetic, fractured with 5% of carbonate veinlets, trace of pyrite.					
131.86	143.75 V3 <b>Mafic Volcanic</b> Fine grained green rock, non-magnetic some short shear zone C.A. 70-75°.	143.00	143.75	55489	0.75	13
143.75	147.33 V3; TU3 <b>Mafic Volcanic; Mafic Tuff</b> Grey beige silicified and sheared rock with grey veins and veinlets. Fine pyrite in the central part. Basalt or tuff???	143.00	143.75	55490 (Std)	0.75	835
147.33	152.42 V3 <b>Mafic Volcanic</b> Same as 131.86 to 143.75m with some limonitic joints parallel to the core.	143.75	145.05	55491	1.30	10
152.42	158.61 V3 <b>Mafic Volcanic 70°</b> Carbonated green shear rock, C.A. 70-75°. More altered between 156 to 157m pyrite trace to 2%.	145.05	146.35	55492	1.30	176
158.61	163.10 I3A <b>Gabbro</b> Amphibolitized green gabbro, coarse grained, non-magnetic.	146.35	147.35	55493	1.00	45
163.10	192.00 I3A <b>Gabbro</b> Medium grained gabbro, non-magnetic, green and amphibolitized. More fractured with joint at C.A. 25-30° between 174.5m to 180m same between 186m to 190.5m.	147.35	148.00	55494	0.65	<8
192.00	201.90 V3 <b>Mafic Volcanic</b> Aphanitic to fine grained dark green rock, slightly sheared and carbonated in the first meter after become more chloritised with 1-2% of fine disseminated pyrite and pyrrhotite. The last 20cm is magnetic.	148.00	156.00	55495	1.00	11
201.90	212.00 I3A <b>Gabbro</b> Medium grained grey-greenish grey rock and become magnetic at 204.10 to 211.15m. Some veins and veinlets from 207.20m to 211m C.A. 60-65°.	156.00	156.50	55496	0.50	246
		156.50	157.40	55497	0.90	<8
		157.40	158.61	55498	1.21	<8
				55499	1.02	

## West Point

	Description	Analyse				
		D <sub>e</sub>	A	N° d'échantillon	Longueur	Au (ppb)
212.00	219.30 V3 <b>Ma</b> fic Volcanic Fine grained greenish grey rock, non-magnetic except for small centimetric zone. Silicified and mineralized zone + pyrite + pyrrhotite 5-8% from 213.74 to 214.80m. Brecciated with trace of pyrite from 214.80 to 215.80m.	212.00	213.00	55963	1.00	9
		213.00	213.75	55964	0.75	31
		213.00	213.75	55965 (Std)	0.75	6.027
		213.75	214.75	55966	1.00	1.252
		214.75	215.73	55967	0.98	242
		215.73	216.82	55968	1.09	<8
215.80	216.80 VEI:..... Veln Quartz carbonate vein.					
219.30	223.10 I3A <b>Gabbro</b> Fine to medium grained greenish gabbro, magnetic.	228.10	228.35	55969	0.25	26
223.10	236.95 I3A <b>Gabbro</b> Coarse grained non-magnetic gabbro. Amphibolitized and chloritized.	232.40	232.80	55970	0.40	24
228.18	228.31 VEI:...75° Py; Veln 75° Pyrite Quartz vein trace of pyrite C.A. 75°.	237.00	237.75	55971	0.75	9
236.95	237.75 V3 <b>Ma</b> fic Volcanic Fine grained rock, green, non-magnetic with some quartz carbonatite veins, trace of pyrite.					
237.75	241.90 I3A <b>Gabbro</b> Same as 223.10 to 236.95m.	241.90	242.85	55972	0.95	30
241.90	258.50 I3A <b>Gabbro</b> Very coarse grained gabbro + mineralized zone, magnetic. 3-5% of pyrite and pyrrhotite from 251m to 253.20m.	242.85	243.71	55973	0.86	<8
		243.71	244.68	55974	0.97	<8
		243.71	244.68	55975 (Dbl)	0.97	19
241.90	243.30 VEI:...Py03 Po; Veln Pyrite 3% Pyrrhotite 90% of quartz, black chlorite and tourmaline vein, 3-4% of pyrite pyrrhotite.					
		244.68	245.05	55976	0.37	<8
		245.05	245.58	55977	0.53	<8
		245.58	246.40	55978	0.82	<8
		246.40	247.20	55979	0.80	<8
		247.20	248.20	55980	1.00	<8

## West Point

	Description	Analyse					
		D <sub>e</sub>	A	N° d'échantillon	Longueur	Au (ppb)	
248.65	249.40	VEI:0.01::Py100 Pg; Véni 0.01 Pyrite 100% Pyrrhotite 0.5cm to 1cm pyrite pyrrhotite vein in the core axe.	248.20 249.40 250.90 252.00 253.10 254.10 253.10 254.10 255.00 256.50 258.60 258.60 261.00 262.50 264.00 265.50	249.40 250.90 252.00 253.10 254.10 254.10 255.00 256.50 260.10 260.10 261.00 262.50 264.00 265.50	55981 55982 55983 55984 55985 55986 (Bln) 55987 55988 55989 55990 (Std)	1.20 1.50 1.10 1.10 1.00 1.00 0.90 1.50 1.50 1.50 0.90 1.50 1.50 1.50 1.50	10 <8 <8 14 <8 <8 13 <8 806 9 10 11 19
258.50	268.18	TU3 <b>Mafic Tuff 75°</b> Grey sheared rock C.A. 75-80°. 5% of concordant veinlets, magnetic, trace of disseminated pyrite. Some mud fault <1cm.	271.00 272.00	272.00 273.00	55995 55996	1.00 1.00	
268.18	270.80	TU3 <b>Mafic Tuff</b> Fine to medium grained grey rock, non-magnetic except for the last 40cm.	274.70	276.25 282.33	55997 55998	<8 18	
270.80	272.80	TU3 <b>Mafic Tuff 80°</b> Foliated to shear zone C.A. 60-70° with 5% of veins and veinlets and 1% of disseminated pyrite.	272.80	273.00	55996	1.00	
272.80	274.70	TU3 <b>Mafic Tuff</b> Same as 268.18m to 270.80m.	274.70	275.90 281.30	55997 55998	<8 46	
274.70	282.25	13A <b>Gabbro</b> Coarse grained green gabbro, chloritized and amphibolized, non-magnetic with 1-2% of pyrite + pyrrhotite in the last meter.	282.25	282.33 283.00 284.00 285.00 286.90 289.67 290.00 291.00 291.50	55999 56000 56001 56002 56003 56004 56005 56006	0.67 1.00 1.00 0.60 0.33 1.00 0.50 0.50	
289.60	291.40	13A <b>Gabbro</b> Probably same rock than above but with 30% of quartz carbonate veins and veinlets, non-magnetic, some small zone of shearing C.A. 70-80°	V3	292.00	56006	594	
291.40	294.05	<b>Mafic Volcanic 75°</b>					


## West Point

	Description	Analyse				
		Dø	A	Nº d'échantillon	Longueur	Au (ppb)
294.05	295.50 V3 <b>Mafic Volcanic</b> Shear zone magnetic rock with garnet.					
295.50	300.00 I3A <b>Gabbro</b> Less intense shearing medium grained with some silicification and trace of garnet.					
300.00						

Fin du sondage  
 Nombre d'échantillons : 77  
 Nombre d'échantillons QAQC : 8  
 Longueur totale échantillonnée : 75.20

## West Point

<b>Sondage :</b> WP-14-04	Titre minier : 2273686 Canton : Hazeur Rang : Lot : Foré par : Forage Nordic Décrit par : Jeannot Théberge	Place de travail :  Date de description : 2014-11-21  Date : 2014-09-20 Du : 2014-12-22 Au :	Section :  Niveau : Place de travail :																																										
Collet		UTM Nad83 Zone 18 <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <td>Est</td> <td>520 639.0</td> </tr> <tr> <td>Nord</td> <td>5 481 982.0</td> </tr> <tr> <td>Élevation</td> <td>381.0</td> </tr> </table>		Est	520 639.0	Nord	5 481 982.0	Élevation	381.0																																				
Est	520 639.0																																												
Nord	5 481 982.0																																												
Élevation	381.0																																												
-Déviation																																													
<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tr> <th>Azimut :</th> <td>165.00°</td> <th>Plongée :</th> <td>-50.00°</td> </tr> <tr> <th>Plongée :</th> <td></td> <th>Longueur :</th> <td>300.00 m</td> </tr> </table>				Azimut :	165.00°	Plongée :	-50.00°	Plongée :		Longueur :	300.00 m																																		
Azimut :	165.00°	Plongée :	-50.00°																																										
Plongée :		Longueur :	300.00 m																																										
-Déviation																																													
<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th>Type</th> <th>Profondeur</th> <th>Azimut</th> <th>Plongée</th> <th>Invalidé</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>Flexite</td> <td>51.00</td> <td>162.60°</td> <td>-50.30°</td> <td>Non</td> <td>mag:55641</td> </tr> <tr> <td>Flexite</td> <td>102.00</td> <td>163.50°</td> <td>-50.70°</td> <td>Non</td> <td>mag:55161</td> </tr> <tr> <td>Flexite</td> <td>153.00</td> <td>163.60°</td> <td>-50.70°</td> <td>Non</td> <td>mag:55185</td> </tr> <tr> <td>Flexite</td> <td>201.00</td> <td>166.50°</td> <td>-50.90°</td> <td>Non</td> <td>mag:55192</td> </tr> <tr> <td>Flexite</td> <td>251.00</td> <td>162.50°</td> <td>-52.20°</td> <td>Non</td> <td>mag:57936</td> </tr> <tr> <td>Flexite</td> <td>300.00</td> <td>166.10°</td> <td>-52.70°</td> <td>Non</td> <td>mag:56840</td> </tr> </tbody> </table>				Type	Profondeur	Azimut	Plongée	Invalidé	Description	Flexite	51.00	162.60°	-50.30°	Non	mag:55641	Flexite	102.00	163.50°	-50.70°	Non	mag:55161	Flexite	153.00	163.60°	-50.70°	Non	mag:55185	Flexite	201.00	166.50°	-50.90°	Non	mag:55192	Flexite	251.00	162.50°	-52.20°	Non	mag:57936	Flexite	300.00	166.10°	-52.70°	Non	mag:56840
Type	Profondeur	Azimut	Plongée	Invalidé	Description																																								
Flexite	51.00	162.60°	-50.30°	Non	mag:55641																																								
Flexite	102.00	163.50°	-50.70°	Non	mag:55161																																								
Flexite	153.00	163.60°	-50.70°	Non	mag:55185																																								
Flexite	201.00	166.50°	-50.90°	Non	mag:55192																																								
Flexite	251.00	162.50°	-52.20°	Non	mag:57936																																								
Flexite	300.00	166.10°	-52.70°	Non	mag:56840																																								
Description																																													
Dimension de la carotte : Carotte NQ Cimenté : Non Entreposé : Oui																																													
Dimension de la carotte : Carotte NQ Cimenté : Non Entreposé : Oui																																													



## West Point

	Description	Analyse				
		De	A	N° d'échantillon	Longueur	Au (ppb)
0.00	19.20 OB <b>Overburden</b> Overburden (casing left)					
19.20	58.80 V3 <b>Mafic Volcanic</b> Green aphanitic to fine grained rock, non-magnetic. 3-5% of carbonate veins and veinlets C.A. 80-85° but some fine veinlets at C.A. 15-20°. From 43m some carbonate veinlets with alteration halo C.A. 10-15°.	37.80	38.75	55398	0.95	<8
37.88	39.36 V3 <b>Mafic Volcanic</b> Folded quartz-carbonate veins zone with some sericitic and chlorite, trace to 1% pyrite - pyrrhotite.	38.75	39.43	55399	0.68	<8
58.80	61.60 TU3 <b>Mafic Tuff 75°</b> Green shear tuff zone C.A. 75-80°.	59.35	60.50	55400	1.15	9
61.60	81.00 V3 <b>Mafic Volcanic</b> Same as 19.20m to 58.80m, non-magnetic, some amphibolitization starting at 67.5m.	60.50	61.70	55401	1.20	97
81.00	82.50 V3 <b>Mafic Volcanic 80°</b> Light green shear carbonated mafic volcanic or tuff, C.A. 80°.	83.85	84.57	55402	0.72	<8
82.50	88.70 V3 <b>Mafic Volcanic</b> Aphanitic-line grained rock, green, non-magnetic, trace of pyrite.	83.85	84.57	55402	0.72	<8
83.92	84.00 V3 <b>Vein 80°</b> Quartz vein C.A. 80°.	84.00	84.25	55403	0.34	
84.17	84.25 V3 <b>Vein Pyrite</b> Quartz-carbonate vein + hematite and chlorite, trace of pyrite.	84.25	84.51	55403	0.34	
84.36	84.51 V3 <b>Vein Pyrite</b> Quartz-carbonate vein + hematite and chlorite trace of pyrite.	84.51	88.70	55403	0.34	
88.70	95.95 TU3 <b>Mafic Tuff 80°</b> Grey green Tuff C.A. 80-85 fine grained, non-magnetic.	92.31	92.65	55403	0.34	
92.40	92.53 V3 <b>Vein Pyrrhotite 1% Pyrite</b> Grey quartz vein with 1% pyrrhotite+pyrite maybe some arsenopyrite.	92.65	93.48	55404	0.83	27
93.50	93.56 V3 <b>Vein 80°</b> Black-grey quartz vein C.A. 80°.	93.48	94.20	55405	0.72	150

## West Point

	Description	Analyse					
		Dé	A	Nº d'échantillon	Longueur	Au (ppb)	
93.85	93.90 VÉI: 80°; Vain 80° Black-grey quartz vein C.A. 80°.						
94.03	94.10 VÉI: 80°; Vain 80° Black-grey quartz vein C.A. 80°.	94.20	95.00	55406	0.80	210	
95.95	98.37 <b>Mafic Volcanic</b> Dark green fine grained, non-magnetic rock.						
98.37	V3 <b>Mafic Tuff</b> Same as 88.70m at 95.95m. Broken core.						
102.20	102.20 V3 <b>Mafic Volcanic</b> Grey green fine grained rock with fine carbonate veinlets C.A. 0-10° with alteration halo. From 111.38m to 111.50m little breccia C.A. 20°.	107.00 110.00	108.00 111.00	55407 55408	1.00 1.00	<8 <8	
111.50	130.31 <b>Mafic Volcanic</b> Dark green aphanitic to fine grained rock with 3-4% carbonate veinlets C.A. 80° and some parallel to the core. Non-magnetic.						
130.31	137.23 V3; TU3 <b>Mafic Volcanic; Mafic Tuff</b> Grey-green, aphanitic to fine grained rock with some shear zone. Trace to 1% very fine pyrite and some fine stringers.	130.31 131.00 132.00 133.50 133.50 135.00 136.10 136.10 137.15 137.15 138.55 138.55 139.25 140.00 140.50 141.50 142.05 142.05 142.45 142.45	131.00 130.31 131.00 132.00 133.50 135.00 136.10 136.10 137.15 137.15 138.55 139.25 140.00 140.50 141.50 142.05 142.45 142.45	55409 55410 (Bln) 55411 55412 55413 55414 55415 (Sld) 55416 55417 55418 55419 55420 55421 55422 55423 55424 55425 (Dbl)	0.69 0.69 1.00 1.50 1.50 1.10 1.10 1.05 1.40 0.70 0.75 0.50 1.00 0.55 0.40 0.45 0.45	<8 <8 <8 <8 <8 <8 17 410 254 1196 894 13 12 298 <8 <8	
137.23	142.60 <b>Mafic Tuff</b> Grey green rock C.A. 75-80° with 5-10% of quartz-carbonate veins and veinlets, trace of pyrite except for some silicified zones pyrite with 2-5% very fine; 139.40m to 139.55m, 140m to 140.30m, 142.16 to 142.30m.						

## West Point

	Description	Analyse				
		D <sub>e</sub>	A	N° d'échantillon	Longueur	Au (ppb)
142.60	147.00	TU3	146.08	147.00	55426	0.92
		<b>Mafic Tuff 80°</b> Same as above but less silification.				54
147.00	165.00	13A				
		<b>Gabbro</b> Green gabbro slightly shear until 148.5m, medium grained chloritized, non-magnetic.				
165.00	177.15	13A				
		<b>Gabbro</b> Fine to medium grained green gabbro, slightly magnetic.				
177.15	181.40	TU3				
		<b>Mafic Tuff 75°</b> Light grey shear tuff C.A. 75-80° . From 179m to 180m broken core with some veins and veinlets.				
178.60	178.72	STV:::80°Py10 Po; Stockwork 80% Pyrrhotite 10% Pyrrhotite				
		Quartz veins zone C.A. 80° with 10% of pyrite+pyrrhotite. 1-2% pyrite/pyrrhotite in the wall rock.				
181.40	196.60	13A	183.39	183.70	55428	0.31
		<b>Gabbro</b> Black green medium to coarse grained rock with som magnetic zones. From 183.40 to 185.50m some pyrite pyrrhotite in chlorite carbonate veins. At 194.70m Stringers of pyrite+pyrrhotite 2-3mm.	183.70	184.42	55429	0.72
196.60	204.25	13A	184.42	185.42	55430	1.00
		<b>Gabbro</b> Dark grey to black rock slightly magnetic and silicified with medium to coarse grained. More mineralisation all along the zone (pyrite + pyrrhotite). At 201m pegmatisation.	194.68	195.32	55431	0.64
			200.00	200.00	55432	1.50
			201.00	201.00	55433	1.00
			201.00	201.85	55434	0.85
			201.00	201.85	55435 (Blin)	0.85
			201.85	202.95	55436	1.10
			202.95	204.25	55437	1.30
			207.00	208.00	55438	1.00
			208.00	208.50	55439	0.50
			208.50	208.50	55440 (Std)	0.50
			209.00	209.00	55441	0.50
			211.15	211.56	55442	0.41
208.75	208.75	13A				
		<b>Gabbro 70°</b> Shear zone, probably a gabbro. C.A. 70-75°. 5% to carbonate quartz veinlets. The first 2m are magnetic, non-magnetic for the rest.				
208.08	208.46	VEI:::80°-Pyd2; Vein 80° Pyrite 2%				
		Grey quartz mineralized vein, pyrite-pyrrhotite 1-2%. C.A. 80°.				
208.75	236.77	13A				
		<b>Gabbro</b> Dark grey magnetic gabbro medium grained, 2-3% of quartz carbonate veinlets. At 212.40m, stringers pyrite+pyrrhotite C.A.15°. Sheared and carbonated from 236.78 to 237.14 C.A. 75° with 2-5% of pyrite+pyrrhotite.				
211.29	211.49	VEI:::70°;;				
			211.56	212.88	55443	1.32
						49

## West Point


		Description	Analyse			
			Dø	A	Nº d'échantillon	Longueur
		Vein 70° Quartz carbonate vein C.A. 70° VEI:::30°;Py Po;	212.88	213.30	55444	0.42
		Vein 30° Pyrite Pyrrhotite Carbonate vein with patch of quartz, pyrite pyrrhotite C.A. 30°. VEI:::70°;	213.30	213.90	55445	0.60
211.70	211.75	Vein 70° Grey smoky quartz C.A. 70° STW:::60°;Po:04; Stockwork 60° Pyrrhotite 4%	216.63	217.63	55446	1.00
213.00	213.21	3 quartz veins with 4-5% of pyrite+pyrrhotite, C.A. 60. Some mineralisation between the 3 veinlets and the vein above.	219.00	220.00	55447	1.00
213.71	213.76	Gabbro Brecia with clusters of pyrite+pyrrhotite VEI:::65°;Po:03 Py;	226.92	227.38	55448	0.46
217.00	217.44	Vein 65° Pyrrhotite 3% Pyrite Grey quartz vein, 2-5% of pyrite pyrrhotite, C.A.65° . carbonated and slightly shear up to 227.30m.	227.38	228.00	55449	0.62
227.02	227.20	Gabbro Medium grained gabbro, non-magnetic. Starts to have more veinlets at 248m.	236.60	237.15	55450	0.55
236.77	251.25	Gabbro Magnetic dark green-greenish grey more altered, magnetic.	253.80	254.40	55451	0.60
251.25	257.48	Vein Pyrite 1% Grey quartz vein with 1% of pyrite in the vein and 2-3% in the wall rock.	254.40	255.00	55452	0.60
253.86	254.18	VEI:::Py:01; Vein Pyrite 1% 1cm quartz vein C.A. 25° with 2-3% of pyrite + pyrrhotite.	255.00	256.50	55453	1.50
254.71	254.76	Gabbro Altered grey-greenish grey rock, non-magnetic with brecciated zone up to 258.12m-3-5% fine disseminated pyrite from 259.74m to 260.10m	256.50	257.30	55454	0.80
257.48	263.64	Gabbro Non-magnetic coarse grained gabbro, dark green.	257.30	258.20	55455	0.90
263.64	268.37	Gabbro Magnetic gabbro slightly shear C.A. 70°-80°	258.20	259.70	55456	1.50
268.37	283.35		260.20	261.00	55457	0.50
			268.35	269.12	55460 (Bn)	0.80
			268.35	269.12	55461	0.77
			269.12	269.72		0.60

## West Point

	Description	Analyse				
		D <sub>e</sub>	A	N° d'échantillon	Longueur	Au (ppb)
269.20	269.35 VEI:::::Pod1 Py; Vélin Pyrrhotite 1% Pyrite white quartz vein trace to 2% pyrite + pyrrhotite.					
269.56	269.70 VEI:::::Py01 Po; Vélin Pyrite 1% Pyrrhotite White quartz vein trace to 2% pyrite+pyrrhotite.	269.72 276.00 277.00 277.60 277.00 277.60 278.04 278.04 279.00 280.50 281.20 281.63	270.30 277.00 277.60 277.60 277.60 278.04 279.00 280.50 281.20 281.63	55462 55463 55464 55465 (Std) 55466 55467 55468 55469 55470	0.58 1.00 0.60 0.60 0.44 0.96 1.50 0.70 0.43	55 <8 144 5 633 316 13 30 <8 129
277.82	277.90 VEI:::::Pod5 Py; Vélin Pyrrhotite 5% Pyrite Quartz vein with 5-10% pyrite+pyrrhotite					
281.44	281.53 VEI:::::Py05; Vélin Pyrite 5% White quartz vein with 5-10% of pyrite+pyrrhotite					
283.35	288.80 V3 Mafic Volcanic					
288.80	298.30 Gabbro Coarse grained gabbro, non-magnetic, dark grey-green. 265.28m with fine pyrite up to 2%.	V3 291.02 Vélin White quartz vein.	284.78 285.40	55471	0.62 1 659	
290.91	291.02 Vélin White quartz vein.					
298.30	300.00 13A Gabbro Medium to fine grained gabbro grey-green.					
300.00	Fin du sondage Nombre d'échantillons : 67 Nombre d'échantillons QACQ : 7 Longueur totale échantillonnée : 55.50					

## **APPENDIX 2**

### **Lab certificate**



**TECHNI-LAB**

pyroanalyse  
géochimie  
environnement

**Client :**

Monsieur Jeannot Théberge  
Terrax Management  
139, Avenue Québec  
Rouyn-Noranda (Québec)  
J9X 6M8

Date d'émission: 3 déc. 2014  
Date de réception: 14 nov. 2014  
Date d'analyses: 1 déc. 2014  
Projet: Hazeur  
Certificat: 34729

**CERTIFICAT D'ANALYSE**

66 échantillons de carottes ont été reçus pour analyses.

**Notes :**

Ce certificat remplace et annule tous certificats antérieurs, le cas échéant.

- Ce document est pour l'usage exclusif du client et ne peut être reproduit, sinon en entier, sans l'autorisation écrite de Techni-Lab S. G. B. Abitibi inc. Si vous avez reçu ce certificat par erreur, soyez avisé que tout usage, reproduction ou distribution de celui-ci est strictement interdit. Les échantillons seront conservés pendant 30 jours à partir de la date du certificat à moins d'avis écrit du client.
- Les résultats d'essai ne se rapportent qu'aux objets soumis à l'essai tels qu'ils ont été reçus par le laboratoire.



Les résultats des échantillons sont vérifiés et approuvés par :

Samuel April  
Samuel APRIL, chimiste 2013-172





**TECHNI-LAB**

pyroanalyse  
géochimie  
environnement

**CERTIFICAT D'ANALYSE**

À l'attention de Monsieur Jeannot Théberge

Date d'émission: 3 déc. 2014

Date de réception : 14 nov. 2014

Date d'analyses : 1 déc. 2014

Projet : Hazeur

Certificat : 34729

Client Terrax Management  
139, Avenue Québec  
Rouyn-Noranda (Québec)  
J9X 6M8

Échantillon #	Au ppb	Au g/t	>1.0 g/t	Gravimétrie
Méthode utilisée:	TMT-G5B	TMT-G5C		
55251	89			
55252	<8			
55253	<8			
55254	<8			
55255	<8			
55256	<8			
55257	<8			
55258	<8			
55259	<8			
55260	<8			
55261	32			
55262	<8			
55263	<8			
55264	11			
55265	887			
55266	12			
55267	<8			
55268	<8			
55269	<8			
55270	<8			
55271	16			
55272	<8			
55273	<8			
55274	<8			
55275	<8			
55276	<8			
55277	<8			
55278	23			
55279	<8			
55280	109			
55281	9			
55282	<8			
55283	<8			
55284	12			
55285	<8			

2/5

**TECHNI-LAB**pyroanalyse  
géochimie  
environnement**CERTIFICAT D'ANALYSE**

À l'attention de Monsieur Jeannot Théberge

Client Terrax Management  
139, Avenue Québec  
Rouyn-Noranda (Québec)  
J9X 6M8

Date d'émission: 3 déc. 2014

Date de réception : 14 nov. 2014

Date d'analyses : 1 déc. 2014

Projet : Hazeur

Certificat : 34729

Échantillon <i>n</i>	Au ppb	Au g/t +1.0 g/t Gravimétrie
Méthode utilisée:	TMI-G5B	TMI-G5C
55286	42	
55287	37	
55288	<8	
55289	16	
55290	6024	
55291	268	
55292	11	
55293	54	
55294	<8	
55295	<8	
55296	68	
55297	38	
55298	181	
55299	215	
55300	4273	4.15
55301	2381	2.23
55302	438	
55303	21	
55304	957	
55305	<8	
55306	<8	
55307	19	
55308	12	
55309	79	
55310	<8	
55311	<8	
55312	42	
55313	142	
55314	42	
55315	877	
55316	980	
55261-Dup	23	
55282-Dup	<8	
55301-Dup		2.31



**TECHNI-LAB**

pyroanalyse  
géochimie  
environnement

**CERTIFICAT D'ANALYSE**

À l'attention de Monsieur Jeannot Théberge

Date d'émission: 3 déc. 2014

Date de réception : 14 nov. 2014

Date d'analyses : 1 déc. 2014

Projet : Hazeur

Certificat : 34729

Client Terrax Management  
139, Avenue Québec  
Rouyn-Noranda (Québec)  
J9X 6M8

Échantillon	Au	Au
#	ppb	g/t
		>1.0 g/t
Gravimétrie		
Méthode utilisée:	TMT-G5B	TMT-G5C
55303-Dup	24	
55316-Dup	966	
OXC 129	216	
OXC 129	213	
OXC 129	201	
OXC 129	220	
OXC 129	206	
OXJ 120	2262	
OXK 119	3719	
OXK 119	3749	
OXK 119	3724	
OXK 119	3724	
OXK 119		3.58
OXP 116		14.66
OXQ 90		24.26



**TECHNI-LAB**

pyroanalyse  
géochimie  
environnement

À l'attention de Monsieur Jeannot Théberge

Client: Terrax Management  
139, Avenue Québec  
Rouyn-Noranda (Québec)  
J9X 6M8

Date d'émission: 3 déc. 2014

Date de réception: 14 nov. 2014

Date d'analyse: 1 déc. 2014

Projet: Hazeur

Certificat: 34729

### MÉTHODE ACCRÉDITÉE

TMT-G5B	Or par SAA avec digestion d'Aqua Regia par micro-ondes
TMT-G5C	Or finition par gravimétrie
TMT-G5E	Palladium et Platine par absorption atomique électrothermique (Four au Graphite)
TMT-G5F	Ag, Cu, Pb, Zn, Ni et Co par ICP avec digestion d'Aqua Regia

### MÉTHODE NON ACCRÉDITÉE

TMT-G5G	Argent par Gravimétrie
TMT-G2	Densité
TMT-G5Z	Titration du Zinc

### MÉTHODE ACCRÉDITÉE PAR LE CCN

<i>Méthode</i>	<i>Paramètre</i>	<i>Limite de</i>	<i>Méthode</i>	<i>Paramètre</i>	<i>Limite de</i>
TMT-G5B	Au ppb (5 ml)	8	TMT-G5F	Ag ppm	0.3
TMT-G5B	Au g/t (10 ml)	0.01	TMT-G5F	Co ppm	2
TMT-G5C	Au gravimétrie g/l	0.08	TMT-G5F	Cu ppm	1
TMT-G5E	Pd ppb	2	TMT-G5F	Ni ppm	2
TMT-G5E	Pt ppb	3	TMT-G5F	Pb ppm	3
			TMT-G5F	Zn ppm	1

Ce rapport est pour l'usage exclusif du client et ne peut être reproduit, sinon en entier, sans l'autorisation  
écrite de Techni-Lab S.G.B. Abitibi inc.



Annexe 1 du certificat no 34729 - 55



# TECHNI-LAB

pyroanalyse  
géochimie  
environnement

**Client :**

Monsieur Jeannot Théberge  
Terrax Management  
139, Avenue Québec  
Rouyn-Noranda (Québec)  
J9X 6M8

Date d'émission: 19 déc. 2014  
Date de réception: 19 nov. 2014

Date d'analyses: 8 déc. 2014

Projet: Hazcur  
Certificat: 34746

## CERTIFICAT D'ANALYSE

134 échantillons de carottes ont été reçus pour analyses.

**Notes :**

---

Ce certificat remplace et annule tous certificats antérieurs, le cas échéant.

- ④ Ce document est pour l'usage exclusif du client et ne peut être reproduit, sinon en entier, sans l'autorisation écrite de Techni-Lab S. G. B. Abitibi inc. Si vous avez reçu ce certificat par erreur, soyez avisé que tout usage, reproduction ou distribution de celui-ci est strictement interdit. Les échantillons seront conservés pendant 30 jours à partir de la date du certificat à moins d'avis écrit du client.
- ④ Les résultats d'essai ne se rapportent qu'aux objets soumis à l'essai tels qu'ils ont été reçus par le laboratoire.



Les résultats des échantillons sont vérifiés et approuvés par :

Samuel April  
Samuel APRIL, chimiste 2013-172





**TECHNI-LAB**

pyroanalyse  
géochimie  
environnement

**CERTIFICAT D'ANALYSE**

À l'attention de Monsieur Jeannot Théberge

Date d'émission: 19 déc. 2014

Date de réception : 19 nov. 2014

Date d'analyses : 8 déc. 2014

Projet : Ilazeur

Certificat : 34746

Client Terrax Management  
139, Avenue Québec  
Rouyn-Noranda (Québec)  
J9X 6M8

Échantillon #	Au ppb	Au g/t ≥1.0 g/t
		Gravimétrie
Méthode utilisée	TMT-G5B	TMT-G5C
55317	1255	1.07
55318	166	
55319	38	
55320	34	
55321	159	
55322	584	
55323	10	
55324	52	
55325	14	
55326	<8	
55327	68	
55328	<8	
55329	1770	1.84
55330	215	
55331	105	
55332	131	
55333	97	
55334	202	
55335	<8	
55336	<8	
55337	14	
55338	60	
55339	29	
55340	19	
55341	189	
55342	143	
55343	10	
55344	698	
55345	<8	
55346	<8	
55347	<8	
55348	<8	
55349	<8	
55350	<8	
55351	16	
55352	<8	

**TECHNI-LAB**pyroanalyse  
géochimie  
environnement**CERTIFICAT D'ANALYSE**

À l'attention de Monsieur Jeannot Théberge

Date d'émission: 19 déc. 2014

Date de réception : 19 nov. 2014

Date d'analyses : 8 déc. 2014

Projet : Hazeur

Certificat : 34746

Client Terrax Management  
139, Avenue Québec  
Rouyn-Noranda (Québec)  
J9X 6M8

Échantillon #	Au ppb	Au g/t
		>1,0 g/t
		Gravimétrie
Méthode utilisée:	TMT-G5B	TMT-G5C
55353	30	
55354	<8	
55355	15	
55356	<8	
55357	<8	
55358	10	
55359	<8	
55360	<8	
55361	16	
55362	<8	
55363	16	
55364	84	
55365	6041	
55366	192	
55367	76	
55368	166	
55369	50	
55370	52	
55371	303	
55372	27	
55373	139	
55374	280	
55375	541	
55376	7661	3.45
55377	10	
55378	104	
55379	13	
55380	120	
55381	<8	
55382	<8	
55383	44	
55384	31	
55385	<8	
55386	9	
55387	55	
55388	15	

3/7

**TECHNI-LAB**pyroanalyse  
géochimie  
environnement**CERTIFICAT D'ANALYSE**

À l'attention de Monsieur Jeannot Théberge

Date d'émission: 19 déc. 2014

Date de réception : 19 nov. 2014

Date d'analyses : 8 déc. 2014

Projet : Hazeur

Certificat : 34746

Client Terrax Management  
139, Avenue Québec  
Rouyn-Noranda (Québec)  
J9X 6M8

Échantillon #	Au ppb	Au g/t >1.0 g/t Gravimétrie
Méthode utilisée.	TMT-G5B	TMT-G5C
55389	23	
55390	854	
55391	55	
55392	637	
55393	1320	1.84
55394	41	
55395	<8	
55396	1270	1.03
55397	<8	
55398	<8	
55399	<8	
55400	9	
55401	97	
55402	<8	
55403	30	
55404	27	
55405	150	
55406	210	
55407	<8	
55408	<8	
55409	<8	
55410	<8	
55411	<8	
55412	<8	
55413	<8	
55414	<8	
55415	5732	
55416	17	
55417	410	
55418	254	
55419	1196	0.95
55420	894	
55421	13	
55422	12	
55423	298	
55424	<8	

4/7

**TECHNI-LAB**pyroanalyse  
géochimie  
environnement**CERTIFICAT D'ANALYSE**

À l'attention de Monsieur Jeannot Théberge

Date d'émission: 19 déc. 2014

Date de réception : 19 nov. 2014


Date d'analyses : 8 déc. 2014

Projet : Hazeur

Certificat : 34746

Client Terrax Management  
139, Avenue Québec  
Rouyn-Noranda (Québec)  
J9X 6M8

Échantillon #	Au ppb	Au g/t
		>1.0 g/t
		Gravimétrique
<i>Méthode utilisée:</i>	<i>TMT-G5B</i>	<i>TMT-G5C</i>
55425	<8	
55426	54	
55427	560	
55428	65	
55429	37	
55430	28	
55431	59	
55432	45	
55433	17	
55434	11	
55435	<8	
55436	35	
55437	13	
55438	219	
55439	196	
55440	839	
55441	24546	18.19
55442	54	
55443	49	
55444	85	
55445	955	
55446	182	
55447	13	
55448	944	
55449	11	
55450	606	
55324-Dup	55	
55345-Dup	<8	
55366-Dup	161	
55376-Dup	6680	
55383-Dup	35	
55426-Dup	48	
55448-Dup	938	
OXC 129	208	
OXC 129	195	

**TECHNI-LAB**pyroanalyse  
géochimie  
environnement**CERTIFICAT D'ANALYSE**

À l'attention de Monsieur Jeannot Théberge

Client Terrax Management  
139, Avenue Québec  
Rouyn-Noranda (Québec)  
J9X 6M8

Date d'émission: 19 déc. 2014  
Date de réception : 19 nov. 2014  
Date d'analyses : 8 déc. 2014  
Projet : Hazeur  
Certificat : 34746

Échantillon #	Au	Au
	ppb	g/t
>1.0 g/t		
Gravimétrie		
Méthode utilisée:	TMT-G5B	TMT-G5C
OXC 129	199	
OXC 129	193	
OXC 129	196	
OXC 129	205	
OXC 129	193	
OXJ 120		2.29
OXK 119	3399	
OXK 119	3415	
OXK 119	3592	
OXK 119	3515	
OXK 119	3422	
OXK 119	3628	
OXK 119	3541	
OXK 119	3492	
OXP 116		15.01
OXQ 90		24.92



**TECHNI-LAB**

pyroanalyse  
géochimie  
environnement

À l'attention de Monsieur Jeannot Théberge

Client: Terrax Management  
139, Avenue Québec  
Rouyn-Noranda (Québec)  
J9X 6M8

Date d'émission: 19 déc. 2014

Date de réception: 19 nov. 2014

Date d'analyse: 8 déc. 2014

Projet: Hazeur  
Certificat: 34746

### MÉTHODE ACCRÉDITÉE

TMT-G5B	Or par SAA avec digestion d'Aqua Regia par micro-ondes
TMT-G5C	Or finition par gravimétrie
TMT-G5E	Palladium et Platine par absorption atomique électrothermique (Four au Graphite)
TMT-G5F	Ag, Cu, Pb, Zn, Ni et Co par ICP avec digestion d'Aqua Regia

### MÉTHODE NON ACCRÉDITÉE

TMT-G5G	Argent par Gravimétrie
TMT-G2	Densité
TMT-G5Z	Titration du Zinc

### MÉTHODE ACCRÉDITÉE PAR LE CCN

Méthode	Paramètre	Limite de	Méthode	Paramètre	Limite de
TMT-G5B	Au ppb (5 ml)	8	TMT-G5F	Ag ppm	0.3
TMT-G5B	Au g/t (10 ml)	0.01	TMT-G5F	Co ppm	2
TMT-G5C	Au gravimétrie g/t	0.08	TMT-G5F	Cu ppm	1
TMT-G5E	Pd ppb	2	TMT-G5F	Ni ppm	2
TMT-G5E	Pt ppb	3	TMT-G5F	Pb ppm	3
			TMT-G5F	Zn ppm	1

Ce rapport est pour l'usage exclusif du client et ne peut être reproduit, sinon en entier, sans l'autorisation écrite de Techni-Lab S.G.B. Abitibi inc.



Annexe 1 du certificat no. 34746 - 7/7

184, Principale - C.P. 208, Ste-Germaine-Boulé (Québec) J0Z 1M0 Téléphone : 819 787-6116 • Télécopieur : 819 787-6527 courriel : infoquebec@aclabs.com



**TECHNI-LAB**

pyroanalyse  
géochimie  
environnement

**Client :**

Monsieur Jeannot Théberge  
Terrax Management  
139, Avenue Québec  
Rouyn-Noranda (Québec)  
J9X 6M8

Date d'émission: 18 déc. 2014  
Date de réception: 24 nov. 2014  
Date d'analyses: 9 déc. 2014  
Projet: Hazcur  
Certificat: 34756

**CERTIFICAT D'ANALYSE**

106 échantillons de carottes ont été reçus pour analyses.

**Notes :**

Ce certificat remplace et annule tous certificats antérieurs, le cas échéant.


- ⑧ Ce document est pour l'usage exclusif du client et ne peut être reproduit, sinon en entier, sans l'autorisation écrite de Techni-Lab S. G. B. Abitibi inc. Si vous avez reçu ce certificat par erreur, soyez avisé que tout usage, reproduction ou distribution de celui-ci est strictement interdit. Les échantillons seront conservés pendant 30 jours à partir de la date du certificat à moins d'avis écrit du client.
- ⑨ Les résultats d'essai ne se rapportent qu'aux objets soumis à l'essai tels qu'ils ont été reçus par le laboratoire.



Les résultats des échantillons sont vérifiés et approuvés par :

Samuel April  
Samuel APRIL, chimiste 2013-172



**TECHNI-LAB**pyroanalyse  
géochimie  
environnement**CERTIFICAT D'ANALYSE**

À l'attention de Monsieur Jeannot Théberge

Client Terrax Management  
139, Avenue Québec  
Rouyn-Noranda (Québec)  
J9X 6M8

Date d'émission: 18 déc. 2014


Date de réception : 24 nov. 2014

Date d'analyses : 9 déc. 2014

Projet : Hazeur

Certificat : 34756

Échantillon #	Au	Au
	ppb	g/t
>1.0 g/t		
Gravimétrique		
Méthode utilisée	TMT-G5B	TMT-G5C
55451	<8	
55452	13	
55453	18	
55454	19	
55455	9	
55456	37	
55457	21	
55458	46	
55459	<8	
55460	<8	
55461	98	
55462	55	
55463	<8	
55464	144	
55465	5633	
55466	316	
55467	13	
55468	30	
55469	<8	
55470	129	
55471	1659	1.53
55472	10	
55473	<8	
55474	<8	
55475	<8	
55476	38	
55477	11	
55478	13	
55479	<8	
55480	22	
55481	<8	
55482	<8	
55483	<8	
55484	<8	
55485	<8	

**TECHNI-LAB**pyroanalyse  
géochimie  
environnement**CERTIFICAT D'ANALYSE**

À l'attention de Monsieur Jeannot Théberge

Date d'émission: 18 déc. 2014

Date de réception : 24 nov. 2014

Date d'analyses : 9 déc. 2014

Projet : Hazeur

Certificat : 34756

Client Terrax Management  
139, Avenue Québec  
Rouyn-Noranda (Québec)  
J9X 6M8

Échantillon <i>g</i>	Au ppb	Au g/t >1.0 g/t Gravimétrie
<i>Méthode utilisée:</i>	<i>TMT-G5B</i>	<i>TMT-G5C</i>
55486	19	
55487	49	
55488	<8	
55489	13	
55490	835	
55491	10	
55492	176	
55493	45	
55494	<8	
55495	11	
55496	246	
55497	<8	
55498	<8	
55499	<8	
55500	36	
55951	197	
55952	12	
55953	<8	
55954	<8	
55955	30	
55956	16	
55957	<8	
55958	10	
55959	<8	
55960	<8	
55961	9	
55962	<8	
55963	9	
55964	31	
55965	6027	
55966	1252	1.11
55967	242	
55968	<8	
55969	26	
55970	24	

**TECHNI-LAB**pyroanalyse  
géochimie  
environnement**CERTIFICAT D'ANALYSE**

À l'attention de Monsieur Jeannot Théberge

Date d'émission: 18 déc. 2014

Client Terrax Management  
139, Avenue Québec  
Rouyn-Noranda (Québec)  
J9X 6M8

Date de réception : 24 nov. 2014

Date d'analyses : 9 déc. 2014

Projet : Hazeur

Certificat : 34756

Échantillon #	Au ppb	Au g/t	>1.0 g/t	Gravimétrie
Méthode utilisée*	TMT-G5B	TMT-G5C		
55971	9			
55972	30			
55973	<8			
55974	<8			
55975	19			
55976	<8			
55977	<8			
55978	<8			
55979	<8			
55980	<8			
55981	10			
55982	<8			
55983	<8			
55984	14			
55985	<8			
55986	<8			
55987	<8			
55988	13			
55989	<8			
55990	806			
55991	9			
55992	10			
55993	11			
55994	19			
55995	<8			
55996	18			
55997	<8			
55998	46			
55999	18			
56000	127			
56001	113			
56002	453			
56003	1585	1.89		
56004	352			
56005	124			

**TECHNI-LAB**pyroanalyse  
géochimie  
environnement**CERTIFICAT D'ANALYSE**

À l'attention de Monsieur Jeannot Théberge

Date d'émission: 18 déc. 2014

Date de réception : 24 nov. 2014

Date d'analyses : 9 déc. 2014

Projet : Hazeur

Certificat : 34756

Client Terrax Management  
139, Avenue Québec  
Rouyn-Noranda (Québec)  
J9X 6M8

Échantillon #	Au ppb	Au g/t ≥1.0 g/t	Gravimétric	
			TMT-G5B	TMT-G5C
56006	594			
55461-Dup	75			
55471-Dup		1,60		
55482-Dup	<8			
55606-Dup	726			
55953-Dup	<8			
55966-Dup	1103			
55987-Dup	<8			
OXC 129	201			
OXC 129	205			
OXC 129	208			
OXC 129	203			
OXC 129	186			
OXJ 120		2,37		
OXK 119	3392			
OXK 119	3648			
OXK 119	3582			
OXK 119	3843			
OXK 119	3620			
OXK 119	3492			
OXP 116		14,31		
OXQ 90		23,91		



**TECHNI-LAB**

pyroanalyse  
géochimie  
environnement

À l'attention de Monsieur Jeannot Théberge

Client: Terrax Management  
139, Avenue Québec  
Rouyn-Noranda (Québec)  
J9X 6M8

Date d'émission: 18 déc. 2014  
Date de réception: 24 nov. 2014  
Date d'analyse: 9 déc. 2014  
Projet: Hazeur  
Certificat: 34756

### MÉTHODE ACCRÉDITÉE

TMT-G5B	Or par SAA avec digestion d'Aqua Regia par micro-ondes
TMT-G5C	Or finition par gravimétrie
TMT-G5E	Palladium et Platine par absorption atomique électrothermique (Four au Graphite)
TMT-G5F	Ag, Cu, Pb, Zn, Ni et Co par ICP avec digestion d'Aqua Regia

### MÉTHODE NON ACCRÉDITÉE

TMT-G5G	Argent par Gravimétrie
TMT-G2	Densité
TMT-G5Z	Titration du Zinc

### MÉTHODE ACCRÉDITÉE PAR LE CCN

Méthode	Paramètre	Limite de	Méthode	Paramètre	Limite de
TMT-G5B	Au ppb (5 ml)	8	TMT-G5F	Ag ppm	0.3
TMT-G5B	Au g/t (10 ml)	0.01	TMT-G5F	Co ppm	2
TMT-G5C	Au gravimétrie g/t	0.08	TMT-G5F	Cu ppm	1
TMT-G5E	Pd ppb	2	TMT-G5F	Ni ppm	2
TMT-G5E	Pt ppb	3	TMT-G5F	Pb ppm	3
			TMT-G5F	Zn ppm	1

Ce rapport est pour l'usage exclusif du client et ne peut être reproduit, sinon en entier, sans l'autorisation écrite de Techni-Lab S.G.B. Abitibi inc.



Annexe I du certificat no. 34756 - 6/6

184, Principale - C.P. 208, Ste-Germaine-Boulé (Québec) J0Z 1M0 Téléphone : 819 787-6116 • Télécopieur : 819 787-6527 courriel : infoquebec@actlabs.com

*Quality Analysis ...*



*Innovative Technologies*

**Date Submitted:** 02-Dec-14  
**Invoice No.:** A14-09465  
**Invoice Date:** 10-Dec-14  
**Your Reference:** 34729 SG14-1786 TERRAX

Techni-Lab Abitibi Inc.(Actlabs)  
184 Rue Principale  
Ste-Germaine-Boule Quebec J0Z 1M0  
Canada

ATTN: Andre Caouette

## CERTIFICATE OF ANALYSIS

66 Pulp samples were submitted for analysis.

The following analytical package was requested:

Code 1F2 Total Digestion ICP(TOTAL)

REPORT      **A14-09465**

This report may be reproduced without our consent. If only selected portions of the report are reproduced, permission must be obtained. If no instructions were given at time of sample submittal regarding excess material, it will be discarded within 90 days of this report. Our liability is limited solely to the analytical cost of these analyses. Test results are representative only of material submitted for analysis.

**Notes:**

Values which exceed the upper limit should be assayed for accurate numbers.

CERTIFIED BY:

A handwritten signature in black ink, appearing to read "Emmanuel Eseme".

Emmanuel Eseme, Ph.D.  
Quality Control

ACTIVATION LABORATORIES LTD.  
41 Bittern Street, Ancaster, Ontario, Canada, L9G 4V5  
TELEPHONE +905 648-9611 or +1 888.228.5227 FAX +1.905.648.9613  
E-MAIL [Ancaster@actlabs.com](mailto:Ancaster@actlabs.com) ACTLABS GROUP WEBSITE [www.actlabs.com](http://www.actlabs.com)



## Results

Analyte Symbol	Ag	Al	As	Ba	Be	Bi	Ca	Cd	Co	Cr	Cu	Fe	Ga	Hg	K	Mg	Li	Mo	Na	Ni	P	Pb
Unit Symbol	ppm	%	ppm	ppm	ppm	ppm	%	ppm	ppm	ppm	ppm	%	ppm	ppm	%	ppm	ppm	ppm	ppm	%	ppm	ppm
Lower Limit	0.3	0.01	3	7	1	2	0.01	0.3	1	0.01	1	0.01	1	1	0.01	1	1	0.01	1	0.001	3	
Method Code	TD-ICP																					
55251	<0.3	6.27	<3	149	<1	<2	10.3	<0.3	37	153	109	6.48	16	<1	0.15	2.59	26	1300	<1	1.36	93	0.026
55252	<0.3	6.52	<3	31	<1	<2	8.08	<0.3	31	162	66	6.09	14	<1	0.07	2.57	22	1060	<1	1.12	56	0.044
55253	<0.3	5.28	<3	394	<1	<2	6.74	<0.3	34	276	95	5.97	12	<1	0.36	2.46	31	1040	11	0.94	84	0.021
55254	<0.3	6.47	<3	54	<1	2	7.41	<0.3	43	268	72	8.01	14	<1	0.09	3.41	26	1340	4	1.50	105	0.023
55255	<0.3	7.55	<3	672	<1	<2	10.1	<0.3	42	236	75	8.50	14	<1	0.78	3.07	36	1440	1	1.48	96	0.021
55256	<0.3	6.95	<3	335	<1	<2	8.77	<0.3	44	236	155	8.00	15	<1	0.42	2.89	37	1320	<1	1.39	105	0.023
55257	<0.3	6.82	<3	77	<1	<2	7.61	<0.3	43	182	73	7.85	15	<1	0.17	3.16	48	1080	<1	1.44	108	0.020
55258	<0.3	7.18	<3	28	<1	<2	6.94	<0.3	48	194	175	8.68	15	<1	0.05	3.30	31	1480	<1	1.25	108	0.027
55259	<0.3	7.67	<3	27	<1	<2	7.25	<0.3	51	149	162	9.00	17	<1	0.08	3.68	27	1510	<1	1.71	126	0.028
55260	0.4	5.16	10	475	1	<2	13.7	<0.3	4	59	55	1.77	12	<1	1.69	1.09	10	934	9	2.13	14	0.038
55261	<0.3	5.86	<3	270	<1	<2	9.98	<0.3	37	125	89	6.82	16	<1	0.18	2.87	34	1170	<1	1.10	86	0.020
55262	<0.3	6.92	<3	125	<1	<2	7.49	<0.3	47	180	115	8.30	15	<1	0.09	3.64	39	1350	<1	1.27	115	0.030
55263	<0.3	6.86	3	111	<1	<2	7.93	0.7	46	194	167	8.06	15	<1	0.09	3.31	32	1350	<1	1.48	109	0.025
55264	<0.3	6.70	9	138	<1	<2	6.60	<0.3	46	206	131	8.09	14	<1	0.19	3.64	33	1350	<1	1.92	109	0.030
55265	0.7	8.06	49	140	3	13	2.38	<0.3	22	54	188	5.39	20	<1	3.00	1.70	2	459	<1	2.78	72	0.093
55266	<0.3	6.80	<3	184	<1	<2	7.42	<0.3	44	125	107	7.91	14	<1	0.18	3.25	36	1320	<1	1.76	103	0.023
55267	<0.3	7.39	<3	40	<1	<2	7.70	<0.3	46	129	93	8.43	17	<1	0.12	3.55	23	1360	<1	1.74	113	0.027
55268	<0.3	8.16	<3	34	<1	<2	5.85	0.3	57	186	187	10.0	18	1	0.07	4.29	48	1490	<1	0.84	132	0.026
55269	<0.3	3.67	<3	35	<1	<2	2.97	<0.3	21	280	81	3.45	16	<1	0.09	1.42	19	575	<1	0.71	54	0.019
55270	<0.3	7.09	<3	57	<1	<2	8.33	<0.3	47	143	78	8.33	16	<1	0.18	3.39	26	1360	<1	1.21	112	0.020
55271	<0.3	6.78	<3	59	<1	<2	8.62	<0.3	43	139	113	7.91	16	<1	0.07	3.14	31	1430	<1	1.51	103	0.026
55272	<0.3	6.82	<3	43	<1	<2	7.94	<0.3	46	185	165	7.80	15	<1	0.09	3.20	25	1440	<1	1.49	106	0.026
55273	<0.3	6.76	5	40	<1	2	7.83	<0.3	47	218	158	7.85	15	<1	0.08	3.28	29	1340	4	1.40	110	0.027
55274	<0.3	4.44	<3	31	<1	<2	8.06	<0.3	29	288	48	5.75	9	<1	0.07	2.33	19	1010	6	0.96	77	0.015
55275	<0.3	6.90	4	27	<1	<2	7.09	<0.3	45	168	111	7.83	15	<1	0.06	3.33	34	1260	<1	1.15	108	0.023
55276	<0.3	6.63	<3	36	<1	<2	7.18	<0.3	44	141	102	7.70	16	<1	0.09	3.41	27	1270	<1	1.73	110	0.022
55277	<0.3	6.96	<3	134	<1	<2	6.47	<0.3	47	126	109	7.69	14	<1	0.22	3.18	30	1280	<1	2.15	117	0.024
55278	<0.3	7.18	<3	179	<1	<2	4.84	0.5	43	114	75	8.11	15	<1	0.34	3.62	37	1280	<1	1.87	113	0.028
55279	0.4	7.59	<3	86	<1	<2	3.85	1.1	26	99	41	5.08	16	<1	0.20	1.80	25	615	4	4.20	76	0.048
55280	<0.3	7.22	<3	103	<1	<2	3.92	<0.3	35	103	61	7.11	16	<1	0.32	2.85	28	981	<1	2.73	73	0.043
55281	<0.3	7.16	<3	29	<1	<2	4.12	2.1	41	123	73	7.82	18	<1	0.06	3.40	31	887	<1	2.40	91	0.038
55282	0.4	7.18	<3	67	<1	<2	4.07	0.4	41	150	73	7.52	16	<1	0.38	3.24	39	844	1	2.25	102	0.041
55283	0.7	5.11	<3	548	<1	<2	5.49	<0.3	26	286	38	2.72	12	<1	1.79	1.16	29	534	10	0.17	106	0.029
55284	0.8	5.20	21	159	<1	<2	6.12	<0.3	29	315	36	3.44	13	<1	0.59	1.69	23	701	11	1.40	102	0.022
55285	0.3	5.13	<3	505	1	<2	12.8	<0.3	4	119	37	1.65	12	<1	1.68	0.87	9	814	8	2.01	12	0.033
55286	<0.3	6.95	4	19	<1	<2	5.90	<0.3	34	185	55	5.57	16	<1	0.22	2.59	26	722	2	2.68	115	0.037
55287	<0.3	5.44	<3	7	<1	<2	5.57	<0.3	49	112	221	9.43	16	<1	0.04	2.73	26	1080	<1	1.13	36	0.017
55288	<0.3	2.32	8	7	<1	<2	5.42	<0.3	113	1200	131	9.93	8	<1	0.02	10.5	8	1380	<1	0.02	1240	0.022
55289	<0.3	1.75	<3	7	<1	<2	8.34	<0.3	22	269	17	2.92	7	<1	<0.01	1.09	8	413	<1	0.09	116	0.008
55290	1.0	8.00	99	149	4	<2	2.34	<0.3	21	53	77	5.85	22	<1	3.54	1.68	2	447	<1	3.01	74	0.083
55291	<0.3	4.45	<3	24	2	<2	9.83	<0.3	71	25	676	11.3	18	<1	0.06	3.62	18	1560	<1	1.81	181	0.041
55292	<0.3	3.96	<3	8	<1	<2	9.18	<0.3	56	139	51	8.21	14	<1	0.02	2.05	18	1320	<1	0.14	56	0.033
55293	<0.3	5.79	<3	62	2	<2	6.32	<0.3	65	21	344	13.9	20	<1	0.12	3.15	28	2140	<1	0.75	32	0.073
55294	<0.3	7.50	<3	22	1	<2	5.85	<0.3	37	52	31	10.6	21	<1	0.04	1.79	25	1460	<1	2.19	5	0.127
55295	<0.3	0.45	<3	18	<1	<2	1.47	<0.3	7	431	13	0.94	1	<1	0.01	0.11	2	148	30	0.16	11	0.002
55296	<0.3	6.23	<3	27	<1	<2	6.67	<0.3	45	40	30	9.87	20	<1	0.03	2.13	32	1220	<1	1.63	8	0.044
55297	<0.3	5.70	<3	34	1	<2	3.95	<0.3	22	96	46	11.0	24	<1	0.05	0.84	18	1730	<1	2.20	5	0.130
55298	<0.3	6.04	3	53	<1	<2	4.80	<0.3	20	69	29	10.6	26	<1	0.11	1.06	25	1510	<1	1.90	2	0.138
55299	<0.3	2.31	10	17	<1	<2	1.44	1.5	7	292	35	2.50	5	<1	0.09	0.29	8	155	23	1.21	10	0.060

# Activation Laboratories Ltd.

**A14-09465**

**Report:**

Analyte Symbol	Ag	Al	As	Ba	Be	Bi	Ca	Cr	Cu	Fe	Ga	Hg	K	Mg	Li	Mn	Mo	Na	Ni	P	Pb
Unit Symbol	ppm	%	ppm	%	%	ppm	ppm	ppm	ppm	ppm	ppm	ppm									
Lower limit	0.3	0.01	3	7	1	2	0.01	0.3	1	0.01	1	0.01	0.01	0.01	1	1	0.01	1	0.001	3	
Method Code	TD-ICP																				
55300	0.4	5.88	<3	96	<1	4	6.96	<0.3	21	76	40	7.84	19	<1	0.70	1.32	33	760	<1	1.82	6
55301	<0.3	5.89	<3	13	<1	<2	5.47	0.3	29	80	27	10.5	23	<1	0.05	1.38	22	1330	<1	2.00	4
55302	<0.3	6.00	<3	132	1	<2	4.45	<0.3	27	77	26	11.0	24	<1	0.25	1.08	16	1290	<1	2.89	3
55303	<0.3	6.14	5	183	1	<2	4.07	<0.3	30	63	47	11.0	24	<1	0.50	1.27	18	1480	<1	2.76	4
55304	0.6	5.74	<3	65	2	<2	3.65	<0.3	12	144	29	5.44	25	<1	0.19	0.46	12	702	11	3.07	5
55305	<0.3	5.73	<3	80	2	<2	3.19	<0.3	6	130	45	4.73	23	<1	0.26	0.35	12	685	8	2.92	4
55306	0.5	6.04	3	130	2	<2	3.60	<0.3	6	158	19	4.52	26	<1	0.47	0.31	13	714	8	2.98	7
55307	<0.3	6.23	<3	158	2	<2	3.28	<0.3	5	130	17	4.47	28	<1	0.78	0.29	15	744	2	2.75	4
55308	0.6	5.85	<3	103	1	<2	3.46	<0.3	7	167	59	4.04	21	<1	0.27	0.29	6	677	14	3.33	6
55309	0.8	6.44	<3	95	1	<2	3.74	<0.3	30	142	226	4.89	19	<1	0.19	0.31	10	687	10	3.79	5
55310	<0.3	5.25	<3	501	1	<2	13.6	<0.3	4	82	41	1.73	12	<1	1.80	1.07	10	913	9	2.09	13
55311	0.7	6.91	4	142	1	<2	5.26	<0.3	19	79	193	6.42	20	<1	0.24	0.30	9	871	8	4.82	5
55312	0.6	4.55	<3	178	1	<2	3.51	<0.3	5	154	18	5.91	23	<1	0.28	0.33	7	775	10	3.30	4
55313	0.9	7.25	4	145	<1	<2	3.39	<0.3	26	107	228	5.56	23	<1	0.19	0.49	11	617	7	4.23	3
55314	0.7	6.63	<3	55	<1	<2	5.28	<0.3	22	99	253	6.92	26	<1	0.13	0.77	16	839	9	3.58	4
55315	0.6	8.27	49	139	3	8	2.40	0.4	22	52	184	5.50	22	<1	2.88	1.72	2	474	<1	2.80	74
55316	1.0	5.61	<3	22	1	<2	2.93	<0.3	11	168	68	6.22	22	<1	0.04	0.64	10	803	12	2.87	4

## Results

Analyte Symbol	Sto	S	Sc	Sr	Te	Ti	U	V	W	Y	Zn	Zr
Unit Symbol	ppm	%	ppm	ppm	ppm	%	ppm	ppm	ppm	ppm	ppm	ppm
Lower Limit	5	0.01	4	1	2	0.01	5	10	2	5	1	5
Method Code	TD-ICP											
55251	<5	0.28	30	121	<2	0.15	<5	<10	104	<5	13	61
55252	<5	0.10	28	144	5	0.18	<5	<10	102	<5	12	57
55253	<5	0.29	26	97	12	0.34	<5	<10	172	<5	12	56
55254	<5	0.16	32	109	2	0.50	<5	<10	237	<5	14	76
55255	<5	0.19	38	102	6	0.43	<5	<10	233	<5	16	139
55256	<5	0.28	35	112	3	0.24	<5	<10	147	<5	15	97
55257	<5	0.09	35	68	7	0.21	<5	<10	136	<5	15	69
55258	<5	0.44	36	111	9	0.30	<5	<10	171	<5	17	83
55259	<5	0.26	39	146	11	0.23	<5	<10	137	<5	19	85
55260	<5	0.30	<4	309	6	0.20	<5	<10	30	<5	15	63
55261	<5	0.38	30	114	8	0.24	<5	<10	125	<5	13	98
55262	<5	0.18	34	125	5	0.22	<5	<10	124	<5	15	79
55263	<5	0.36	35	154	3	0.23	<5	<10	138	<5	15	308
55264	<5	0.19	34	90	6	0.26	<5	<10	156	<5	14	113
55265	<5	2.47	6	322	13	0.54	<5	10	72	<5	6	54
55266	<5	0.15	35	111	8	0.25	<5	<10	139	<5	15	77
55267	<5	0.17	39	121	10	0.17	<5	<10	118	<5	17	102
55268	<5	0.33	50	124	3	0.36	<5	<10	186	<5	19	139
55269	<5	0.14	11	57	2	0.25	<5	<10	54	<5	6	49
55270	<5	0.10	38	117	7	0.25	<5	<10	198	<5	17	81
55271	<5	0.27	34	101	3	0.23	<5	<10	133	<5	16	115
55272	<5	0.19	33	87	6	0.23	<5	<10	140	<5	15	112
55273	<5	0.14	34	105	7	0.52	<5	<10	221	<5	15	87
55274	<5	0.10	24	76	5	0.33	<5	<10	157	<5	11	52
55275	<5	0.12	36	92	5	0.25	<5	<10	151	<5	15	86
55276	<5	0.21	33	75	12	0.18	<5	<10	131	<5	15	89
55277	<5	0.30	33	72	8	0.20	<5	<10	136	<5	14	117
55278	<5	0.38	33	54	2	0.22	<5	<10	121	<5	16	207
55279	<5	0.94	18	47	3	0.38	<5	20	139	<5	9	272
55280	<5	0.54	27	60	4	0.26	<5	<10	104	<5	15	146
55281	<5	0.88	29	53	4	0.29	<5	<10	108	9	16	575
55282	<5	0.95	27	50	5	0.44	<5	<10	163	<5	12	193
55283	<5	0.51	13	46	6	0.21	<5	<10	86	6	8	75
55284	<5	0.27	15	96	7	0.28	<5	<10	120	9	8	53
55285	<5	0.31	<4	298	3	0.19	<5	10	34	<5	14	55
55286	<5	0.25	19	90	7	0.34	<5	10	147	<5	10	53
55287	<5	0.28	38	68	5	0.16	<5	<10	437	<5	10	82
55288	<5	0.18	19	76	10	0.32	<5	<10	127	<5	6	74
55289	<5	0.11	25	52	3	0.23	<5	<10	64	<5	6	36
55290	<5	3.02	5	274	10	0.53	<5	10	71	<5	6	92
55291	<5	0.30	43	87	5	0.15	<5	<10	166	<5	18	62
55292	<5	0.61	22	74	13	0.76	<5	<10	218	<5	13	75
55293	<5	0.33	22	106	9	0.19	<5	<10	149	<5	23	97
55294	<5	0.15	7	355	8	0.18	<5	<10	19	<5	24	124
55295	<5	0.18	<4	21	<2	0.10	<5	<10	23	<5	2	11
55296	<5	0.55	49	80	<2	0.23	<5	<10	145	<5	23	87
55297	<5	0.24	34	73	8	0.17	<5	<10	6	<5	61	131
55298	<5	0.28	32	74	6	0.16	<5	<10	19	<5	50	131
55299	<5	1.50	6	37	<2	0.20	<5	<10	36	18	20	423

**Activation Laboratories Ltd.****A14-09465****Report:**

Analyte Symbol	Sb	S	Sc	Sr	Te	Tl	U	V	W	Y	Zn	Zr
Unit Symbol	ppm	%	ppm	ppm	%	ppm						
Lower limit	5	0.01	4	1	2	0.01	5	10	2	5	1	5
Method Code	TD-ICP											
55300	<5	2.88	33	82	10	0.54	<5	95	12	22	49	96
55301	<5	0.69	37	97	7	0.36	<5	45	<5	35	169	40
55302	<5	0.23	33	111	<2	0.19	<5	21	<5	47	100	43
55303	<5	0.04	37	103	10	0.16	<5	34	<5	45	95	37
55304	<5	0.58	17	86	6	0.54	<5	10	30	<5	71	43
55305	<5	0.07	13	77	5	0.35	<5	10	4	<5	94	50
55306	5	0.05	12	66	5	0.30	<5	10	4	<5	103	58
55307	<5	0.04	12	70	8	0.24	<5	<10	3	<5	106	56
55308	<5	0.26	12	109	3	0.36	<5	<10	36	<5	97	40
55309	<5	0.81	11	119	4	0.43	<5	10	42	<5	101	42
55310	5	0.30	<4	314	9	0.20	<5	10	30	<5	16	65
55311	<5	0.96	11	216	6	0.56	<5	10	83	<5	85	28
55312	<5	0.12	8	157	5	0.42	<5	10	60	<5	57	40
55313	<5	1.79	14	117	5	0.46	<5	10	38	<5	63	31
55314	<5	1.37	14	104	8	0.44	<5	10	60	12	68	48
55315	<5	2.53	6	329	15	0.55	<5	10	73	<5	6	57
55316	<5	0.51	13	82	8	0.38	<5	<10	16	9	86	77

Analyte Symbol	Ag	Al	As	Ba	Be	Bi	Ca	Cd	Cr	Cu	Fe	Ga	Hg	K	Mg	Li	Mn	Mo	Na	Ni	P	Pb
Unit Symbol	ppm	%	ppm	%	ppm	ppm	%	ppm	ppm	ppm	ppm	ppm	ppm	%	ppm							
Lower Limit	0.3	0.01	3	7	1	2	0.01	0.3	1	1	0.01	0.01	1	1	0.01	1	1	0.01	1	0.001	3	
Method Code	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP										
GXR-4 Meas	3.4	6.60	95	107	2	15	1.02	<0.3	15	45	6380	2.98	17	<1	2.96	1.61	10	149	292	0.51	41	0.129
GXR-4 Cert	4.0	7.20	98.0	1640	1.90	19.0	1.01	0.860	14.6	64.0	6520	3.09	20.0	0.110	4.01	1.66	11.1	155	310	0.564	42.0	0.120
SDC-11 Meas	8.04	8	613	3	1.02	18	45	29	45.6	20	<1	2.47	0.92	32	863	1.41	36	0.051	21			
SDC-11 Cert	8.34	0.220	630	3.00	1.00	18.0	64.00	30.00	4.82	21.00	0.20	2.72	1.02	34.00	880.00	1.52	38.0	0.0690	25.00			
GXR-6 Meas	0.3	13.3	219	>1000	1	<2	0.17	<0.3	14	49	69	5.51	27	<1	1.69	0.57	32	1080	<1	0.09	27	0.033
GXR-6 Cert	1.30	17.7	330	1300	1.40	0.290	0.180	1.00	13.8	96.0	66.0	5.58	35.0	0.0680	1.87	0.609	32.0	1010	2.40	0.104	27.0	0.0350
SAR-M (U.S.G.S.) Meas	3.6	4.95	35	739	3	<2	0.50	4.3	11	305	3.00	14	2.57	0.43	27	4530	11	1.07	43	0.063	923	
SAR-M (U.S.G.S.) Cert	3.64	6.30	38.8	801	2.20	1.94	0.61	5.27	10.70	331.0000	2.99	17	2.94	0.50	27.4	5220	13.1	1.140	41.5	0.07	982	
DNC-1a Meas			96						54	155	92					4				242		
DNC-1a Cert			118						57.0	270	100.00					5.20				247		
SBC-1 Meas			22	706	3	<2	<0.3	23	66	31	24					136	2			83		28
SBC-1 Cert			25.7	788.0	3.20	0.70	0.40	22.7	109	31.0000	27.0					163.0	2.40			82.8		35.0
55251 Orig	<0.3	6.25	<3	149	<1	<2	0.3	<0.3	37	154	110	6.46	16	<1	0.15	2.58	26	1300	<1	1.35	93	0.026
55251 Dup	<0.3	6.30	<3	149	<1	<2	10.3	<0.3	36	152	107	6.49	17	<1	0.15	2.60	26	1300	<1	1.36	92	0.026
55290 Orig	1.1	8.04	101	153	4	2	2.38	<0.3	22	56	79	5.96	22	<1	3.68	1.71	2	462	<1	3.07	75	0.085
55290 Dup	1.0	7.97	97	144	4	<2	2.29	<0.3	21	49	75	5.75	21	<1	3.40	1.66	2	432	<1	2.94	74	0.081
55292 Orig	<0.3	4.00	<3	8	<1	<2	9.32	<0.3	55	135	53	8.25	14	<1	0.02	2.07	19	1300	<1	0.14	58	0.030
55292 Dup	<0.3	3.92	5	8	<1	5	9.03	<0.3	57	143	49	8.17	14	<1	0.02	2.03	18	1330	8	0.14	55	0.035
55316 Orig	1.1	5.63	<3	22	1	<2	2.93	<0.3	10	165	68	6.23	22	<1	0.04	0.64	10	798	12	2.88	5	0.048
55316 Dup	0.9	5.58	<3	22	1	<2	2.92	<0.3	11	171	68	6.21	22	<1	0.03	0.64	10	808	12	2.86	4	0.048
Method Blank	<0.3	<0.01	<3	<7	<1	<2	<0.01	<0.3	<1		<1	<0.01	<1	<1	<0.01	<1			<1	<0.01	<1	<0.001
Method Blank	<0.3	<0.01	<3	<7	<1	<2	<0.01	<0.3	<1		<1	<0.01	<1	<1	<0.01	<1			<1	<0.01	<1	<0.001
Method Blank	<0.3	<0.01	<3	<7	<1	<2	<0.01	<0.3	<1		<1	<0.01	<1	<1	<0.01	<1			<1	<0.01	<1	<0.001

## QC

Analyte Symbol	Sub	S	Sc	Sr	Te	Tl	U	V	W	Y	Zn	Zr	
Unit Symbol	ppm	%	ppm	ppm	ppm	%	ppm	ppm	ppm	ppm	ppm	ppm	
Lower Limit	5	0.01	4	1	2	0.01	5	10	2	5	1	5	
Method Code	TD-ICP												
GXR-4 Meas	<5	1.66	8	221	5	0.27	<5	<10	85	41	12	70	36
GXR-4 Cert	4.80	1.77	7.70	221	0.970	0.29	3.20	6.20	87.0	30.8	14.0	73.0	186
SDC-11 Meas	<5	16	166	0.11	<5	<10	39	<5	100	100	30		
SDC-11 Cert	0.54	17.00	180.00	0.606	0.70	3.10	102.00	0.80	103.00	290.00			
GXR-6 Meas	<5	0.01	26	38	<2	<5	<10	122	<5	10	131	62	
GXR-6 Cert	3.60	0.0160	27.6	35.0	0.0180	2.20	1.54	186	1.90	14.0	118	110	
SAR-M (U.S.G.S.) Meas	5	7	130	5	0.38	<5	<10	65	19	27	862		
SAR-M (U.S.G.S.) Cert	6.0	7.83	151	0.96	0.38	2.7	3.57	67.2	9.78	28.00	930.0		
DNC-1a Meas	<5	30	123	0.26	0.29			131	13	58	32		
DNC-1a Cert	0.96	31	144.0					148.00		18.0	70.0	38.000	
SBC-1 Meas	<5	20	167					202	5	27	181	101	
SBC-1 Cert	1.01	20.0	178.0					220.0	1.60	36.5	186.0	134.0	
55251 Orig	<5	0.28	30	120	8	0.16	<5	<10	106	<5	13	61	6
55251 Dup	<5	0.28	30	121	<2	0.14	<5	<10	101	<5	13	61	5
55290 Orig	<5	3.05	6	280	7	0.53	<5	10	73	<5	6	90	66
55290 Dup	<5	2.98	5	268	14	0.52	<5	10	69	<5	6	94	64

**Activation Laboratories Ltd.****A14-09465****Report:**

Analyte Symbol	Sb	S	Sc	Sr	Te	Tl	U	V	W	Y	Zn	Zr
Unit Symbol	ppm	%	ppm	ppm	ppm	%	ppm	ppm	ppm	ppm	ppm	ppm
Lower L Limit	5	0.01	4	1	2	0.01	5	10	2	5	1	5
Method Code	TD-ICP											
55292 Orig	<5	0.61	22	74	7	0.39	<5	<10	143	<5	13	82
55292 Dup	<5	0.62	21	73	20	1.13	<5	<10	293	5	13	68
55316 Orig	<5	0.51	13	82	8	0.38	<5	<10	16	8	87	75
55316 Dup	<5	0.51	13	82	8	0.39	<5	<10	16	10	85	80
Method Blank	<5	<0.01	<4	<1	<2	<0.01	<5	<10	<2	<5	<1	<5
Method Blank	<5	<0.01	<4	<1	<2	<0.01	<5	<10	<2	<5	<1	<5
Method Blank	<5	<0.01	<4	<1	<2	<0.01	<5	<10	<2	<5	<1	<5

**Quality Analysis ...**



**Innovative Technologies**

**Date Submitted:** 04-Dec-14  
**Invoice No.:** A14-09582  
**Invoice Date:** 15-Dec-14  
**Your Reference:** 34756 SG14-1829 TERRAX

Techni-Lab Abitibi Inc.(Actlabs)  
184 Rue Principale  
Ste-Germaine-Boule Quebec J0Z 1M0  
Canada

ATTN: Andre Caouette

## CERTIFICATE OF ANALYSIS

106 Pulp samples were submitted for analysis.

The following analytical package was requested:

Code 1F2 Total Digestion ICP(TOTAL)

REPORT      **A14-09582**

This report may be reproduced without our consent, if only selected portions of the report are reproduced, permission must be obtained. If no instructions were given at time of sample submittal regarding excess material, it will be discarded within 90 days of this report. Our liability is limited solely to the analytical cost of these analyses. Test results are representative only of material submitted for analysis.

Notes:

Values which exceed the upper limit should be assayed for accurate numbers.

CERTIFIED BY:



Emmanuel Eseme , Ph.D.  
Quality Control

ACTIVATION LABORATORIES LTD.  
41 Bittern Street, Ancaster, Ontario, Canada, L9G 4V5  
TELEPHONE +905 648-9611 or +1.888.228.5227 FAX +1.905.648.9613  
E-MAIL: Ancaster@actlabs.com ACTLABS GROUP WEBSITE www.actlabs.com







## Activation Laboratories Ltd.

## Report: A14-09582

Analyte Symbol	Ag	Al	As	Ba	Be	Bi	Ca	Cd	Co	Cr	Cu	Fe	Ga	Hg	K	Mg	Li	Mn	Mo	Na	Ni	P	Pb
Unit Symbol	ppm	%	ppm	%	ppm	ppm	ppm	ppm	ppm	%	ppm	ppm											
Lower Limit	0.3	0.01	3	7	1	2	0.01	0.3	1	0.01	1	0.01	1	1	0.01	1	1	1	0.01	1	0.001	3	
Method Code	TD-ICP																						
56000	<0.3	7.18	<3	153	1	<2	6.10	<0.3	41	88	97	10.3	22	<1	0.19	2.01	14	1600	<1	3.02	12	<3	
56001	<0.3	7.72	<3	112	<1	4	4.15	<0.3	40	44	35	11.3	23	<1	0.11	1.63	15	1820	<1	3.28	3	<3	
56002	0.4	6.48	63	157	<1	3	5.37	0.3	34	73	84	10.7	26	<1	0.35	1.47	12	1540	<1	3.25	6	<3	
56003	0.6	6.99	15	54	1	3	8.01	<0.3	31	50	123	9.57	21	<1	0.11	1.47	15	1800	3	3.52	8	<3	
56004	0.3	7.78	9	135	<1	<2	5.52	0.3	43	27	179	12.4	23	<1	0.59	2.32	29	1910	<1	2.86	9	<3	
56005	<0.3	6.59	<3	98	<1	<2	8.26	<0.3	52	174	112	11.8	21	<1	0.97	3.34	25	1880	<1	2.28	110	0.076	
56006	<0.3	4.64	18	311	2	<2	8.11	2.4	35	119	125	9.41	19	<1	0.96	1.89	22	1520	<1	2.15	70	0.091	

**Results**

Analyte Symbol	Sb	S	Sc	Sr	Te	Tl	Tl	U	V	W	Y	Zn	Zr
Unit Symbol	ppm	ppm	ppm	ppm	ppm	%	ppm						
Lower Limit	5	0.01	4	1	2	0.01	5	10	2	5	1	1	5
Method Code	TD-ICP												
55451	<5	0.27	23	155	6	0.38	<5	<10	158	<5	10	81	16
55452	<5	0.44	35	157	<2	0.15	<5	<10	127	<5	14	129	5
55453	<5	0.24	37	226	<2	0.13	<5	<10	156	<5	17	130	7
55454	<5	0.20	42	216	3	0.20	<5	<10	226	<5	17	109	9
55455	<5	1.42	31	227	<2	0.45	<5	<10	137	<5	9	93	47
55456	<5	0.12	61	115	<2	0.20	<5	<10	112	<5	11	71	17
55457	<5	0.34	49	187	2	0.42	<5	<10	122	<5	9	207	31
55458	<5	0.23	55	152	<2	0.34	<5	<10	99	<5	9	139	24
55459	<5	0.29	35	146	15	1.71	<5	<10	240	8	17	162	36
55460	<5	0.31	<4	281	<2	0.21	<5	10	33	5	15	52	158
55461	<5	1.54	21	117	4	0.70	<5	<10	121	<5	9	189	28
55462	<5	1.37	23	91	5	0.57	<5	<10	57	<5	9	186	27
55463	<5	0.04	29	219	<2	0.21	<5	<10	4	<5	64	167	37
55464	<5	0.36	34	139	5	0.17	<5	<10	5	<5	69	199	23
55465	<5	3.13	5	283	10	0.56	<5	10	72	<5	6	89	66
55466	<5	1.32	33	187	8	0.52	<5	<10	9	<5	66	148	43
55467	<5	0.06	35	176	4	0.13	<5	<10	5	<5	72	208	17
55468	<5	0.09	34	170	4	0.23	<5	<10	4	6	73	229	25
55469	<5	0.09	34	183	<2	0.23	<5	<10	5	<5	81	211	45
55470	<5	0.80	32	164	6	0.65	<5	<10	79	<5	55	163	59
55471	<5	0.38	27	207	9	0.67	<5	<10	246	7	16	78	46
55472	<5	0.29	36	97	3	0.36	<5	<10	186	<5	18	84	8
55473	<5	0.22	38	114	7	0.32	<5	<10	171	<5	18	90	6
55474	<5	0.23	37	117	<2	0.16	<5	<10	126	<5	17	100	5
55475	<5	0.23	35	114	<2	0.22	<5	<10	130	<5	17	94	6
55476	<5	0.33	36	131	<2	0.23	<5	<10	132	<5	17	85	<5
55477	<5	0.22	32	123	4	0.27	<5	<10	128	<5	15	75	<5
55478	<5	0.21	35	94	<2	0.18	<5	<10	116	<5	15	84	5
55479	<5	0.17	37	116	4	0.20	<5	<10	131	<5	16	83	7
55480	<5	0.13	9	31	<2	0.13	<5	<10	57	<5	4	24	8
55481	<5	0.20	38	117	6	0.44	<5	<10	197	<5	18	85	7
55482	<5	0.16	38	117	7	0.24	<5	<10	157	<5	16	81	5
55483	<5	0.18	40	126	6	0.18	<5	<10	125	<5	17	82	<5
55484	<5	0.14	33	119	<2	0.25	<5	<10	141	<5	13	141	<5
55485	<5	0.34	4	320	6	0.22	<5	10	34	<5	17	77	159
55486	<5	0.18	32	97	10	0.23	<5	<10	126	<5	7	71	12
55487	<5	0.49	33	131	<2	0.33	<5	<10	155	<5	7	70	20
55488	<5	0.20	35	106	6	0.19	<5	<10	115	<5	18	115	<5
55489	<5	0.19	38	163	<2	0.23	<5	<10	124	<5	16	82	<5
55490	<5	2.73	6	359	10	0.62	<5	10	80	<5	7	61	77
55491	<5	0.20	35	94	<2	0.16	<5	<10	118	<5	13	77	7
55492	<5	0.40	32	333	3	0.29	<5	<10	136	<5	10	70	17
55493	<5	0.33	34	175	<2	0.14	<5	<10	108	<5	11	75	6
55494	<5	0.08	39	155	6	0.34	<5	190	205	<5	19	92	5
55495	<5	0.09	38	216	4	0.26	<5	<10	132	<5	17	83	15
55496	<5	1.23	20	128	7	0.42	<5	<10	155	7	7	120	73
55497	<5	0.37	18	101	<2	0.20	<5	<10	95	<5	9	186	40
55498	<5	0.12	28	106	<2	0.21	<5	<10	105	<5	11	80	25
55499	<5	0.12	34	54	9	0.58	<5	<10	242	<5	12	93	9

Analyte Symbol	Stb	S	Sc	Sr	Te	Tl	U	V	W	Y	Zn	Zr
Unit Symbol	ppm	%	ppm	ppm	%	ppm						
Lower Limit	5	0.01	4	1	2	0.01	5	10	2	5	1	5
Method Code	TD-ICP											
559500	<5	0.15	36	159	6	0.28	<5	<10	153	<5	18	110
55951	<5	0.54	40	173	<2	0.29	<5	<10	380	<5	11	108
55952	<5	0.32	49	150	<2	0.11	<5	<10	452	<5	9	104
55953	<5	0.20	55	121	<2	0.23	<5	<10	532	<5	19	119
55954	<5	0.17	57	126	<2	0.23	<5	<10	473	<5	19	117
55955	<5	0.11	56	118	<2	0.31	<5	<10	496	<5	19	124
55956	<5	0.18	58	140	5	1.04	<5	10	757	<5	19	116
55957	<5	0.18	56	131	<2	0.32	<5	<10	414	<5	19	120
55958	<5	0.13	20	79	5	0.32	<5	<10	131	<5	7	62
55959	<5	0.17	19	78	6	0.27	<5	<10	129	<5	6	84
55960	<5	0.34	<4	314	3	0.22	<5	10	33	<5	16	57
55961	<5	0.20	17	85	3	0.38	<5	10	125	<5	6	77
55962	<5	0.28	20	85	<2	0.32	<5	<10	233	<5	6	160
55963	<5	0.76	51	139	4	0.34	<5	<10	420	<5	8	103
55964	<5	0.29	54	127	<2	0.12	<5	<10	387	<5	9	116
55965	<5	3.19	5	293	11	0.57	<5	10	75	<5	6	90
55966	<5	1.80	39	158	4	0.37	<5	<10	145	<5	9	74
55967	<5	0.38	42	60	5	0.16	<5	<10	206	<5	12	74
55968	<5	0.24	28	214	<2	0.30	<5	<10	121	<5	41	20
55969	<5	0.13	39	235	<2	0.24	<5	<10	126	<5	10	55
55970	<5	0.13	64	152	2	0.21	<5	<10	124	<5	11	76
55971	<5	0.11	44	203	3	0.19	<5	<10	80	<5	14	95
55972	<5	0.61	21	602	4	0.34	<5	<10	115	<5	17	117
55973	<5	0.37	13	418	<2	0.16	<5	<10	36	<5	19	138
55974	<5	0.21	7	103	<2	0.23	<5	<10	47	<5	7	50
55975	<5	0.23	6	91	<2	0.27	<5	<10	39	<5	6	41
55976	<5	0.37	17	221	<2	0.21	<5	10	71	<5	15	135
55977	<5	0.35	5	116	3	0.62	<5	<10	50	<5	8	38
55978	<5	0.71	19	273	6	0.33	<5	20	111	<5	9	90
55979	<5	0.06	14	315	<2	0.11	<5	<10	24	<5	21	135
55980	<5	0.33	6	432	<2	0.14	<5	10	8	<5	29	139
55981	<5	1.76	4	403	4	0.48	<5	10	12	<5	30	128
55982	<5	0.33	4	368	3	0.16	<5	10	11	<5	28	147
55983	<5	1.13	5	395	<2	0.38	<5	20	38	<5	25	86
55984	<5	1.75	10	297	<2	0.37	<5	10	98	<5	23	57
55985	<5	1.41	9	295	2	0.38	<5	20	84	<5	25	73
55986	<5	0.35	<4	317	<2	0.22	<5	10	35	<5	17	55
55987	<5	0.57	6	250	2	0.46	<5	10	43	<5	25	118
55988	5	0.76	<4	347	5	0.71	<5	10	47	<5	23	119
55989	<5	0.29	21	86	<2	0.37	<5	<10	147	<5	5	63
55990	<5	2.72	6	349	7	0.60	<5	10	79	<5	7	60
55991	<5	0.14	18	104	3	0.28	<5	<10	124	<5	5	81
55992	<5	0.16	18	131	4	0.30	<5	<10	124	<5	6	81
55993	<5	0.17	18	110	5	0.28	<5	<10	127	<5	5	83
55994	<5	0.12	18	95	4	0.28	<5	<10	122	<5	5	83
55995	<5	0.16	18	92	<2	0.30	<5	<10	128	<5	6	81
55996	<5	0.15	32	139	<2	0.31	<5	<10	138	<5	8	74
55997	<5	0.66	46	425	<2	0.50	<5	<10	594	<5	8	139
55998	5	0.50	16	193	17	1.67	<5	<10	269	7	23	141
55999	<5	0.15	27	142	4	0.44	<5	<10	178	6	20	130

**Activation Laboratories Ltd.****A14-09582****Report:**

Analyte Symbol	Sb	S	Sc	Sr	Te	Ti	Tl	U	V	W	Y	Zn	Zr
Unit Symbol	ppm	%	ppm	ppm	ppm	%	ppm						
Lower Limit	5	0.01	4	1	2	0.01	5	10	2	5	1	1	5
Method Code	TD-ICP												
56000	<5	0.59	37	164	3	0.33	<5	<10	81	>5	18	105	9
56001	<5	0.27	36	197	<2	0.08	<5	<10	41	<5	24	125	<5
56002	<5	2.13	32	235	<2	0.47	<5	<10	48	<5	18	112	6
56003	<5	0.74	5	286	2	0.54	<5	20	83	<5	25	105	166
56004	<5	0.68	13	252	4	0.41	<5	10	82	<5	27	142	108
56005	<5	0.92	34	292	<2	0.35	<5	<10	125	<5	16	122	44
56006	<5	0.71	30	425	<2	0.31	<5	<10	79	8	32	607	42

Analyte Symbol	Ag	Al	As	Ba	Be	Bi	Cd	Co	Cr	Cu	Fe	Ga	Hg	K	Mg	Li	Mn	Mo	Na	Ni	P	Pb	
	ppm	%	ppm	ppm	ppm	%	ppm	ppm	ppm	ppm	%	ppm	ppm	%	ppm	ppm	ppm	ppm	ppm	%	ppm	ppm	
Lower Limit	0.3	0.01	3	7	1	2	0.01	0.3	1	0.01	1	0.01	0.01	1	1	0.01	1	0.01	1	0.001	3		
Method Code	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP										
GXR-4 Meas	3.6	6.76	102	80	2	15	1.03	0.3	14	51	6540	3.09	16	<1	3.01	1.65	11	154	314	0.48	40	0.131	
GXR-4 Cert	4.0	7.20	98.0	1640	1.90	19.0	1.01	0.860	14.6	64.0	6520	3.09	20.0	0.110	4.01	1.66	11.1	155	310	0.564	42.0	0.120	
GXR-4 Meas	3.5	6.82	102	91	2	11	1.03	<0.3	13	44	6640	3.11	17	<1	3.36	1.65	10	149	308	0.49	39	0.131	
GXR-4 Cert	4.0	7.20	98.0	1640	1.90	19.0	1.01	0.860	14.6	64.0	6520	3.09	20.0	0.110	4.01	1.66	11.1	155	310	0.564	42.0	0.120	
SDC-1 Meas	8.98	9	630	3	1.11				19	51		32	5.16	22	<1	2.46	1.03	34	951		1.52	36	0.057
SDC-1 Cert	8.34	0.220	630	3.00		1.00			18.0	64.00	30.000	4.82	21.00	0.20	2.72	1.02	34.00	880.00		1.52	38.0	0.0590	
SDC-1 Meas	8.52	9	601	3		1.09			18	48		31	4.96	22	<1	2.40	1.00	33	921		1.49	37	0.054
SDC-1 Cert	8.34	0.220	630	3.00		1.00			18.0	64.00	30.000	4.82	21.00	0.20	2.72	1.02	34.00	880.00		1.52	38.0	0.0590	
GXR-6 Meas	0.5	12.4	306	>1000	<1	2	0.16	<0.3	13	57	68	5.39	28	<1	1.81	0.56	30	1100	2	0.09	25	0.0337	
GXR-6 Cert	1.30	17.7	330	1300	1.40	2.90	0.180	1.00	13.8	96.0	66.0	5.58	35.0	0.0680	1.87	0.609	32.0	1010	2.40	0.104	27.0	0.0350	
GXR-6 Meas	0.4	13.7	249	>1000	1	<2	0.18	<0.3	13	70	5.75	29	<1	1.79	0.61	32	1110	<1	0.09	26	0.0335		
GXR-6 Cert	1.30	17.7	330	1300	1.40	2.90	0.180	1.00	13.8	66.0	5.58	35.0	0.0680	1.87	0.609	32.0	1010	2.40	0.104	27.0	0.0350		
SAR-M (U.S.G.S.)	4.2	6.53	35	776	4	2	0.64	4.9	11	326	3.45	15			3.03	0.50	28	5050	7	1.16	47	0.062	
Meas																					1020		
SAR-M (U.S.G.S.)	3.64	6.30	38.8	801	2.20	1.94	0.61	5.27	10.70		331.0000	2.99	17		2.94	0.50	27.4	5220	13.1	1.140	41.5	0.07	
Cert																					982		
SAR-M (U.S.G.S.)	3.5	6.20	28	712	3	<2	0.63	4.8	10	327	3.31	16	2.79	0.48	29	4960	4	1.11	44	0.061			
Meas																					983		
SAR-M (U.S.G.S.)	3.64	6.30	38.8	801	2.20	1.94	0.61	5.27	10.70		331.0000	2.99	17		2.94	0.50	27.4	5220	13.1	1.140	41.5	0.07	
Cert																					261		
DNC-1a Meas																					247		
DNC-1a Cert																					249		
DNC-1a Meas																					247		
DNC-1a Cert																					83		
SBC-1 Meas																					28		
SBC-1 Cert																					35.0		
SBC-1 Meas																					29		
SBC-1 Cert																					35.0		
SBC-1 Meas	25	25.7	788.0	3.20	0.70	0.40	22.7	109	31.0000	27.0						163.0	2.40						
SBC-1 Cert	25	25.7	788.0	3.20	0.70	0.40	22.7	109	31.0000	27.0						149	2						
SBC-1 Meas	<0.3	6.89	6	17	<1	<2	9.35	<0.3	41	187	131	B.15	17	<1	0.09	3.41	25	1390	1	1.61	103	0.024	
SBC-1 Cert	<0.3	6.83	4	17	<1	<2	9.30	<0.3	41	190	134	B.06	17	<1	0.09	3.37	25	1380	1	1.59	104	0.024	
SBC-1 Meas	<0.3	4.64	14	66	<1	<2	6.11	<0.3	44	157	145	B.63	17	<1	0.16	2.18	17	1260	<1	1.35	30	0.041	
SBC-1 Cert	<0.3	4.68	12	66	<1	<2	6.15	<0.3	42	138	142	B.60	18	<1	0.16	2.17	17	1260	<1	1.34	29	0.041	
SBC-1 Meas	<0.3	1.27	<3	11	<1	<2	25.3	<0.3	13	19	8	3.72	4	<1	0.02	0.75	5	3380	<1	0.22	4	0.004	
SBC-1 Cert	<0.3	1.17	4	10	<1	2	23.7	<0.3	12	17	8	3.45	3	<1	0.02	0.69	5	3200	<1	0.20	3	0.005	
SBC-1 Meas	<0.3	2.62	<3	144	1	<2	6.66	0.5	82	751	250	9.12	10	<1	0.66	8.45	26	1470	<1	0.22	830	0.022	
SBC-1 Cert	<0.3	2.72	<3	146	1	<2	6.82	0.4	85	901	259	9.25	11	<1	0.69	8.71	26	1500	<1	0.22	852	0.022	
Method Blank	<0.3	<0.01	<3	<7	<1	<2	<0.01	<0.3	<1					<1	<0.01	<0.01	<1			<0.01	<3		
Method Blank	<0.3	<0.01	<3	<7	<1	<2	<0.01	<0.3	<1					<1	<0.01	<0.01	<1			<0.01	<3		
Method Blank	<0.3	<0.01	<3	<7	<1	<2	<0.01	<0.3	<1					<1	<0.01	<0.01	<1			<0.01	<3		
Method Blank	<0.3	<0.01	<3	<7	<1	<2	<0.01	<0.3	<1					<1	<0.01	<0.01	<1			<0.01	<3		
Method Blank	<0.3	0.02	<3	<7	<1	<2	<0.01	<0.3	<1					<1	<0.01	<0.01	<1			<0.01	<3		
QC																							

Analyte Symbol	Sb	S	Sc	Sr	Te	Ti	Tl	U	V	W	Y	Zn	Zr
Unit Symbol	ppm	%	ppm	ppm	ppm	%	ppm						
Lower Limit	5	0.01	4	1	2	0.01	5	10	2	5	1	1	5
Method Code	TD-ICP												
GXR4 Meas	<5	1.74	8	212	4	0.29	<5	<10	88	41	13	73	37
GXR4 Cert	4.80	1.77	7.70	221	0.970	0.29	3.20	6.20	87.0	30.8	14.0	73.0	186
GXR4 Meas	<5	1.75	8	211	8	0.29	<5	<10	86	39	13	72	36
GXR4 Cert	4.80	1.77	7.70	221	0.970	0.29	3.20	6.20	87.0	30.8	14.0	73.0	186
SDC-1 Meas	<5	17	182		0.23	<5	<10	57	<5	108	11	128	36
SDC-1 Cert	0.54		17.00	180.00	0.606	0.70	3.10	102.00	0.80		103.00	290.00	
SDC-1 Meas	<5	16	176		0.18	<5	<10	50	<5		106	106	37
SDC-1 Cert	0.54		17.00	180.00	0.606	0.70	3.10	102.00	0.80		103.00	290.00	
GXR-6 Meas	<5	0.01	25	36	3	<5	<10	179	<5	11	11	128	93
GXR-6 Cert	3.60	0.0160	27.6	36.0	0.0180	2.20	1.54	186	1.90	14.0	118	110	
GXR-6 Meas	<5	0.02	26	40	<2		<5	<10	130	<5	10	133	62
GXR-6 Cert	3.60	0.0160	27.6	35.0	0.0180	2.20	1.54	186	1.90	14.0	118	110	
SARM (U.S.G.S.) Meas	<5	10	154	3	0.38	<5	<10	67	18	35	963		
SARM (U.S.G.S.) Cert	6.0		7.83	151	0.96	0.38	2.7	3.57	67.2	9.78	28.00	930.0	
SARM (U.S.G.S.) Meas	<5	9	150	4	0.28	<5	<10	54	13	34		925	
SARM (U.S.G.S.) Cert	6.0		7.83	151	0.96	0.38	2.7	3.57	67.2	9.78	28.00	930.0	
DNC-1a Meas	<5	31	136		0.30			144		15	64	34	
DNC-1a Cert	0.96	31	144.0		0.29			148.00		18.0	70.0	38.000	
DNC-1a Meas	<5	30	130		0.29			141		14	61	32	
DNC-1a Cert	0.96	31	144.0		0.29			148.00		18.0	70.0	38.000	
SBC-1 Meas	<5	20	172		0.49	<5	<10	207	7	28	185	104	
SBC-1 Cert	1.01	20.0	178.0		0.51	0.89	5.76	220.0	1.60	36.5	186.0	134.0	
SBC-1 Meas	<5	21	186		0.54	<5	<10	141	<5	29	192	107	
SBC-1 Cert	1.01	20.0	178.0		0.51	0.89	5.76	220.0	1.60	36.5	186.0	134.0	
55477 Orig	<5	0.22	32	124	4	0.27	<5	<10	129	<5	15	75	<5
55477 Dup	<5	0.22	32	123	3	0.28	<5	<10	126	<5	15	75	<5
55986 Orig	<5	0.15	32	137	<2	0.28	<5	<10	130	<5	8	74	15
55986 Dup	<5	0.15	33	141	<2	0.34	<5	<10	146	<5	8	74	35
Method Blank	<5	<0.01	<4	<1	<2	<0.01	<5	<10	<2	<5	<1	<5	
Method Blank	<5	<0.01	<4	<1	<2	<0.01	<5	<10	2	<5	<1	<5	
Method Blank	<5	<0.01	<4	<1	<2	<0.01	<5	<10	4	<5	<1	<5	
Method Blank	<5	<0.01	<4	<1	<2	<0.01	<5	<10	2	<5	<1	<5	
Method Blank	<5	<0.01	<4	<1	<2	<0.01	<5	<10	2	<5	<1	<5	
Method Blank	<5	<0.01	<4	<1	<2	<0.01	<5	<10	2	<5	<1	<5	
Method Blank	<5	<0.01	<4	<1	<2	<0.01	<5	<10	2	<5	<1	<5	
Method Blank	<5	<0.01	<4	<1	<2	<0.01	<5	<10	2	<5	<1	<5	

*Quality Analysis ...*



*Innovative Technologies*

**Date Submitted:** 04-Dec-14  
**Invoice No.:** A14-09584  
**Invoice Date:** 15-Dec-14  
**Your Reference:** 34746 SG14-1818 TERRAX

Techni-Lab Abitibi Inc.(Actlabs)  
184 Rue Principale  
Ste-Germaine-Boule Quebec J0Z 1M0  
Canada

ATTN: Andre Caouette

## CERTIFICATE OF ANALYSIS

134 Pulp samples were submitted for analysis.

The following analytical package was requested:

Code 1F2 Total Digestion ICP(TOTAL)

REPORT      A14-09584

This report may be reproduced without our consent. If only selected portions of the report are reproduced, permission must be obtained. If no instructions were given at time of sample submittal regarding excess material, it will be discarded within 90 days of this report. Our liability is limited solely to the analytical cost of these analyses. Test results are representative only of material submitted for analysis.

**Notes:**

Values which exceed the upper limit should be assayed for accurate numbers.

CERTIFIED BY:

A handwritten signature in black ink, appearing to read "Emmanuel Eseme".

Emmanuel Eseme, Ph.D.  
Quality Control

ACTIVATION LABORATORIES LTD.  
41 Bittern Street, Ancaster, Ontario, Canada, L9G 4V5  
TELEPHONE +905 648-9611 or +1.888.228.5227 FAX +1.905.648.9613  
E-MAIL [Ancaster@actlabs.com](mailto:Ancaster@actlabs.com) ACTLABS GROUP WEBSITE [www.actlabs.com](http://www.actlabs.com)



## Results

Analyte Symbol	Ag	Al	As	Ba	Be	Bi	Cd	Co	Cr	Cu	Fe	Ga	Hg	K	Mg	Li	Mn	Mo	Na	Ni	P	Pb	
Unit Symbol	ppm	%	ppm	%	ppm	ppm	%	ppm	ppm	ppm	ppm	ppm	%	ppm	%								
Lower Limit	0.3	0.01	3	7	1	2	0.01	0.3	1	0.01	1	0.01	0.01	1	1	0.01	1	1	0.01	1	0.001	3	
Method Code	TD-ICP																						
55317	0.4	6.42	<3	25.3	1	<2	5.70	2.7	41	141	10.2	23	<1	0.77	1.84	19	1330	<1	2.44	15	0.051	4	
55318	<0.3	6.79	<3	22.2	<1	4	4.95	<0.3	38	58	44	9.09	19	<1	0.73	1.90	16	1230	<1	3.02	15	0.058	<3
55319	<0.3	9.03	<3	32	<1	<2	3.68	<0.3	23	35	10	7.09	18	<1	0.06	1.79	17	815	2	4.47	5	0.086	<3
55320	0.5	9.03	5	30	<1	<2	4.28	<0.3	24	30	10	7.14	18	<1	0.06	1.81	18	876	3	4.40	7	0.083	<3
55321	<0.3	8.50	<3	19.9	1	3	5.04	<0.3	22	30	18	6.12	22	<1	0.49	1.10	19	839	2	4.78	4	0.086	<3
55322	0.3	6.31	<3	46	1	3	6.29	0.3	30	89	38	10.2	23	<1	0.02	0.96	23	1230	<1	2.54	5	0.102	<3
55323	<0.3	6.61	5	59	<1	<2	4.61	<0.3	34	67	28	12.0	23	<1	0.17	1.52	17	1850	<1	2.55	6	0.088	<3
55324	<0.3	6.44	3	30.7	1	<2	6.10	0.5	46	76	65	13.1	27	<1	0.83	2.41	27	1910	<1	2.04	14	0.059	<3
55325	<0.3	7.34	<3	37.3	1	<2	5.51	<0.3	44	57	129	11.8	24	<1	0.87	2.50	30	1670	<1	2.31	15	0.058	<3
55326	<0.3	6.86	<3	50	<1	2	4.92	0.4	36	89	33	12.4	25	<1	0.18	1.91	20	1900	<1	2.40	5	0.085	<3
55327	<0.3	5.96	5	69	<1	<2	5.11	0.4	28	75	29	12.2	24	<1	0.18	0.97	14	1770	<1	2.34	3	0.140	3
55328	<0.3	6.00	5	18.7	1	<2	4.91	<0.3	20	105	17	10.9	26	<1	0.58	0.37	11	1400	<1	2.45	4	0.126	<3
55329	0.3	5.70	<3	80	<1	4	5.63	<0.3	17	83	27	9.49	23	<1	0.21	0.51	9	1250	<1	3.04	3	0.115	4
55330	0.5	5.56	9	72	1	2	4.84	0.3	18	275	42	6.83	20	<1	0.56	1.56	17	1140	8	2.55	32	0.069	<3
55331	0.8	5.93	7	12.9	2	<2	3.48	<0.3	7	136	39	7.77	27	<1	0.75	0.23	12	988	9	2.91	3	0.068	<3
55332	0.6	6.02	3	11.4	2	3	2.79	<0.3	8	166	27	8.46	26	<1	0.57	0.31	9	1010	12	3.13	4	0.080	<3
55333	0.5	6.06	<3	10.6	2	3	3.38	<0.3	7	147	11	9.19	26	<1	0.29	0.28	9	1280	11	3.43	6	0.091	<3
55334	0.5	6.02	9	45	2	3	3.45	<0.3	7	166	18	9.85	27	<1	0.11	0.38	9	1360	11	3.30	5	0.104	<3
55335	0.5	5.38	<3	47.1	1	<2	13.9	<0.3	4	71	38	1.70	13	<1	1.91	1.06	10	946	7	2.14	12	0.039	4
55336	0.5	5.18	<3	38	1	3	3.19	<0.3	8	148	15	8.94	25	<1	0.09	0.44	9	1430	10	3.15	3	0.120	<3
55337	0.5	5.92	<3	87	1	3	3.16	<0.3	8	142	16	8.92	24	<1	0.15	0.51	7	1530	9	3.36	3	0.132	<3
55338	<0.3	5.99	<3	50	2	<2	3.41	<0.3	8	148	9	8.75	25	<1	0.10	0.49	7	1500	2	3.37	4	0.116	<3
55339	<0.3	6.09	5	50	1	<2	3.37	<0.3	10	137	5	10.2	26	<1	0.08	0.56	7	1790	2	3.36	3	0.139	<3
55340	<0.3	6.05	4	47	1	<2	3.13	<0.3	10	153	8	9.92	26	<1	0.08	0.54	7	1770	3	3.29	4	0.131	<3
55341	<0.3	6.19	<3	100	1	<2	3.92	<0.3	14	125	18	11.5	25	<1	0.11	0.70	6	2470	<1	3.42	4	0.166	<3
55342	<0.3	6.07	<3	10.3	1	4	4.22	<0.3	15	139	13	11.1	26	<1	0.11	0.70	7	2350	2	3.26	3	0.159	<3
55343	<0.3	6.44	7	93	1	6	4.66	<0.3	21	113	8	13.5	30	<1	0.08	0.85	10	2630	2	3.40	8	0.165	<3
55344	<0.3	6.50	<3	232	<1	<2	7.48	<0.3	36	122	69	8.13	18	<1	0.94	3.14	21	1320	1	1.81	92	0.023	<3
55345	<0.3	6.23	<3	112	<1	<2	3.09	<0.3	15	231	12	2.93	12	<1	0.47	1.48	21	437	10	2.51	69	0.033	<3
55346	<0.3	8.16	<3	92	<1	<2	5.13	<0.3	44	129	69	10.1	22	<1	0.42	3.60	23	1350	<1	2.55	60	0.040	<3
55347	<0.3	7.84	<3	32	<1	5	5.54	<0.3	46	156	102	9.95	21	<1	0.16	3.72	19	1290	<1	2.19	74	0.048	<3
55348	<0.3	7.08	<3	79	<1	<2	7.53	<0.3	40	220	65	9.08	18	<1	0.23	3.43	22	1400	<1	1.80	82	0.037	<3
55349	<0.3	7.88	<3	23	<1	<2	7.91	<0.3	37	161	132	8.97	21	<1	0.07	3.53	20	1270	<1	1.67	73	0.044	<3
55350	<0.3	7.98	3	28	<1	<2	6.58	<0.3	45	124	95	10.1	21	<1	0.13	3.57	15	1380	<1	2.31	85	0.041	<3
55351	<0.3	5.66	<3	7	<1	<2	9.19	<0.3	33	177	81	6.89	13	<1	0.03	3.00	26	1260	<1	0.88	89	0.020	<3
55352	<0.3	9.20	<3	47	<1	5	7.25	<0.3	56	103	10.6	20	<1	0.08	4.75	35	1570	1	1.62	137	0.047	<3	
55353	<0.3	6.52	4	42	<1	<2	7.46	<0.3	41	195	124	7.84	20	<1	0.05	3.22	26	1100	5	1.43	101	0.033	5
55354	<0.3	3.54	<3	20	<1	<2	19.5	<0.3	17	106	32	4.87	9	<1	0.07	1.98	19	1120	4	0.55	40	0.016	9
55355	<0.3	6.96	<3	41	<1	<2	8.62	<0.3	39	185	114	7.57	18	<1	0.07	3.23	49	1030	1	1.34	102	0.028	<3
55356	<0.3	7.16	<3	34	<1	<2	9.29	<0.3	40	193	89	6.76	14	<1	0.16	3.09	32	1350	<1	2.00	103	0.023	<3
55357	<0.3	7.24	3	40	<1	3	6.74	<0.3	46	266	116	9.29	16	<1	0.13	3.41	29	1540	3	1.84	102	0.030	<3
55358	<0.3	7.62	<3	49	<1	<2	7.46	<0.3	47	335	133	9.57	17	<1	0.14	4.27	29	1600	<1	1.83	123	0.072	<3
55359	<0.3	7.08	12	114	<1	<2	7.13	0.4	44	242	137	9.07	15	<1	0.20	3.59	36	1410	<1	1.36	106	0.026	<3
55360	0.3	5.54	4	51.7	1	<2	13.8	<0.3	4	94	51	1.63	13	<1	1.98	0.99	10	893	10	2.18	13	0.037	7
55361	<0.3	4.81	<3	239	<1	<2	3.97	<0.3	30	269	84	5.54	11	<1	0.35	2.39	28	783	9	0.74	72	0.020	<3
55362	<0.3	7.56	<3	77	<1	2	6.93	<0.3	47	145	139	8.65	17	<1	0.11	3.65	37	1400	<1	1.70	116	0.025	<3
55363	<0.3	6.66	<3	54	<1	<2	7.19	0.9	54	276	102	8.52	18	<1	0.15	2.47	18	1520	<1	1.50	142	0.052	<3
55364	<0.3	5.03	<3	107	1	<2	7.31	0.7	43	273	101	8.52	12	<1	0.15	2.47	18	1520	<1	3.14	99	0.022	<3
55365	1.2	8.65	97	120	4	4	2.48	0.4	21	56	84	6.34	23	<1	3.59	1.80	2	494	<1	3.14	99	0.089	53



## Activation Laboratories Ltd.

## Report: A14-09584

Analyte Symbol	Ag	Al	As	Ba	Be	Bi	Ca	Cd	Co	Cr	Cu	Fe	Ga	Hg	K	Mg	Li	Na	Mo	Mn	Ni	P	Pb
Unit Symbol	ppm	%	ppm	ppm																			
Lower Limit	0.3	0.01	3	7	1	2	0.01	0.3	1	0.01	1	0.01	0.01	1	1	0.01	1	0.01	1	0.001	1	0.001	
Method Code	TD-ICP																						
55416	<0.3	8.05	<3	46	<1	3	7.82	<0.3	50	164	9.33	16	<1	0.10	3.97	33	1530	1	1.75	121	<3	0.029	
55417	<0.3	7.33	<3	257	<1	<2	7.64	<0.3	42	164	111	8.20	<1	0.44	3.42	38	1240	<1	1.89	101	0.028	<3	
55418	<0.3	5.96	6	237	1	3	6.78	0.4	37	217	96	7.17	<1	0.34	2.85	29	1280	4	2.21	93	0.029	<3	
55419	<0.3	6.40	14	197	1	3	5.61	<0.3	37	226	97	7.39	<1	0.18	2.92	19	1300	5	3.38	92	0.023	<3	
55420	<0.3	5.81	56	50	1	3	6.03	<0.3	38	249	92	7.03	<1	0.60	2.79	19	1060	10	2.39	97	0.058	4	
55421	<0.3	7.27	4	266	<1	<2	7.09	<0.3	41	212	96	8.06	<1	0.81	3.52	33	1410	<1	2.00	115	0.023	3	
55422	<0.3	7.65	<3	35	<1	<2	7.45	<0.3	45	141	99	8.26	<1	0.07	3.49	41	1290	<1	2.10	121	0.025	<3	
55423	<0.3	6.87	31	48	<1	3	6.95	<0.3	41	200	113	8.02	<1	0.09	3.40	33	1260	3	1.90	114	0.027	<3	
55424	<0.3	7.10	<3	30	<1	3	9.07	<0.3	48	184	131	9.01	<1	0.11	3.11	32	1380	5	1.18	112	0.026	<3	
55425	<0.3	6.83	4	28	<1	3	9.30	<0.3	49	173	134	8.49	<1	0.10	2.91	28	1330	4	1.08	104	0.023	5	
55426	<0.3	7.51	5	181	<1	<2	7.11	0.5	38	127	75	7.78	<1	0.68	2.94	25	1310	1	2.30	87	0.036	<3	
55427	<0.3	6.30	3	66	<1	<2	6.34	0.9	54	64	114	11.1	<1	1.38	2.76	26	1320	<1	1.82	16	0.023	4	
55428	<0.3	4.79	<3	60	1	12	7.30	0.4	83	37	206	14.2	<1	0.12	3.26	15	1960	2	0.42	103	0.054	<3	
55429	<0.3	5.85	<3	189	2	<2	7.94	0.4	72	38	314	14.3	<1	0.47	3.42	19	1940	<1	1.18	86	0.066	4	
55430	<0.3	5.23	<3	167	2	<2	8.71	0.8	76	31	233	15.6	<22	<1	0.38	3.66	21	2080	<1	0.60	112	0.042	4
55431	<0.3	5.82	<3	76	2	<2	8.99	0.4	90	34	264	13.9	<22	<1	0.20	3.48	13	1750	<1	0.66	150	0.046	<3
55432	<0.3	5.25	<3	123	2	<2	8.72	0.4	80	25	399	15.4	<21	<1	0.25	3.60	16	2010	<1	0.78	143	0.051	7
55433	<0.3	5.44	9	158	2	<2	9.33	0.4	81	28	323	14.8	<22	<1	0.37	3.55	18	2000	<1	0.87	103	0.057	3
55434	<0.3	6.77	4	207	2	<2	8.11	0.3	61	45	150	13.6	<24	<1	0.30	3.25	20	2080	<1	1.03	53	0.076	<3
55435	0.4	5.40	<3	494	1	<2	14.2	<0.3	4	70	95	1.95	13	<1	1.98	1.09	10	935	7	2.09	13	0.038	6
55436	<0.3	6.85	<3	154	3	<2	6.34	0.3	51	30	148	12.2	<21	<1	0.24	2.28	19	1730	<1	2.40	14	0.089	3
55437	<0.3	6.72	<3	157	2	<2	6.81	<0.3	43	37	144	11.2	<18	<1	0.19	2.29	16	1870	<1	2.78	10	0.096	<3
55438	<0.3	4.16	4	24	<1	<2	8.29	0.3	72	511	12.0	20	<1	0.04	4.09	26	1760	<1	0.41	197	0.034	<3	
55439	<0.3	3.54	5	122	<1	4	3.61	<0.3	35	240	78	6.37	13	<1	0.19	1.38	8	942	2	1.69	35	0.029	<3
55440	0.8	8.85	57	95	3	10	2.54	0.6	22	53	196	5.92	<22	<1	3.09	1.84	3	514	<1	2.96	76	0.101	49
55441	0.7	5.31	13	34	<1	<2	7.25	<0.3	40	74	85	10.7	<21	<1	0.08	1.92	19	1620	<1	1.08	6	0.030	3
55442	<0.3	4.80	3	162	<1	<2	10.3	<0.3	35	53	28	10.6	<18	<1	0.15	1.73	18	2210	<1	1.04	4	0.031	<3
55443	<0.3	6.63	3	203	<1	<2	5.42	0.3	44	48	70	13.1	<22	<1	0.21	1.96	16	2200	<1	1.92	3	0.042	4
55444	<0.3	4.67	3	150	<1	<2	3.80	<0.3	32	185	83	9.83	17	<1	0.18	1.42	12	1700	<1	1.41	4	0.036	<3
55445	<0.3	5.68	7	326	<1	11	4.26	0.5	49	63	56	13.5	<22	<1	0.31	1.81	14	2190	3	2.26	4	0.055	<3
55446	<0.3	7.02	<3	124	<1	3	5.46	0.3	38	46	86	12.6	<24	<1	0.17	1.87	20	2210	<1	2.41	3	0.037	4
55447	<0.3	6.57	3	140	<1	<2	4.95	0.6	37	43	25	13.8	23	<1	0.21	1.91	16	2110	<1	1.97	2	0.059	3
55448	<0.3	5.93	<3	105	<1	<2	4.65	<0.3	38	94	54	11.2	<24	<1	0.48	1.78	19	1520	<1	2.29	4	0.050	<3
55449	<0.3	6.71	<3	206	<1	3	5.78	<0.3	53	36	45	11.6	<21	<1	0.60	2.66	23	1640	<1	2.29	6	0.023	<3
55450	<0.3	5.88	3	145	<1	<2	6.90	0.6	48	65	66	11.7	<23	<1	0.89	2.33	27	2030	<1	2.04	6	0.025	5

**Results**

Analyte Symbol	Stb	S	Sc	Te	Ti	Ti	U	V	W	Y	Zn	Zr
Unit Symbol	ppm	%	ppm	ppm	%	ppm						
Lower Limit	5	0.01	4	1	0.01	5	10	2	5	1	1	5
Method Code	TD-ICP											
55317	<5	1.09	40	135	<2	0.39	<5	<10	165	13	30	980
55318	<5	1.01	33	143	9	0.57	<5	10	314	<5	19	117
55319	<5	0.15	20	130	6	0.43	<5	20	144	<5	15	61
55320	<5	0.15	20	134	3	0.43	<5	20	144	6	16	79
55321	<5	0.37	18	149	5	0.40	<5	20	125	<5	15	89
55322	<5	2.12	32	126	6	0.45	<5	<10	56	<5	42	98
55323	<5	0.14	40	123	<2	0.11	<5	<10	42	<5	48	134
55324	<5	0.91	48	89	2	0.36	<5	<10	151	5	36	154
55325	<5	0.18	44	148	5	0.18	<5	<10	187	<5	35	116
55326	<5	0.10	41	140	6	0.19	<5	<10	145	<5	54	114
55327	<5	0.47	32	85	<2	0.29	<5	<10	15	<5	59	109
55328	<5	0.54	29	103	6	0.49	<5	<10	10	<5	67	104
55329	<5	0.96	25	162	6	0.52	<5	10	28	<5	49	95
55330	<5	0.59	21	131	4	0.44	<5	<10	72	<5	28	72
55331	<5	1.06	17	99	4	0.47	<5	10	11	<5	38	55
55332	<5	0.93	18	80	3	0.51	<5	10	10	<5	48	59
55333	<5	0.48	18	92	10	0.52	<5	10	9	<5	78	76
55334	<5	0.39	20	102	9	0.52	<5	10	9	<5	75	87
55335	<5	0.32	<4	285	<2	0.21	<5	10	32	<5	17	53
55336	<5	0.03	17	104	10	0.57	<5	10	7	<5	56	91
55337	<5	0.57	23	102	2	0.60	<5	10	9	<5	57	55
55338	<5	0.08	22	106	<2	0.38	<5	10	5	<5	75	91
55339	<5	0.12	24	105	11	0.34	<5	20	5	<5	84	109
55340	<5	0.11	23	102	<2	0.34	<5	10	5	<5	83	105
55341	<5	0.32	29	128	10	0.28	<5	<10	6	<5	86	145
55342	<5	0.52	29	124	8	0.45	<5	<10	6	<5	81	137
55343	<5	0.12	31	145	13	0.65	<5	10	23	<5	85	161
55344	<5	0.25	28	279	<2	0.38	<5	<10	155	<5	12	90
55345	<5	0.04	11	79	9	0.20	<5	<10	67	<5	7	58
55346	<5	0.59	38	105	7	0.41	<5	<10	178	<5	28	62
55347	<5	0.74	37	171	6	0.71	<5	<10	261	<5	26	104
55348	<5	0.17	31	194	5	0.20	<5	<10	120	<5	20	79
55349	<5	0.18	34	121	<2	0.21	<5	<10	124	<5	25	54
55350	<5	0.31	39	147	<2	0.19	<5	<10	133	<5	27	88
55351	<5	0.23	26	95	<2	0.18	<5	<10	112	<5	13	76
55352	<5	0.13	45	125	<2	0.65	<5	<10	277	<5	21	105
55353	<5	0.47	31	93	3	0.38	<5	<10	196	<5	13	67
55354	<5	0.23	27	53	<2	0.09	<5	10	136	<5	12	71
55355	<5	0.39	34	115	6	0.32	<5	<10	164	<5	16	103
55356	<5	0.13	35	96	<2	0.23	<5	<10	128	<5	16	69
55357	<5	0.47	36	157	4	0.57	<5	<10	248	<5	16	92
55358	<5	0.24	37	213	<2	0.40	<5	<10	206	<5	18	123
55359	<5	0.33	36	104	<2	0.23	<5	<10	141	<5	17	178
55360	6	0.34	4	302	3	0.23	<5	10	38	<5	17	76
55361	<5	0.23	25	81	<2	0.34	<5	<10	159	<5	11	51
55362	<5	0.14	37	105	<2	0.39	<5	<10	189	<5	18	83
55363	<5	1.19	46	143	<2	0.32	<5	<10	378	<5	13	174
55364	<5	0.36	15	168	<2	0.15	<5	<10	43	<5	15	269
55365	<5	3.31	6	296	10	0.58	<5	10	76	<5	6	92

## Activation Laboratories Ltd.

Report: A14-09584

Analyte Symbol	Sb	S	Sc	Sr	Te	Ti	U	V	W	Y	Zn	Zr
Unit Symbol	ppm	%	ppm	ppm	%	ppm						
Lower Limit	5	0.01	4	1	2	0.01	5	10	2	5	1	5
Method Code	TD-ICP											
553366	<5	0.65	6	315	<2	0.38	<5	10	26	<5	18	160
553367	<5	0.96	<4	359	10	0.42	<5	10	24	7	23	502
553368	<5	0.79	<4	313	<2	0.51	<5	10	48	7	17	348
553369	<5	0.61	9	339	<2	0.36	<5	<10	45	<5	25	274
553370	<5	0.33	6	380	2	0.20	<5	10	23	<5	28	149
553371	<5	0.83	7	324	8	0.44	<5	10	43	<5	25	115
553372	<5	0.61	7	378	4	0.35	<5	10	26	<5	25	137
553373	<5	0.99	4	349	8	0.39	<5	20	46	<5	25	106
553374	<5	1.75	<4	364	6	0.57	<5	20	77	<5	23	178
553375	<5	3.21	<4	340	6	0.60	<5	20	82	<5	25	145
553376	<5	0.87	6	303	5	0.44	<5	10	44	<5	24	165
553377	<5	0.20	<4	411	7	0.83	<5	10	26	<5	23	165
553378	<5	0.92	<4	491	12	0.66	<5	10	23	<5	24	136
553379	<5	0.49	<4	549	<2	0.34	<5	10	23	<5	28	139
553380	<5	1.47	5	398	2	0.45	<5	20	82	<5	26	78
553381	<5	0.44	14	280	<2	0.18	<5	<10	43	<5	26	136
553382	<5	0.21	14	257	<2	0.22	<5	<10	33	<5	27	149
553383	<5	0.75	10	301	5	0.40	<5	10	63	<5	27	100
553384	<5	0.78	10	300	<2	0.54	<5	340	82	<5	24	87
553385	<5	0.35	5	384	<2	0.24	<5	10	37	<5	17	61
553386	<5	0.31	8	242	2	0.46	<5	10	57	<5	29	200
553387	<5	1.63	<4	361	5	0.48	<5	20	151	<5	27	81
553388	<5	0.43	37	295	14	1.32	<5	<10	604	<5	13	124
553389	<5	1.66	39	218	7	0.49	<5	<10	167	<5	9	94
553390	<5	2.64	6	344	9	0.59	<5	10	77	<5	6	56
553391	<5	0.35	42	158	<2	0.15	<5	<10	153	<5	16	137
553392	<5	0.38	38	212	<2	0.21	<5	<10	110	<5	14	118
553393	<5	0.51	27	276	2	0.27	<5	<10	55	<5	13	87
553394	<5	0.37	40	157	3	0.30	<5	<10	159	<5	13	108
553395	<5	0.89	36	205	<2	0.36	<5	10	22	<5	39	189
553396	<5	0.81	39	253	<2	0.40	<5	<10	40	<5	38	161
553397	<5	0.72	46	109	<2	0.30	<5	<10	8	<5	38	155
553398	<5	0.22	27	123	<2	0.31	<5	<10	147	<5	13	78
553399	<5	0.33	37	130	<2	0.26	<5	<10	121	<5	14	223
554000	<5	0.48	32	138	3	0.33	<5	<10	114	<5	18	106
554001	<5	0.37	37	152	5	0.35	<5	<10	128	<5	17	58
554002	<5	0.25	34	98	<2	0.15	5	<10	104	<5	16	89
554003	<5	0.56	32	158	3	0.40	<5	<10	221	6	10	65
554004	<5	0.28	39	145	12	0.35	<5	<10	187	<5	11	89
554005	<5	0.48	35	139	6	0.35	<5	<10	179	<5	139	17
554006	<5	0.66	37	187	11	0.46	<5	<10	247	<5	13	64
554007	<5	0.12	31	96	<2	0.49	<5	<10	213	6	10	74
554008	<5	0.11	37	95	2	0.26	<5	<10	171	<5	13	83
554009	<5	0.17	36	135	<2	0.26	<5	<10	139	<5	17	87
55410	<5	0.35	4	357	7	0.23	<5	10	35	<5	17	56
55411	<5	0.50	37	122	<2	0.27	<5	<10	122	<5	17	63
55412	<5	0.81	26	123	6	0.44	<5	10	148	<5	18	90
55413	<5	0.88	37	173	5	0.50	<5	<10	212	<5	19	76
55414	<5	0.43	34	149	8	0.56	<5	<10	228	<5	18	88
55415	<5	3.34	6	302	9	0.59	<5	10	80	<5	6	97

Analyte Symbol	Sb	S	Sc	Sr	Te	Tl	U	V	W	Y	Zn	Zr
Unit Symbol	ppm	%	ppm	ppm	ppm	%	ppm	ppm	ppm	ppm	ppm	ppm
Lower Limit	5	0.01	4	1	2	0.01	5	10	2	5	1	5
Method Code	TD-ICP											
55416	<5	0.30	40	159	4	0.38	<5	104	<5	19	89	<5
55417	<5	0.28	33	151	<2	0.22	<5	140	<5	13	87	11
55418	<5	0.34	28	316	2	0.48	<5	<10	229	8	8	125
55419	<5	0.93	30	483	5	0.49	<5	10	227	7	6	71
55420	<5	1.51	28	383	<2	0.45	<5	<10	204	10	7	75
55421	<5	0.17	35	159	2	0.21	<5	<10	125	<5	11	78
55422	<5	0.16	35	127	<2	0.24	<5	<10	135	<5	15	86
55423	<5	1.11	32	133	<2	0.42	<5	<10	203	<5	14	83
55424	<5	0.63	31	152	3	0.51	<5	<10	220	<5	16	125
55425	<5	0.65	31	150	<2	0.47	<5	<10	192	<5	15	124
55426	<5	0.55	27	140	<2	0.39	<5	<10	160	<5	9	215
55427	<5	1.58	47	161	<2	0.38	<5	<10	373	<5	13	203
55428	<5	1.25	23	217	14	1.62	<5	<10	448	<5	12	138
55429	<5	0.23	29	209	5	0.28	<5	<10	213	<5	22	145
55430	<5	0.34	32	139	<2	0.27	<5	<10	265	<5	19	255
55431	<5	0.59	36	228	<2	0.31	<5	<10	261	<5	16	153
55432	<5	0.99	33	226	3	0.32	<5	<10	161	<5	17	141
55433	<5	0.52	32	292	7	0.33	<5	10	200	7	20	136
55434	<5	0.58	28	280	2	0.34	<5	<10	192	<5	19	154
55435	<5	0.36	4	356	<2	0.22	<5	10	34	<5	17	58
55436	<5	0.96	13	229	<2	0.36	<5	10	56	<5	24	130
55437	<5	0.89	14	270	<2	0.39	<5	<10	56	<5	22	113
55438	<5	0.36	45	213	<2	0.16	<5	<10	130	<5	13	97
55439	<5	1.02	20	152	4	0.56	<5	<10	143	<5	7	50
55440	<5	2.74	6	353	8	0.61	<5	10	78	<5	7	60
55441	<5	0.26	25	156	<2	0.09	<5	<10	31	<5	21	120
55442	<5	0.15	22	107	4	0.13	<5	<10	7	<5	19	109
55443	<5	0.97	36	230	3	0.37	<5	<10	10	<5	20	146
55444	<5	0.39	28	107	<2	0.34	<5	<10	40	<5	21	135
55445	<5	0.58	30	126	14	1.40	<5	<10	56	<5	27	183
55446	<5	1.74	43	204	3	0.43	<5	<10	13	<5	16	141
55447	<5	0.66	43	134	<2	0.29	<5	<10	6	<5	18	263
55448	<5	1.62	38	106	3	0.40	<5	<10	82	<5	25	122
55449	<5	0.28	50	159	6	0.21	<5	10	237	<5	18	108
55450	<5	1.22	37	163	<2	0.34	<5	<10	72	<5	19	137

QC	Ag	Al	As	Ba	Be	Bi	Ca	Cd	Co	Cr	Cu	Fe	Ga	Hg	K	Mg	Li	Mn	Mo	Na	Ni	P	Pb
	ppm	ppm	%	ppm	ppm	%	ppm	ppm															
Lower Limit	0.3	0.01	3	7	1	2	0.01	0.3	1	1	0.01	0.01	1	1	0.01	1	1	0.01	1	0.01	1	0.001	3
Method Code	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP	TD-ICP										
GXR-4 Meas	3.6	6.76	102	80	2	15	1.03	0.3	14	51	6540	3.09	16	<1	3.01	1.65	11	154	314	0.48	40	0.131	47
GXR-4 Cert	4.0	7.20	98.0	1640	1.90	19.0	1.01	0.860	14.6	64.0	6520	3.09	20.0	0.110	4.01	1.66	11.1	155	310	0.564	42.0	0.120	52.0
GXR-4 Meas	3.5	6.82	102	91	2	11	1.03	<0.3	13	44	6640	3.11	17	<1	3.36	1.65	10	149	308	0.49	39	0.131	45
GXR-4 Cert	4.0	7.20	98.0	1640	1.90	19.0	1.01	0.860	14.6	64.0	6520	3.09	20.0	0.110	4.01	1.66	11.1	155	310	0.564	42.0	0.120	52.0
SDC-1 Meas	8.98	9	630	3	1.11	19	51	32	5.16	22	<1	2.46	1.03	34	951	1.52	36	0.057	23				
SDC-1 Cert	8.34	0.220	630	3.00	1.00	18.0	64.00	30.000	4.82	21.00	0.20	2.72	1.02	34.00	88.00	1.52	38.0	0.0690	25.00				
SDC-1 Meas	8.52	9	601	3	1.09	18	48	31	4.96	22	<1	2.40	1.00	33	921	1.49	37	0.054	21				
SDC-1 Cert	8.34	0.220	630	3.00	1.00	18.0	64.00	30.000	4.82	21.00	0.20	2.72	1.02	34.00	88.00	1.52	38.0	0.0690	25.00				
GXR-6 Meas	0.5	12.4	306	>1000	<1	2	0.16	<0.3	13	57	68	53.9	28	<1	1.81	0.56	30	110	2	0.09	25	0.037	91
GXR-6 Cert	1.30	17.7	330	1300	1.40	0.290	0.180	1.00	13.8	96.0	66.0	5.58	35.0	0.0680	1.87	0.609	32.0	1010	2.40	0.104	27.0	0.0350	101
GXR-6 Meas	0.4	13.7	249	>1000	1	<2	0.18	<0.3	13	70	5.75	29	<1	1.79	0.61	32	1110	<1	0.09	26	0.035	96	
GXR-6 Cert	1.30	17.7	330	1300	1.40	0.290	0.180	1.00	13.8	66.0	5.58	35.0	0.0680	1.87	0.609	32.0	1010	2.40	0.104	27.0	0.0350	101	
SAR-M(U.S.G.S.) Meas	4.2	6.53	35	776	4	2	0.64	4.9	11	326	3.45	15	3.03	0.50	28	5050	7	1.16	47	0.062	1020		
SAR-M(U.S.G.S.) Cert	3.64	6.30	38.8	801	2.20	1.94	0.61	5.27	10.70	331.0000	2.99	17	2.94	0.50	27.4	5220	13.1	1.140	41.5	0.07	982		
SAR-M(U.S.G.S.) Meas	3.5	6.20	28	712	3	<2	0.63	4.8	10	327	3.31	16	2.79	0.48	29	4980	4	1.11	44	0.061	983		
SAR-M(U.S.G.S.) Cert	3.64	6.30	38.8	801	2.20	1.94	0.61	5.27	10.70	331.0000	2.99	17	2.94	0.50	27.4	5220	13.1	1.140	41.5	0.07	982		
DNC-1a Meas				100				56	242	105					5	5.20					261		
DNC-1a Cert				118				57.0	270	100.00					4						247		
DNC-1a Meas				93				53	128	100					5.20						249		
DNC-1a Cert				118				57.0	270	100.00					141						247		
SBC-11 Meas				19	491	3	2	0.5	21	101	34	25								83			
SBC-11 Cert				25.7	788.0	3.20	0.70	0.40	22.7	109	31.0000	27.0									28		
SBC-1 Meas				25	449	3	4	0.4	23	86	33	28									35.0		
SBC-1 Cert				25.7	788.0	3.20	0.70	0.40	22.7	109	31.0000	27.0									29		
55319.Dng	<0.3	8.84	5	31	<1	<2	3.63	<0.3	23	34	9	7.00	18	<1	0.06	1.77	17	805	2	4.43	5	0.084	<3
55319.Dup	<0.3	9.22	<3	32	<1	3	3.73	<0.3	23	35	11	7.18	18	<1	0.06	1.81	18	825	2	4.52	4	0.087	<3
55328.Dng	<0.3	5.95	6	187	1	4	4.92	<0.3	21	112	16	10.9	26	<1	0.58	0.37	11	1420	<1	2.44	4	0.126	4
55328.Dup	<0.3	6.04	4	187	1	<2	4.89	<0.3	20	98	17	10.8	25	<1	0.58	0.37	11	1370	<1	2.45	3	0.125	<3
55347.Dng	<0.3	7.57	<3	31	<1	7	5.44	<0.3	45	157	98	9.81	20	<1	0.15	3.70	19	1280	3	2.15	72	0.050	<3
55347.Dup	<0.3	8.10	<3	33	<1	3	5.64	<0.3	47	155	107	10.1	21	<1	0.17	3.75	19	1310	<1	2.24	75	0.046	<3
55371.Dng	0.4	7.62	3	175	2	5.81	<0.3	39	64	188	9.99	19	<1	0.30	1.62	17	1570	<1	3.40	7	0.153	<3	
55371.Dup	<0.3	7.83	<3	176	2	5.82	<0.3	38	56	191	9.97	20	<1	0.30	1.62	17	1580	<1	3.45	8	0.158	3	
55374.Dng	0.7	8.06	3	120	2	3	4.95	0.4	46	41	253	8.37	19	<1	0.19	0.88	14	1060	2	4.48	8	0.188	<3
55374.Dup	0.7	8.11	<3	122	2	3	5.02	0.5	47	41	257	8.52	18	<1	0.19	0.89	14	1060	2	4.55	7	0.193	<3
55422.Dng	<0.3	7.63	<3	35	<1	<2	7.42	<0.3	45	97	8.23	16	<1	0.07	3.47	41	1280	<1	2.08	123	0.025	<3	
55422.Dup	<0.3	7.68	<3	35	<1	<2	7.48	<0.3	45	138	102	8.30	16	<1	0.07	3.51	42	1310	<1	2.11	120	0.025	<3
55435.Dng	0.4	5.37	5	491	1	<2	14.2	<0.3	4	69	95	1.96	13	<1	1.96	1.08	10	927	7	2.09	12	0.038	6
55435.Dup	0.4	5.43	<3	496	1	<2	14.3	<0.3	5	71	95	1.94	13	<1	2.01	1.09	10	943	7	2.09	13	0.038	6
55437.Dng	<0.3	6.71	10	155	2	<2	6.79	<0.3	43	38	144	11.2	18	<1	0.19	2.29	16	1880	<1	2.79	10	0.095	<3
55437.Dup	<0.3	6.72	<3	158	<2	<2	6.84	<0.3	43	36	144	11.2	19	<1	0.20	2.29	16	1880	<1	2.76	11	0.096	<3
55447.Dng	<0.3	6.57	3	141	<1	<2	4.97	0.7	37	45	24	13.8	22	<1	0.21	1.91	16	2120	<1	1.98	1	0.059	3
55447.Dup	<0.3	6.58	4	139	<1	<2	4.92	0.5	37	42	27	13.8	24	<1	0.21	1.91	16	2110	<1	1.97	2	0.059	3
Method Blank	<0.3	<0.01	<3	<7	<1	<2	<0.01	<0.3	<1	<1	<0.01	<0.01	<1	<1	<0.01	<1	<1	<0.01	<1	<0.01	<1	<0.001	<3
Method Blank	<0.3	<0.01	<3	<7	<1	<2	<0.01	<0.3	<1	<1	<0.01	<0.01	<1	<1	<0.01	<1	<1	<0.01	<1	<0.01	<1	<0.001	<3
Method Blank	<0.3	<0.01	<3	<7	<1	<2	<0.01	<0.3	<1	<1	<0.01	<0.01	<1	<1	<0.01	<1	<1	<0.01	<1	<0.01	<1	<0.001	<3
Method Blank	<0.3	<0.01	<3	<7	<1	<2	<0.01	<0.3	<1	<1	<0.01	<0.01	<1	<1	<0.01	<1	<1	<0.01	<1	<0.01	<1	<0.001	<3

## QC

Analyte Symbol	Ag	Al	As	Ba	Be	Bi	Ca	Cd	Co	Cr	Cu	Fe	Ga	Hg	K	Mg	Li	Mn	Mo	Na	Ni	P	Pb
Unit Symbol	ppm	%	ppm	ppm	ppm	ppm	ppm	%	ppm	ppm	ppm	ppm	ppm	ppm	%	ppm	ppm	ppm	ppm	ppm	%	ppm	ppm
Lower Limit	0.3	0.01	3	7	1	2	0.01	0.3	1	1	0.01	1	1	0.01	1	1	0.01	1	0.01	1	0.001	3	
Method Code	TD-ICP																						
Method Blank	<0.3	<0.01	<3	<7	<1	<2	<0.01	<0.3	<1	<2	<0.01	<0.3	<1	<0.01	<1	<1	<0.01	<1	<0.01	<1	<1	<0.001	<3
Method Blank	<0.3	<0.01	<3	<7	<1	<2	<0.01	<0.3	<1	<2	<0.01	<0.3	<1	<0.01	<1	<1	<0.01	<1	<0.01	<1	<1	<0.001	<3
Method Blank	<0.3	0.02	<3	<7	<1	<2	<0.01	<0.3	<1	<2	<0.01	<0.3	<1	<0.01	<1	<1	<0.01	<1	<0.01	<1	<1	<0.001	<3

Analyte Symbol	Sb	S	Sc	Sr	Te	Ti	Tl	U	V	W	Y	Zn	Zr
Unit Symbol	ppm	%	ppm	ppm	ppm	%	ppm	ppm	ppm	ppm	ppm	ppm	ppm
Lower Limit	5	0.01	4	1	2	0.01	5	10	2	5	1	1	5
Method Code	TD-ICP	TD-ICP											
GXR-4 Meas	<5	1.74	8	212	4	0.29	<5	<10	88	41	13	73	37
GXR-4 Cert	4.80	1.77	7.70	221	0.970	0.29	3.20	6.20	87.0	30.8	14.0	73.0	186
GXR-4 Meas	<5	1.75	8	211	8	0.29	<5	<10	86	39	13	72	36
GXR-4 Cert	4.80	1.77	7.70	221	0.970	0.29	3.20	6.20	87.0	30.8	14.0	73.0	186
SDC-1 Meas	<5	17	182	0.23	<5	<10	57	<5	57	108	36		
SDC-1 Cert	0.54	17.00	180.00	0.606	0.70	3.10	102.00	0.80		103.00	280.00		
SDC-1 Meas	<5	16	176	0.18	<5	<10	50	<5	50	106	37		
SDC-1 Cert	0.54	17.00	180.00	0.606	0.70	3.10	102.00	0.80		103.00	280.00		
GXR-5 Meas	<5	0.01	25	36	3	<5	<10	179	<5	11	128	93	
GXR-5 Cert	3.60	0.0160	27.6	35.0	0.0180	2.20	1.54	186	1.90	14.0	118	110	
GXR-5 Meas	<5	0.02	26	40	<2	<5	<10	130	<5	10	133	62	
GXR-5 Cert	3.60	0.0160	27.6	35.0	0.0180	2.20	1.54	186	1.90	14.0	118	110	
SAR-M (U.S.G.S.) Meas	<5	10	154	3	0.38	<5	<10	67	18	35	963		
SAR-M (U.S.G.S.) Cert	6.0	7.83	151	0.96	0.38	2.7	3.57	67.2	9.78	28.00	930.0		
SAR-M (U.S.G.S.) Meas	<5	9	150	4	0.28	<5	<10	54	13	34	925		
SAR-M (U.S.G.S.) Cert	6.0	7.83	151	0.96	0.38	2.7	3.57	67.2	9.78	28.00	930.0		
DNC-1a Meas	<5	31	136	0.30	0.29			144		15	64	34	
DNC-1a Cert	0.96	31	144.0	0.29				148.00		18.0	70.0	381.000	
DNC-1a Meas	<5	30	130	0.29				141		14	61	32	
DNC-1a Cert	0.96	31	144.0	0.29				148.00		18.0	70.0	381.000	
SBC-1 Meas	<5	20	172	0.49	<5	<10	207	7	28	185	104		
SBC-1 Cert	1.01	20.0	178.0	0.51	0.89	5.76	220.0	1.60	36.5	186.0	134.0		
SBC-1 Meas	<5	21	186	0.54	<5	<10	225	<5	29	192	107		
SBC-1 Cert	1.01	20.0	178.0	0.51	0.89	5.76	220.0	1.60	36.5	186.0	134.0		
55319 Orig	<5	0.15	20	127	8	0.41	<5	20	139	<5	15	80	88
55319 Dup	<5	0.15	21	132	4	0.46	<5	20	150	6	16	82	93
55328 Orig	<5	0.55	29	103	3	0.54	<5	<10	11	<5	67	105	102
55328 Dup	<5	0.54	30	102	9	0.44	<5	<10	8	68	103	62	
55347 Orig	<5	0.73	35	168	7	0.90	<5	<10	303	<5	25	102	37
55347 Dup	<5	0.75	38	173	6	0.52	<5	<10	218	<5	28	105	28
55371 Orig	<5	0.83	7	323	5	0.46	<5	10	47	<5	25	115	48
55371 Dup	<5	0.84	7	325	10	0.42	<5	10	38	<5	25	116	49
55374 Orig	<5	1.73	<4	361	3	0.54	<5	20	73	<5	23	176	115
55374 Dup	<5	1.76	4	366	8	0.59	<5	20	81	<5	23	181	119
55422 Orig	<5	0.16	35	126	<2	0.19	<5	<10	116	<5	15	87	<5
55422 Dup	<5	0.16	35	128	2	0.29	<5	<10	155	<5	16	85	<5
55435 Orig	<5	0.36	4	366	<2	0.22	<5	10	34	<5	17	58	173
55435 Dup	<5	0.36	4	366	<2	0.22	<5	10	33	<5	17	58	155

**Activation Laboratories Ltd.****A14-09584****Report:**

Analyte Symbol	Sb	S	Sc	Sr	Ta	Ti	Tl	U	V	W	Y	Zn	Zr
Unit Symbol	ppm	%	ppm	ppm	ppm	%	ppm						
Lower Limit	5	0.01	4	1	2	0.01	5	10	2	5	1	1	5
Method Code	TD-ICP												
55437 Orig	<5	0.90	13	267	6	0.37	<5	<10	55	<5	22	105	12
55437 Dup	<5	0.88	14	272	<2	0.41	<5	10	57	<5	22	121	17
55447 Orig	<5	0.66	43	134	2	0.29	<5	<10	7	<5	18	264	5
55447 Dup	<5	0.66	43	134	<2	0.29	<5	<10	6	<5	18	262	5
Method Blank	<5	<0.01	<4	<1	<2	<0.01	<5	<10	<2	<5	<1	<1	<5
Method Blank	<5	<0.01	<4	<1	<2	<0.01	<5	<10	2	<5	<1	<1	<5
Method Blank	<5	<0.01	<4	<1	<2	<0.01	<5	<10	4	<5	<1	<1	<5
Method Blank	<5	<0.01	<4	<1	<2	<0.01	<5	<10	<2	<5	<1	<1	<5
Method Blank	<5	<0.01	<4	<1	<2	<0.01	<5	<10	<2	<5	<1	<1	<5
Method Blank	<5	<0.01	<4	<1	<2	<0.01	<5	<10	<2	<5	<1	<1	<5
Method Blank	<5	<0.01	<4	<1	<2	<0.01	<5	<10	<2	<5	<1	<1	<5
Method Blank	<5	<0.01	<4	<1	<2	<0.01	<5	<10	<2	<5	<1	<1	<5